

SETUP & OPERATION MANUAL

FEATURES

Sturdy welded steel frame & precision balanced wheels with replaceable tires.

Easy-to-assemble open-base steel stand.

Precision easy-adjust European style blade guide bearings included.

Two cutting speeds for excellent results in either hard or soft woods.

Miter gauge with aluminum crosscut fence included.

Deluxe dual-position rip fence system.

Hinged doors and easily accessible blade tension knob, for fast blade changes and adjustments.

Extra-large 21 1/2 x 15 3/4 cast-iron table.

Smooth running heavy-duty 2/3 HP motor.

Safety lock-out switch with removable key to prevent unauthorized use.

Multi-size dust port fits 4", 3", or 2" hose.

SPECIFICATIONS

- Wheel size
12" (305 mm)
- Wheel speeds (2)
445 & 970 rpm
- Blade speeds (2)
1444 & 3150 lin. fpm
- Maximum blade width
3/4" (20 mm)
- Minimum blade width
1/8" (3 mm)
- Blade length
88" (2240 mm)
- Table size
21 1/2" x 15 3/4" (548 x 400 mm)
- Table tilt
0° to 45° (right)
- Table height
37 3/8" (950 mm)
- Maximum width of cut
12" (305 mm)
- Maximum depth of cut
6 1/2" (165 mm)
- Dust port
4", 3" and 2" (102, 76 or 51mm)
- Base dimensions (l x w)
18 1/4" x 15 3/4" (465 x 400 mm)
- Motor
2/3 HP, 120 V, 6,4 A
- Weight
165 lbs (75 kg)

12" WOOD CUTTING BANDSAW



MODEL #90-040

