



# TEXTURED DECKOVER® SOLID COLOR COATING

## NO. 5005



### PRODUCT INFORMATION

BEHR PREMIUM Textured DECKOVER® Coating is an innovative, waterproofing solid color coating that will bring your old, weathered wood or concrete back to life. The advanced 100% acrylic resin creates a durable coating on your tired deck, rejuvenating its look. Textured DECKOVER Coating is designed to conceal splinters & cracks up to 1/4" and creates a textured, slip-resistant finish. It is available in a selection of popular wood and concrete custom colors.

### RECOMMENDED USES:

Recommended for properly prepared interior and exterior weathered or cracked horizontal and vertical surfaces such as:

- Wood
- Composite
- Concrete

Do not use on drivable surfaces such as garage floors and driveways.

### PRODUCT SPECIFICATIONS:

**Tint Bases/Max Tint Load:**

No. 5005 116 oz./14 oz.

**Resin Type:** 100% Acrylic

**Weight per Gallon:** 11.5 lbs

**% Solids by Volume:** 51%

**% Solids by Weight:** 65%

**VOC:** <50 g/L

**Flash Point:** N/A

**Viscosity:** 95-105 KU (Paste Paddle)

**Recommended Film Thickness:**

Wet: 21 mils Dry: 11 mils @ 75 Sq. Ft./Gal.  
per 2 coats (5.5 mils Dry per coat)

**Coverage:** 75 Sq. Ft./Gal. 2 coats required.

### APPLICATION:

**Brush:** Nylon/polyester brush

**Roller:** 1/4" - 1/2" nap

DO NOT USE WITH AIRLESS SPRAYER

**Dry Time:** @ 77° & 50% RH

**To Recoat:** 4-6 hours

**Light Foot Traffic:** 24-48 hours

**Full Cure:** 72 hours

- For nail holes and cracks up to 1/4", completely fill in with DECKOVER Coating using a nylon/polyester brush and allow to dry prior to rolling. Deep nail holes and cracks may require additional filling.
- Use pressure while rolling and apply generously.
- Avoid painting if humidity is expected to be greater than 80%
- 2 coats required

### SURFACE PREPARATION:

**The following steps and products are required:**

(Proper surface preparation is required.) Exterior Wood Surfaces: Replace rotting or unstable boards and remove loose splinters. For exterior failing coatings or to remove loose wood fibers, use a product such as BEHR PREMIUM® No. 64 Wood Stain & Finish Stripper followed by BEHR PREMIUM No. 63 All-In-One Wood Cleaner to neutralize the wood. When No. 64 is not needed, a product such as No. 63 MUST be used to remove mill glaze and clean the exterior wood surface. After using either No. 64 or No. 63, rinse thoroughly with a garden hose or pressure washer. When rinsing with a pressure washer, use the broadest spray pattern while keeping the nozzle at least 24" away from the surface. Allow the area to dry at least 24 hours before coating. Lightly sand to remove remaining wood fibers/fuzz.

**Concrete Surfaces:** Avoid areas that are structurally weak or subject to hydrostatic pressure above 8 psi. Allow new surfaces to cure for 30 days. Use a product such as BEHR PREMIUM No. 992 Concrete & Masonry Paint Stripper to strip peeling coating. Use a product such as BEHR PREMIUM No. 991 Concrete & Masonry Cleaner & Etcher to clean and etch uncoated concrete or No. 990 Concrete & Masonry Degreaser & Cleaner on sound, coated surfaces prior to coating. See behr.com for additional product information.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

COMPLIES WITH THE BELOW AS OF 3/1/2015			
SCAQMD	YES	LADCO	YES
CARB	YES	AIM	YES
LEED v.3 (2009) <sup>†</sup>	YES	MPI#	127
OTC	YES	FLAME SPREAD/CLASS A	YES

### CLEAN UP:

Clean all tools and equipment with clean water. For proper disposal of empty containers and unused product, contact your household refuse collection service.

### CAUTIONS/LIMITATIONS:

- Protect from freezing
- Do not use without the addition of tinting colorants
- Do not use if rain is expected within 24 hours
- DO NOT THIN PRODUCT
- Avoid applying paint in direct sunlight or hot surfaces
- Test product for color on a small hidden area before proceeding
- Painted surfaces may become slippery when wet
- Shelf life under normal conditions is two years (unopened containers)
- Do not use on drivable surfaces such as garage floors and driveways
- Temperature Range: 50-90°F (10-32°C)

### GENERAL INFORMATION:



**Warning!** Causes eye and skin irritation. Wear protective clothing, gloves, eye, and face protection. Do not eat, drink, or smoke when using this product. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

**First aid: If in eyes:** Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists. **If on skin:** Wash with plenty of soap and water.

**If swallowed:** Rinse mouth and get medical attention if you feel unwell.

