

THE HOME DEPOT

Inspection Requirement

ATLANTA, GEORGIA 30339-4024

REPORT NO.: 85122850625V08

SKU#:	682292/USA 683323/USA 684496/USA 715938/USA 718936/USA	MODEL#:	33-HB-1 33-HB-2 33-HB-4 33-F10-4 33-F9-2	DEPT. #:	59	COE #:	1
SUPPLIER:	YERSH			SUPPLIER	: # :	123	25
FACTORY:	XIAMEN UPTRADE	FURNISHING	INDUSTRIAL CO.,	FACTORY #: 2004423			123
FACTORY ADDRESS:	NO.5-11, HUATAI RO FUJIAN CHINA	OAD, HULI DI	STRICT XIAMEN	FACIONI	#•	2004	423
	·=	PC 1-3/8" HB O		1		1	

MSL 2PC 1-3/8 HB MAH

MSL 2PC 1-3/8" FMARBLE MAH MSL 2PC 1-3/8" FMARBLE OAK



PRODUCT DESCRIPTION:





33-HB-1

33-HB-2

33-HB-4





33-F10-4

IMPORTANT: The product photos are not intended as the color reference.

This product requirement contains the following documents:

- 1. Product Requirements
- 2. Packaging Requirements
- 3. Product Documentation
- 4. Product Photos
- 5. Inspection Plan
- 6. Defect classification
- 7. Revision history

Form Owner: THD QA - Issue Date: 6/23/08 - Version #: 4

Proprietary & Confidential

The Home Depot Company Information

	Prepared by:	Nana Liu	Reviewed by:	Nancy Du	Approved by:	Brian Tam)		
HANDER TO SERVICE TO S	Date:	Dec 21, 2012	Date:	Dec 21, 2012	Date:	Dec 21, 2012		
BUREAU VERITAS	Con	trol-Subconti	rol Number:	8034.3442.4107.51717 8034.3442.4107.51718 8034.3442.4107.51720 8034.3442.4107.51731 8034.3442.4107.51732				

1. Product Requirements

Item#	Item	Qty	Style / Feature / Finish / Color	Dimension / Measurement	Tolerance	Material
33-HB- 1	MSL 2PC 1- 3/8" HB WH	4.53inLx3.78inWx3.78inH		Dimension: 4.53inLx3.78inWx3.78inH		WOOD
33-HB- 2	MSL 2PC 1- 3/8 HB OAK	2	OAK	Weight: 0.28lbs Dimension: 4.53inLx3.78inWx3.78inH Weight: 0.28lbs	For dimension:	WOOD
33-HB- 4	MSL 2PC 1- 3/8 HB MAH	2	MAHOGANY	Dimension: 4.53inLx3.78inWx3.78inH Weight: 0.28lbs	+/-5%; For weight: +/-10% Note: HD	WOOD
33- F10-4	MSL 2PC 1- 3/8" FMARBLE MAH	2	FMARBLE MAH	Dimension: 2.68inLx3.98inWx2.68inH Weight: 0.97lbs	agree to primarily define +/- 10% weight	WOOD/ MARBLI
33-F9-2	MSL 2PC 1- 3/8" FMARBLE OAK	2	FMARBLE OAK	Dimension: 2.68inLx3.98inWx2.68inH Weight: 0.97lbs	tolerance in our IR document, mainly focus on Poles, for other accessories such as Brackets, Rings, product weight is only for reference.	WOOD/N ARBLE
1.2 PRI	E-PURCHASE T	ESTING	G RESULT			
achieve a "Good" i Home Do Purchase Program "unsatisf	a rating of under The epot's Pre- e Testing	PPT RE 851228: 851229: 851228:	20570	RATING: GOOD GOOD GOOD	REMARK:N/A	
1.3 PEF	RFORMANCE T	TESTS				
Tes	t Property		Test Requ	irement	Comn	nents

PDQ CHECK	Check to make sure all PDQ are designed properly and sturdy enough to hold merchandise. First, remove all the items from the PDQ. Then arrange neatly per manufacturer's design. Repeat upper step 10 times.	Nil
Moisture Content Test	The moisture content of wood product intended for indoor use	Nil
of natural wood	shall be within 4%-13%; The moisture content of wood	
material only	product intended for outdoor use shall be within 8% - 12%;	
Coating Adhesion Test on Coating / Painting Component	1. Cross Hatching Test: Coated metal items shall be rated per the scale specified in the standard when tested as appropriate. Cut coating as specified, apply tape to cuts, then remove tape after 2 min and examine for removal of coating from substrate. Photograph if any plating / finish is removed. Select cutting method as follows: Use the cutter to make parallel cut so that space the cuts 2mm apart and make six cuts: 6 lines (columns) x 6 lines (row) lead to 2mm x 2mm x 25 grids.	Nil
	2. Tape Test: Coated nonmetallic component: press the adhesive tape on coating / painting surface apply tape to cuts, remove tape after 2 min and examine for removal of coating from substrate.	

2. Packaging Requirements

Label Location	Refer to Section 3				
Sensormatic Tags	Reference code 1.4.3.1 & 1.4.3.2 in BV IR 600000-N/A				
UPC/UCC on unit package I 2 of 5 number on master carton (if available)	Reference code 1.4.1.6 & 1.4.1.10 in BV IR 600000, the number should is: UPC/UCC number: 33-HB-1: 4713105460131 33-HB-2: 4713105460162 33-F10-4: 4713105460469 33-F9-2: 4713105460476 I 2 of 5 number: 33-HB-1: 14713105460138 33-HB-2: 14713105460145 33-HB-4: 14713105460169 33-F10-4: 14713105460466 33-F9-2: 14713105460473				
Country of Origin	Reference code 1.4.1.2 in IR 600000 Country of Origin: china				
Importer name and	Reference code 1.4.1.5 in IR 600000				
address	Importer name and address: refer to IR600000- USA				
Bilingual requirement for caution and warning statements and any inserts or instruction manual	Reference code 1.4.1.7 in IR 600000				
Safety listing Label	Reference code 1.4.1.6 in IR 600000 or Refer to section 3.1				
Instruction Sheet	Clear assembly / operating instructions (as applicable) should be identical to those shown in Sec 3				
Warranty Card	N/A				
SWPM (Solid wooden packing material) is used for product packing	No				
Unit package	Reference code 1.4.in IR 600000				
Unit package Size	(L) x (W) x (H)(cm): 33-HB-1/33-HB-2/33-HB-4: 2.76inL x 4.13inW x 7.9inH 33-F10-4/33-F9-2: 3.23inL x 6.18inW x 6.81inH				
Method	33-HB-1: 1 pair per bag, 4 bags per master carton 33-HB-2: 1 pair per bag, 4 bags per master carton 33-HB-4: 1 pair per bag, 4 bags per master carton 33-F10-4: Regular slotted container constructed of single wall-corrugated board, glued at seam joints and flaps are secured by wide tape. Two inner cartons each constructed of single wall-corrugated board are placed inside the master container. Two finials are placed inside each inner carton and protected by single wall-corrugated protector with screw/plastic sheet securing. 33-F9-2: Regular slotted container constructed of single wall-corrugated board, glued at seam joints and flaps are secured by wide tape. Two inner cartons each constructed of single wall-corrugated board are placed inside the master container. Two finals are placed inside each inner carton and protected by single wall-corrugated protector with screw/plastic sheet securing.				

33-HB-1&33-HB-2 & 33-HB-4

ECN 17751, Change the rivet to the smoother one. ECN 17746, Change the rivet to the smoother one.











No photo

33-F10-4 & 33-F9-2





	Packaging Specification						
SKU No.	682292 683323 684496	Model No.	33-HB-1 33-HB-2 33-HB-4				
Piece count	2	Case count	4				
Package component description:	Single-Wall corrugated	Single-Wall corrugated	/				
Component Material:	mponent Material: Corrugated		PVC Bag				
Packaging component per SKU	2/4	2/4	/				
Component dimension: (in, L x W x D)	5.12x13.19x6.30	12.4x4.53x5.91	2.76 x 4.14 x 7.9				
Outer Shipping Case (Tick one per SKU)	[x]	[x]	[]				
Outbound Load Configuration: (select one)	[x] Floor stack [] Pallet [] Slip sheet	[] Crate [] others,				
Gross weight of shipping carton: (lb, includes product)	2.84	Pallet or crate size: (inch, Length X Width, if applicable)	N/A				

	Packaging Specification						
SKU No.	715938	Model No.	33-F10-4				
Piece count	2	Case count	2				
Package component description:	Master Carton Single-Wall corrugated	Unit Packaging Single-Wall corrugated	/				
Component Material:	Corrugated	Corrugated	/				
Packaging component per SKU	2/2	/	/				
Component dimension: (in, L x W x D)	6.69 x 7.09 x 7.95	3.23 x 6.18 x 6.81	/				
Outer Shipping Case (Tick one per SKU)	[X]	[]	[]				
Outbound Load Configuration: (select one)	[X] Floor stack [] Pallet [] Slip sheet	[] Crate [] others,				
Gross weight of shipping carton: (lb, includes product)	4.87 lb.	Pallet or crate size: (inch, Length X Width, if applicable)	N/A				

	Packaging Specification						
SKU No.	718936	Model No.	33-F9-2				
Piece count	2	Case count	2				
Package component description:	Master Carton Single-Wall corrugated	Unit Packaging Single-Wall corrugated	/				
Component Material:	Corrugated	Corrugated	/				
Packaging component per SKU	2/2	/	/				
Component dimension: (in, L x W x D)	6.69 x 7.09 x 7.95	3.23 x 6.18 x 6.81	/				
Outer Shipping Case (Tick one per SKU)	[X]	[]	[]				
Outbound Load Configuration: (select one)	[X] Floor stack [] Pallet [] Slip sheet	[] Crate [] others,				
Gross weight of shipping carton: (lb, includes product)	4.87 lb.	Pallet or crate size: (inch, Length X Width, if applicable)	N/A				

NOTES:

- Other than the specific Packaging Requirement above, for General Packaging Requirement please refer to IR600000).
- For any changes of marking, printing, parts and /or components, the vendor should inform The Home Depot.
 The changes of parts or components may require re-submitting for evaluation.
- Any changes of marking, printing, parts and /or components without informing The Home Depot would be counted as a violation of this Product Requirement.

3. Product Documentation









1-3/8 IN FINIAL REMATE DE 3,4 CM

715 938

ANTIQUE MAHOGANY FINISH ACABADO EN CAOBA ANTIGUO

FOR USE WITH 1-3/8 IN POLES PARA USAR CON POSTES DE 3,4 CM

MADE IN CHINA HECHO EN CHINA

DISTRIBUTED BY:
DISTRIBUIDO POR:
HOME DEPOT
2455 PACES FERRY RD., N.W.
ATLANTA, GA 30339

FOR ASSISTANCE, CALL: SI NECESITA AYUDA, LLAME AL: 1-877-527-0313 HOMEDEPOT.COM

MARTHA STEWART LIVING™ and the MARTHA STEWART Circle Logo™ are trademarks of Martha Stewart Living Omnimedia, inc. Copyright © Martha Stewart Living Omnimedia, inc. All rights reserved.

Recicla



715 938

ANTIQUE MAHOGANY FINISH ACABADO EN CAOBA ANTIGUO

FOR USE
WITH 1-3/8 IN
POLES
PARA USAR CON
POSTES DE 3,4 CM


MADE IN CHINA HECHO EN CHINA

DISTRIBUTED BY: DISTRIBUIDO POR: HOME DEPOT

2455 PACES FERRY RD., N.W. ATLANTA, GA 30339

FOR ASSISTANCE, CALL: SI NECESITA AYUDA, LLAME AL: 1-877-527-0313 HOMEDEPOT.COM

MARTHA STEWART LIVING™ and the MARTHA STEWART Circle Logo™ are trademarks of Martha Stewart Living Omnimedia, Inc. Copyright © Martha Stewart Living Omnimedia, Inc. All rights reserved.



33-F9-2



1-3/8 IN FINIAL REMATE DE 3,4 CM

718 936

HERITAGE OAK FINISH ACABADO EN ROBLE HERITAGE

FOR USE WITH 1-3/8 IN POLES PARA USAR CON POSTES DE 3,4 CM


MADE IN CHINA HECHO EN CHINA

DISTRIBUTED BY:
DISTRIBUIDO POR:
HOME DEPOT
2455 PACES FERRY RD., N.W.
ATLANTA, GA 30339

FOR ASSISTANCE, CALL: SI NECESITA AYUDA, LLAME AL: 1-877-527-0313 HOMEDEPOT.COM

MARTHA STEWART LIVING™ and the MARTHA STEWART Circle Logo™ are trademarks of Martha Stewart Living Omnimedia, inc. Copyright © Martha Stewart Living Omnimedia, inc. All rights reserved.





Components' Net W	Components' Net Weight									
Product Description	PQOB INDEX#		SKU#		REPORT#		I 2 of 5	PCS per sale	Component's net weight (g)	
1 Toddet Description			SKU#		KEPORI#		(外箱條碼)	unit	螺絲	螺絲包
MSL 2PC 1-3/8" HB WH	8034.3442.	.4107.51717	7 682292	2	(8512)285-0625		14713105460138	1 pair	14.80	3.90
MSL 2PC 1-3/8" HB OAK	8034.3442.	.4107.51718	8 683323	3	(8512)285-0625		14713105460145	1 pair	14.80	3.90
MSL 2PC 1-3/8" HB MAH 8034.3442.4107.51720		0 684496	684496 (8512)285-0625			14713105460169	1 pair	14.80	3.90	
Product Description		QOB DEX#	SKU#		REPORT#		12 of 5 (外箱條碼)	PCS per sal unit	net w	oonent's eight (g) 頗釘
MSL 2PC 1-3/8" FMARBLE MAH		1.3442. 7.51731	715938	715938 (8512)292-0		147	713105460466	1 pair	7	.90
MSL 2PC 1-3/8" FMARBLE OAK		1.3442. 7.51732	718936	(85	12)289-0923	147	713105460473	1 pair	7	.90

4. Product Photos



IMPORTANT: The product photos are not intended as the color reference

5. Inspection Plan

5.1 General Inspection Requirement

> Product:

- ♦ Must be without any unsafe defect;
- ♦ Should be free of Cosmetic/Aesthetic defects such as: damaged/broken parts/pieces, scratches, cracks, etc.;
- ♦ Must conform to the country of destination's legal regulations;
- ♦ The unit should comply with client's requirement / approved sample (appearance and function);
- ♦ Marking(s) / label(s) on unit should be clear and should comply with legal requirements.
- ♦ For Marbles:
 - Marble's surface should be smooth.
 - Obvious crackle mark is not accepted. (As fingernail could insert into the crackle and can fell the crackle, it is not acceptable.)
 - Choose similar texture as a pair
 - Refer to THD approved boundary sample for the whole color and appearance effect.

> Packaging:

- ♦ All units will be adequately packaged, and constructed from suitably robust materials, such that it arrives to stores in a sellable condition;
- ♦ The packaging material can protect the goods from damage during transportation;
- ♦ The shipping mark, bar code, label (such as price label), should conform to client's spec and/or approved samples;
- ♦ The packaging should comply to client's requirement / approved sample;
- ♦ Text of illustration, instruction, label and warning statement etc. must be clearly printed in user's language;
- ♦ The illustration, instruction and claim on the packaging artwork / labels must conform to the product appearance and its actual performance;
- ♦ The method and material of pallet / crate etc. should be approved by client.

> Inspection Standard Adopted:

♦ Refer to "THD Inspection Sampling Tool"

Sample Size determination:

- ♦ The Inspection Level Shall refer to Most Updated Switching Rules of The Home Depot.
- ♦ Please Refer to table 5.3 to determine sample size for each audit area
- ♦ Please use "THD Inspection Sampling Tool" to generate the appropriate each SKU sample size for every PSI, which includes multiple SKUs combined in one PSI lot.
- ♦ For the inspection plan is Fix sample size, each SKU shall be drawn according to the required fix sample quantity which cannot be combined.

Acceptable Quality Level:

- ♦ Critical Non-conformity is not allowed
- ♦ AQL 1.0 (or special approved by THD) For Major Non-Conformity
- ♦ AQL 4.0 (or special approved by THD) For Minor Non-Conformity

For checking item that adopt "Fix sample size", nonconformity is not allowed.

General defect classification:

♦ Critical Defect

 Defects that could result in hazardous or unsafe conditions for individuals using or maintaining the product as well as defects contravening legal regulations.

♦ Major Defect

• Functional defects reducing the usability or solidity of the product as well as obvious visual defects reducing the sales value of the product.

♦ Minor Defect

 Defects that are unlikely to reduce the use of the product, but nevertheless may influence the sale.

For random inspection, the following rules are applied:

- ♦ If the same sample has several defects, only the most serious defect is counted.
- ♦ Samples with defect have to be replaced or repaired; In the case of critical defects, the entire shipment must be rejected.

5.2 Equipment List

SP Equipment	Factory Equipment
1. Metal tape	1. Weight scale
2. Bar code reader	2. Sandbags or other loading weights
3. 3M tape/ruler/cutter	3. Assembly tools
4. Moisture content meter	

5.3 Inspection Checklist

Item code	Details	Sampling size
1	Packaging Check	
A	Appearance of master carton	At least the square root of
В	Shipping mark	the total number of
С	Strapping method of master carton	shipping package units, or
D	Pack size	otherwise defined by client, And check all cartons/ pallets/crates that were selected for sampling.
2	Aesthetics / Appearance Check	
A	Instruction (sheet)/warning/warranty	Inspection Level ###
В	Appearance of unit	
С	Accessories	
D	Unit packaging	
3	Bar Code Verification	Inspection Level ###
4	Data Measurement and Test	
A	Size and weight of unit	S-1 per shipment lot, but at
В	PDQ check	least 2 pcs per SKU if
С	Moisture Content Test of natural wood material only	quantity of related SKU exceeds sample size according to S-1.
D	Coating Adhesion Test on Coating / Painting Component	2 Samples per SKU

Note: ### - Shall Refer to Most Updated Switching Rules of The Home Depot.

6. Defect Classification

Item code	Details	Defecti	Defective Classification			
		Critical	Major	Minor		
1	Packaging Check					
Α	Appearance of master carton					
	Damaged / deteriorative/wet		✓			
	Open end is not sealed securely		✓			
	Wrong flute direction of carton		✓			
В	Shipping mark					
	• For carton, shipping label and/or pallet/crate, shipping		✓			
	label less than requirement					
	Wrongly in content and format		✓			
C	Strapping method of master carton					
	Wrong strapping method was used		✓			
D	Pack size					
	The actual quantity does not match requirement of		✓			
	package					
2	Aesthetics / Appearance Check					
Α	Instruction (sheet)/warning/warranty					
	Dirt / scratch / unclear / illegible / wrong / damaged /		\checkmark			
	wrinkled/peeled/detached/smeared/displaced, will cause					
	unsaleable, misunderstanding of reader, information					
	missing etc.)					
	• Dirt / scratch / unclear / illegible / wrong / damaged /			√		
	wrinkled/peeled/detached/smeared/displaced, will not					
	affect sales, although illegible but will not cause					
	information incompletion etc.)					
	Misleading/incorrect descriptions/claims		√			
	Wrong label / Instruction used		✓			
	Missing instruction/warning/warranty/label/marking	✓				
	sheet (will cause safety issue)					
	Missing instruction/warning/warranty shoot/lebel/gording (will not source on faturisque)		v			
В	sheet/label/marking (will not cause safety issue)					
Б	Appearance of unit	✓				
	Non functional sharp point and sharp edge (May injure customer)	•				
	customer) • Live insect/infestation	✓				
		∨ ✓				
	Knives, blades, needles and similar sharp foreign object contamination					
	F	+	√			
	Wyner and the second the second		<u> </u>			
	Donato a haireala		<u> </u>			
	De an acating all alala		•			
	7 / 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		√	•		
	Loose/poor connection between nook and frame		•			

Item code	Details	Defective Classification		
		Critical	Major	Minor
	Deformed, damaged, broken, cracked, rusty mark, dead knot		√	
	Obvious scratched, dirty mark, chipped, glue mark		✓	
	Slight scratched, dirty mark, chipped, glue mark			✓
	Rough on surface		✓	
	Missing piece per set		✓	
	Rusted / Oxidation / corrosion on metal parts		✓	
	Screw / hooks loosen and causing some parts loosed		✓	
	Incorrect plating on metal part		✓	
	Any missing parts or wrong type parts		✓	
	Detached/ missing components		✓	
	Detached/ missing components		✓	
	Hard to adjust length		✓	
С	For Marbles:			
	Marble's surface is not smooth.			✓
	Obvious crackle mark. (As fingernail could insert into the	Fail	the shipm	ent
	crackle and can fell the crackle, it is not acceptable.)		r	
	Texture for a pair is not similar			✓
	The whole color and appearance effect not comply with THD approved boundary sample.	Fail	Fail the shipment	
D	Accessories			
	Missing or incorrect accessories		✓	
	Mismatched accessory		✓	
Е	Unit packaging			
	Dirt / dust /scratches / damage / deformation on labeling or packaging material that will affect selling		✓	
	Dirt / dust /scratches / damage / deformation on labeling or packaging material that will not affect selling			√
	Insufficient protection to product that will cause product damage.		✓	
	Missing "Country of origin" or "Distributor or importer's name and post address" marking or label (single unit)		✓	
	Missing "Country of origin" or "Distributor or importer's name and post address" marking or label (whole lot of certain SKU)	Fail	Fail the shipment	
	Wrong size/style/color assortment within one retail unit		✓	
3	Bar Code Verification			
	Bar code can not be scanned		✓	
	Bar code label is damaged but still can be scanned			✓
	Two bar code labels at same panel of selling package and may lead to wrong payment by double scanning.		√	
	Wrong bar code label is used (single unit)		√	
	Wrong bar code label is used (whole lot of certain SKU)	Fail	the shipm	ent

Item code	Details	Defective Classification		
		Critical	Major	Minor
	Bar code No. on unit does not match PO list		✓	
4	Data Measurement and Test			
A	Size and weight of unit			
	Measured data is out of tolerance		✓	
В	PDQ check			
	Breakage of PDQ or excessive dislocation of foam particles from the display		✓	
С	Moisture Content Test of natural wood material only			
	Moisture content exceeds the standard		✓	
D	Coating Adhesion Test on Coating / Painting Component			
	 Removal of coating is equal or more than 15% after Cross Hatching Test or / and Specimen falls down after Tape test. 	Rej	ect the shi	pment

Note 1: The above described defects are those most commonly found, but not necessarily cover all possible defects.

And the defective classification is for reference only. The final decision of the defective classification would be decided by the inspector.

Note 2: The checking and defect finding evaluation should be conducted at a distance around 76 cm (when an adult extends his hand forward, normally it is distance from eye to tip of middle finger), the time duration for one position is around 3-5 seconds.

7. Revision History

DATE	REVISION	REVISED BY	APPROVED BY
Dec 21, 2012	Draft IR	Nana Liu	Nancy Du
Dec 21, 2012	V00,Initial Released	Nana Liu	Nancy Du
Dec 24, 2012	V01, per customer comments: 1) Updated the product photo for 33-HB-2/33-HB-4/33-F10-4/33-F9-2 on page 1 & 17; 2) Updated the qty to 2 on page 3; 3) Updated the unit package size on page 5; 4) Updated the packaging specification for 33-F10-4/33-F9-2 on page 10-11; 5) Only print barcode on main mark per ECN 15719 on page 16; 6) Updated the tolerance on page 3; 7) Added all related information for the moisture content test; 8) Added the components' net weight on page 17; 9) Added the Finger joints & Pole curvature degree control test on page 26.	Sally Fan	Nancy Du
Dec 27, 2012	V02, Updated the product weight for model#33-HB-2/33-HB-4 as per customer comments.	Sally Fan	Nancy Du
Jan 07, 2013	V03, Updated the unit package size and PVC Bag size as per customer comments.	Sally Fan	Nancy Du
Mar 27, 2013	V04, Updated the product photo and gross weight for 33-F10-4 & 33-F9-2 as per vendor's request.	Sally Fan	Nancy Du
Mar 29, 2013	V05, Per vendor's request, 1) Added the weight tolerance on page 2; 2) Added ECN 15474, pack size change from 4 packs per case to 2 packs for model# 33-F10-4 & 33-F9-2 by recording; 3) Added the Marble PSI standard in part 5 & 6.	Sally Fan	Nancy Du
Apr 02, 2013	V06, 1) Updated the product photo for model#33-HB-4; 2) Updated the product dimension for model#33-HB-1; 3) Updated the product color for model#33-HB-4; 4) Updated the package method and photos for model#33-F10-4 & 33-F9-2 as per customer comments.	Sally Fan	Nancy Du
Jul 25, 2013	V07, Changed the rivet of the package to the smoother one per ECN 17751 for 33-HB-1&33-HB-2 & 33-HB-4.	Aleena Feng	Nancy Du
Sep 20, 2013	V08, Change the rivet to the smoother one as per ECN 17746,	Sally Fan	Nancy Du

Additional tests

^{1.} Finger joints: for 6' poles within 2 finger joints; for 8' poles within 3 finger points. No obvious joint mark and color aberration.

^{2.} Pole curvature degree control: 6' poles within 5mm, 8' poles within 7mm.