

The Pro's Choice Since 1936

SAKRETE®

Paver Set Polymeric Sand

SAKRETE® Paver Set® Sand is a mixture of sand and special additives for paving stone joints. Engineered to resist wind, rain, freezing conditions and substrate movement without washing away.

SAFETY:

READ and UNDERSTAND the Material Safety Data Sheet (MSDS) before using this product. WARNING: Wear protective clothing and equipment. See HMIS block. For emergency information, call CHEMTREC at 800-424-9300 or 703-527-3887 (outside USA). KEEP OUT OF REACH OF CHILDREN.

PREPARATION: (read all directions before starting work)

Pavers must be dry and installed on a draining bed (sand).

PLACEMENT:

1. Pour Paver Set on clean, dry surface
2. Sweep polymeric sand into joints, filling completely. (Maximum Width of joints = 1 1/2")
3. Compact sand in joints. (Minimum Depth of joints = 1")
4. Remove excess Paver Set from surface before wetting.

This is a critical step. Failure to remove ALL Paver Set may result in staining. After sweeping the pavers clean, use a leaf blower, vacuum or other device capable of blowing air to remove the fine dust particles. FAILURE TO COMPLETELY ELIMINATE ALL DUST MAY RESULT IN STAINING.

5. Spray using a mist (avoid spraying into joints or flooding)
6. Repeat spraying a minimum of 4 applications at 10-20 minute intervals..

COVERAGE:

Pail:

- 20 to 35 sq. ft. (1.9 to 3.3 sq. m) for joints of about 1/8" wide
- 8 to 18 sq. ft. (0.7 to 1.7 sq. m) for joints of about 3/8" wide

Bag:

- 50 - 80 sq. ft. (4.6 to 7.4 sq. m) for joints of about 1/8" (3.1 mm)
- 20 - 40 sq. ft. (1.9 to 3.7 sq. m) for joints of about 3/8" wide (9.3 mm)

For more accurate coverage information based on actual paver dimensions, visit Sakrete.com

LIMITED WARRANTY:

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the date the product is purchased. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY. Liability under this warranty is limited to replacement of defective product or, at the manufacturer's option, refund of the purchase price. CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.

STORAGE:

Store in a tightly closed container off the floor in a dry place.

SHELF LIFE: One year from date of manufacture.

PACKAGING:

- 40 lb. bag (27.2 kg) - UPC: 7-64661-15440-2
- 50 lb. bag (22.6 kg) - UPC: Gray - 7-64661-15450-1
- 50 lb. bag (22.6 kg) - UPC: Brown - 7-64661-15451-8

ENVIRONMENTAL ADVISORY:

Uncured or crushed cured cement is an environmental hazard, which may adversely affect fish and wildlife. Dispose of construction debris containing cement, including empty bags, at a permitted municipal disposal firm. Do not use crushed concrete as a fill near an aquatic habitat.

WARNING ! CAUSES IRRITATION - Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Exposure may result in irritation of the skin, eyes or nasal passages from alkali in Portland cement. When wet, contact with the skin or eyes may result in irritation or burns. FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get prompt medical attention; for skin, wash thoroughly with plenty of soap and water. If irritation persists, get medical attention. WARNING! HARMFUL IF INHALED - Avoid breathing dust. Keep container closed. Use with adequate ventilation. Excessive exposure by inhalation over an extended period of time may result in the development of pulmonary diseases including pneumoconiosis and silicosis. Crystalline Silica has been classified by IARC and NTP as a carcinogen.

The SAKRETE Companies
866-SAKRETE
866-725-7383

REV 11/12