



Paint & Varnish Stripper



**Remove all types of paint & varnish
from most surfaces!**

- ✓ Strip thick multiple paint layers or varnish safely from wood, brick, stone, metal and other hard and porous surfaces!
- ✓ The only DIY friendly stripper in the world that is skin safe and works!
- ✓ A weekend project starter starts with the trim then finish the whole room.
- ✓ Generates start to finish adding on sales throughout your stores.
- ✓ Customers will save 60% over cost of hiring a contractor.
- ✓ The average contractor will save 60% in labor hours.
- ✓ Skin safe, fume free, no drip easy to use gel formula!
- ✓ Completely indoor safe with a very low VOC% that's great for all year-round projects!



Paint & Varnish

Stripper

Technical Data Sheet

Description

EZ Strip Paint & Varnish Remover is a non-toxic water-based remover that is PH neutral. Suitable for; all woods, metals (including aluminum), concrete, stone, brick, and other hard surface. EZ Strip Paint & Varnish Stripper is designed to remove varnish, lacquers, wax sealants, paints & multi-layered paints from surfaces safely, and completely dust free removal process. Caution: may etch some plastics, always test a small area first.

Physical Properties

This 100% cling gel gives a slight almond odor but without any fumes. Gel is easily cleaned up with just water and is skin safe. Product is white in color to ensure even application.

Typical Performance

Varnish	15 – 30 Minutes
Lacquers, Stain, & Wax	30 Min – 1 Hour
Paint	30 minutes to 1 hour
Multi-layered paint	1 – 12 hours

The above times are approximations and subject to substrate, age, type of coating, and layers of coating. If possible, always test a small area first for optimal removal time. Coverage is approximately 30 – 50 sq ft per litre.

Environmental

VOC content of this product is minimal, 0.000004%.

All materials are readily biodegradable & water soluble

EZ Strip Paint & Varnish Stripper is not a marine pollutant and can enter water-courses and drains, care must be taken to ensure that any paint solids do not enter surface water drains. Disposal of this product or any by-products should always comply with the requirements of the Environmental Protection Act and its subsidiary regulations and any regional Local Authority requirements. EZ Strip products are safe to dispose of in your household garbage.



Paint & Varnish Stripper

See our how-to videos on MAXstrip.ca
For detailed instructions and project demos!

Instructions for Use



Shake well before use. Apply (brush, roll on, or spray) a liberal coating of MAX Strip. For layered paint, wait ten minutes before applying a second coat of MAX Strip. Cover area with plastic film to prevent drying. Do not let MAX Strip dry out as it will stop working, if MAX Strip does dry out, re-apply.



Determine performance time using these guidelines:
Most Painted Surfaces: 30 minutes to 1 hour
Multi-layered paint: 1 hour to overnight
Stain, floor wax, and varnish: 15 to 30 minutes
Polyurethane and acrylic: 1 to 2 hours



Use a scraping blade to remove softened material and discard safely. Finish removal using a scouring pad or a stainless steel scouring ball with warm water to remove remainder of softened material.



To finish, wipe with a damp cloth. Area must be neutralized with water or MAX Strip will continue to work. Allow surface to dry completely before sanding or painting. *For best performance use MAX Strip above 10°C (50° F). Do not use in direct sunlight. Do not freeze. May etch some plastics.