Safety Data Sheet

* Trusted Quality Since 1921 *

www.rustoleum.com

| 1. Identification | | | |
|----------------------|--|------------------|--|
| Product Name: | VARA 1-GL 2PK HD SPAR VARNISH GLOSS | Revision Date: | 5/11/2015 |
| Product Identifier: | 266323 | Supercedes Date: | New SDS |
| Product Use/Class: | Crystal Clear Waterbased Finish/ Varathane | | |
| Supplier: | Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA | Manufacturer: | Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA |
| Preparer: | Regulatory Department | | |
| Emergency Telephone: | 24 Hour Hotline: 847-367-7700 | | |

2. Hazard Identification

EMERGENCY OVERVIEW: Harmful if swallowed. Causes eye irritation. Vapors irritating to eyes and respiratory tract. Combustible liquid and vapor. Harmful if inhaled. May affect the brain or nervous system causing dizziness, headache or nausea. May cause eye, skin, or respiratory tract irritation. KEEP OUT OF REACH OF CHILDREN. Harmful if inhaled. Use ventilation necessary to keep exposures below recommended exposure limits, if any.

Classification

Symbol(s) of Product



Signal Word Danger

Possible Hazards

15% of the mixture consists of ingredient(s) of unknown acute toxicity

GHS HAZARD STATEMENTS

| Flammable liquid, category 4 | H227 | Combustible liquid |
|--|------|---|
| Acute Toxicity, Dermal, category 5 | H313 | May be harmful in contact with skin. |
| Skin Irritation, category 2 | H315 | Causes skin irritation. |
| Acute Toxicity, Inhalation, category 4 | H332 | Harmful if inhaled. |
| STOT, single exposure, category 3, RTI | H335 | May cause respiratory irritation. |
| STOT, single exposure, category 3, NE | H336 | May cause drowsiness or dizziness. |
| Organic Peroxide, categories C, D | H242 | Heating may cause a fire. |
| Aspiration Hazard, category 2 | H305 | May be harmful if swallowed and enters airways. |
| Eye Irritation, category 2B | H320 | Causes eye irritation. |
| Acute Toxicity, Dermal, category 3 | H311 | Toxic in contact with skin. |
| | | |

GHS PRECAUTIONARY STATEMENTS

P102Keep out of reach of children.P103Read label before use.P202Do not handle until all safety precautions have been read and understood.

| P234 | Keep only in original container. |
|-----------|---|
| P260 | Do not breathe dust/fume/gas/mist/vapors/spray. |
| P261 | Avoid breathing dust/fume/gas/mist/vapors/spray. |
| P262 | Do not get in eyes, on skin, or on clothing. |
| P264 | Wash thoroughly after handling. |
| P270 | Do not eat, drink or smoke when using this product. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P281 | Use personal protective equipment as required. |
| P285 | In case of inadequate ventilation wear respiratory protection. |
| P312 | Call a POISON CENTER or doctor/physician if you feel unwell. |
| P351 | Rinse cautiously with water for several minutes. |
| P374 | Fight fire with normal precautions from a reasonable distance. |
| P402 | Store in a dry place. |
| P410+P412 | Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F. |
| P321 | Specific treatment (see on this label). |
| P352 | Wash with plenty of soap and water. |
| P362 | Take off contaminated clothing and wash before reuse. |
| P332+P313 | If skin irritation occurs: Get medical advice/attention. |
| P304+P340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. |
| P405 | Store locked up. |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |
| P501 | Dispose of contents/container to |
| P210 | Keep away from heat/sparks/open flames/hot surfaces No smoking. |
| P220 | Keep/Store away from clothing//combustible materials. |
| P420 | Store away from other materials. |
| P411+P235 | Store at temperatures not exceeding°C /°F. Keep cool. |
| P322 | Specific measures (see on this label). |
| P361 | Remove/Take off immediately all contaminated clothing. |
| P363 | Wash contaminated clothing before reuse. |
| P302+P352 | IF ON SKIN: Wash with plenty of soap and water. |
| P302+P350 | IF ON SKIN: Gently wash with plenty of soap and water. |

3. Composition/Information On Ingredients

HAZARDOUS SUBSTANCES

| Chemical Name | CAS-No. | <u>Wt.%</u> Range | GHS Symbols | GHS Statements |
|-------------------------------------|-----------------|----------------------|-------------|------------------------------|
| Polyurethane Dispersion | PROPRIET ARY | 10-25 | GHS06-GHS08 | H310-360 |
| Dipropylene glycol monomethyl ether | 34590-94-8 | 2.5-10 | | H227 |
| N-Methyl 2-Pyrrolidone | 872-50-4 | 1.0-2.5 | GHS06-GHS08 | H227-310-331-360-335-315-319 |
| Dipropylene Glycol Monobutyl Ether | 29911-28-2 | 1.0-2.5 | | |

The text for GHS Hazard Statements shown above (if any) is given in the "16. Other Information" section.

4. First-aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

FIRST AID - INGESTION: If swallowed, get medical attention.

5. Fire-fighting Measures

EXTINGUISHING MEDIA: Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep containers tightly closed. No unusual fire or explosion hazards noted. Closed containers may explode when exposed to extreme heat due to buildup of steam. Combustible liquid and vapor.

SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion. Evacuate area and fight fire from a safe distance. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools.

7. Handling and Storage

HANDLING: Wash thoroughly after handling. Wash hands before eating. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. **STORAGE:** Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Keep away from heat, sparks, flame and sources of ignition. Keep container closed when not in use. Store in a dry, well ventilated place. Keep container tightly closed when not in use. Do not store above 120 ° F. Store large quantities in buildings designed and protected for storage of NFPA Class II combustible liquids. Avoid excess heat.

8. Exposure Controls/Personal Protection

| Chemical Name | CAS-No. | Weight % Less Than | ACGIH TLV- TWA | ACGIH TLV- STEL | OSHA PEL-TWA | OSHA PEL- CEILING |
|---------------------------------------|-------------|-----------------------|-----------------------|--------------------|----------------|----------------------|
| Polyurethane Dispersion | PROPRIETARY | 15.0 | N.E. | N.E. | N.E. | N.E. |
| Dipropylene glycol monomethyl ether | 34590-94-8 | 5.0 | 100 ppm (Skin) | 150 ppm (Skin) | 100 ppm (Skin) | N.E. |
| N-Methyl 2-Pyrrolidone | 872-50-4 | 5.0 | 10 ppm (AIHA WEEL) | N.E. | N.E. | N.E. |
| Dipropylene Glycol Monobutyl Ether | 29911-28-2 | 5.0 | N.E. | N.E. | N.E. | N.E. |

PERSONAL PROTECTION

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or in any other circumstances where air purifying respirators may not provide adequate protection.

SKIN PROTECTION: Use impervious gloves to prevent skin contact and absorption of this material through the skin. Nitrile or Neoprene gloves may afford adequate skin protection. Use gloves to prevent prolonged skin contact.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application. Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

9. Physical and Chemical Properties

| Appearance: | iquid | Physical State: | Liquid |
|---------------------------|----------------------------|-----------------------------------|-----------------------|
| Odor: A | mmonia Like | Odor Threshold: | N.E. |
| Relative Density: 1 | .031 | pH: | 8.8 - 9.2 |
| Freeze Point, °C: N | I.D. | Viscosity: | 26 - 36 sec. (4 Ford) |
| Solubility in Water: N | liscible | Partition Coefficient, n-octanol/ | No Information |
| Decompostion Temp., °C: N | lo Information | water: | No Information |
| Boiling Range, °C: 8 | 0 - 999 | Explosive Limits, vol%: | 0.6 - 17.0 |
| Flammability: D | oes not Support Combustion | Flash Point, °C: | >93 |
| Evaporation Rate: S | lower than Ether | Auto-ignition Temp., °C: | No Information |
| Vapor Density: H | leavier than Air | Vapor Pressure: | N.D. |

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

CONDITIONS TO AVOID: Avoid all possible sources of ignition. Avoid temperatures above 120 ° F. Avoid contact with strong acid and strong bases.

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

HAZARDOUS DECOMPOSITION: By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acrid smoke and irritating fumes. Contains solvents which may form carbon monoxide, carbon dioxide, and formaldehyde.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

11. Toxicological information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Causes eye irritation. Substance causes moderate eye irritation.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: May cause skin irritation. Substance may cause slight skin irritation.

EFFECTS OF OVEREXPOSURE - INHALATION: Harmful if inhaled. May cause headaches and dizziness. High vapor concentrations are irritating to the eyes, nose, throat and lungs. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. Prolonged or excessive inhalation may cause respiratory tract irritation.

EFFECTS OF OVEREXPOSURE - INGESTION: Aspiration hazard if swallowed; can enter lungs and cause damage. Irritating to the nose, throat and respiratory tract. Harmful if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| CAS-No. | Chemical Name | Oral LD50 | Dermal LD50 | Vapor LC50 |
|------------------------|---|----------------------------------|------------------------------------|----------------------|
| 34590-94-8 872-50-4 | Dipropylene glycol monomethyl ether N-Methyl 2-Pyrrolidone | 5230 mg/kg Rat 3598 mg/kg Rat | 9500 mg/kg Rabbit 8 g/kg Rabbit | N.I. 3.1 mg/L Rat |
| 0/2 00 1 | | eeee mg/ng hat | e gritg Habbit | o. r mg/E r tat |

N.I. - No Information

12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components. Product is a mixture of listed components.

13. Disposal Information

DISPOSAL INFORMATION: Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

14. Transport Information

| | Domestic (USDOT) | International (IMDG) | <u>Air (IATA)</u> | <u>TDG (Canada</u>) |
|-----------------------|------------------|----------------------|-------------------|----------------------|
| UN Number: | N.A. | N.A. | N.A. | N.A. |
| Proper Shipping Name: | Not Regulated | Not Regulated | Not Regulated | Not Regulated |
| Hazard Class: | N.A. | N.A. | N.A. | N.A. |
| Packing Group: | N.A. | N.A. | N.A. | N.A. |
| Limited Quantity: | No | No | No | No |

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name

N-Methyl 2-Pyrrolidone

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

CALIFORNIA PROPOSITION 65:

WARNING: This product contains a substance known to the State of California to cause cancer.

No Proposition 65 Carcinogens exist in this product.

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

WARNING: This product contains a substance known to the State of California to cause birth defects or other reproductive harm.

Chemical Name

N-Methyl 2-Pyrrolidone

CAS-No. 872-50-4

CAS-No.

872-50-4

International Regulations:

CANADIAN WHMIS:

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

Page 6 / 6

16. Other Information

| HMIS RAT Health: | TINGS 2* | Flammability: | 2 | Physical Hazard: | 0 | Personal Protection: | Х |
|---------------------------------|-------------|---------------|----------------|------------------|---|----------------------|---|
| CANADIA | | IS CLASS: | B3 D2A D2B | | | | |
| NFPA RA ⁻ Health: | TINGS 2 | Flammability: | 2 | Instability | 0 | | |
| VOLATILE | ORGA | NIC COMPOUN | DS, g/L: | 248 | | | |
| MSDS REV | /ISION | DATE: | 5/11/2015 | | | | |
| REASON F | | VISION: | No Information | | | | |
| | | | | | | | |

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

| H227 | Combustible liquid |
|------|--|
| H310 | Fatal in contact with skin. |
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H331 | Toxic if inhaled. |
| H335 | May cause respiratory irritation. |
| H360 | May damage fertility or the unborn child <state effect="" if="" known="" specific=""> <state cause="" conclusively="" exposure="" hazard="" if="" is="" it="" no="" of="" other="" proven="" route="" routes="" that="" the="">.</state></state> |

Icons for GHS Pictograms shown in Section 3 describing each ingredient:



The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.