Date Printed: 2/18/2019 Page 1 / 5

# Safety Data Sheet



www.rustoleum.com

#### 1. Identification

VARA QT 2PK WB ST&PLY SATIN HD **Product Name:** 

HONEY

339788 **Product Identifier:** 

Recommended Use: Stain-Poly/Varathane

**Rust-Oleum Corporation** Supplier:

11 Hawthorn Parkway Vernon Hills, IL 60061

**USA** 

Preparer: Regulatory Department

**Emergency Telephone:** 24 Hour Hotline: 847-367-7700

# \* Trusted Quality Since 1921 \*

Supercedes Date: 6/1/2018

**Revision Date:** 

Rust-Oleum Corporation Manufacturer:

11 Hawthorn Parkway Vernon Hills, IL 60061

USA

2/18/2019

### 2. Hazard Identification

#### Classification

Symbol(s) of Product



#### Signal Word

Danger

#### Possible Hazards

4% of the mixture consists of ingredient(s) of unknown acute toxicity.

#### **GHS HAZARD STATEMENTS**

Reproductive Toxicity, category 1B H360 May damage fertility or the unborn child.

#### **GHS LABEL PRECAUTIONARY STATEMENTS**

P201 Obtain special instructions before use.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405

P501 Dispose of contents/container in accordance with local, regional and national regulations.

# 3. Composition / Information On Ingredients

#### **HAZARDOUS SUBSTANCES**

**Chemical Name** CAS-No. Wt.% **GHS Symbols GHS Statements** Range

Dipropylene Glycol Monomethyl Ether 34590-94-8 2.5-10 Not Available Not Available Date Printed: 2/18/2019 Page 2 / 5

Dipropylene Glycol Monobutyl Ether	29911-28-2	1.0-2.5	Not Available	Not Available
Ethanol	64-17-5	1.0-2.5	GHS02	H225
N-Methyl 2-Pyrrolidone	872-50-4	0.1-1.0	GHS07-GHS08	H315-319-332-335-360
Dimethylethanolamine	108-01-0	0.1-1.0	GHS02-GHS05- GHS06	H226-302-312-314-331-335
Triethylamine	121-44-8	0.1-1.0	GHS02-GHS05- GHS06	H225-302-311-314-331-335
Aqueous Ammonia	1336-21-6	0.1-1.0	GHS05-GHS07	H302-314-335
Carbon Black	1333-86-4	0.1-1.0	Not Available	Not Available

# 4. First-Aid Measures

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**FIRST AID - INGESTION:** If swallowed, rinse mouth with water. If feeling unwell, get medical attention. Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention.

# 5. Fire-Fighting Measures

**EXTINGUISHING MEDIA:** Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Keep containers tightly closed. FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F. No unusual fire or explosion hazards noted.

**SPECIAL FIREFIGHTING PROCEDURES:** Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

Special Fire and Explosion Hazard (Combustible Dust): No Information

#### 6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

# 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

STORAGE: Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Advice on Safe Handling of Combustible Dust: No Information

# 8. Exposure Controls / Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL-TWA	OSHA PEL- CEILING
Dipropylene Glycol Monomethyl Ether	34590-94-8	5.0	100 ppm	150 ppm	100 ppm	N.E.

Date Printed: 2/18/2019 Page 3 / 5

Dipropylene Glycol Monobutyl Ether	29911-28-2	5.0	N.E.	N.E.	N.E.	N.E.
Ethanol	64-17-5	5.0	N.E.	1000 ppm	1000 ppm	N.E.
N-Methyl 2-Pyrrolidone	872-50-4	1.0	N.E.	N.E.	N.E.	N.E.
Dimethylethanolamine	108-01-0	1.0	N.E.	N.E.	N.E.	N.E.
Triethylamine	121-44-8	1.0	0.5 ppm	1 ppm	25 ppm	N.E.
Aqueous Ammonia	1336-21-6	1.0	N.É.	N.E.	N.Ė.	N.E.
Carbon Black	1333-86-4	1.0	3 mg/m3	N.E.	3.5 mg/m3	N.E.

#### PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**SKIN PROTECTION:** Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

### 9. Physical and Chemical Properties

Appearance:	Liquid	Physical State:	Liquid
Odor:	Mild	Odor Threshold:	N.E.
Relative Density:	1.022	pH:	N.D.
Freeze Point, °C:	N.D.	Viscosity:	N.D.
Solubility in Water:	Miscible	Partition Coefficient, n-	ND
Decompostion Temp., °C:	N.D.	octanol/water:	N.D.
Boiling Range, °C:	74 - 537	Explosive Limits, vol%:	1.7 - 12.6
Flammability:	Does not Support Combustion	Flash Point, °C:	94
Evaporation Rate:	Slower than Ether	Auto-ignition Temp., °C:	N.D.
Vapor Density:	Heavier than Air	Vapor Pressure:	N.D.

(See "Other information" Section for abbreviation legend)

# 10. Stability and Reactivity

**CONDITIONS TO AVOID: No Information** 

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

HAZARDOUS DECOMPOSITION: When heated to decomposition, it emits acrid smoke and irritating fumes.

**HAZARDOUS POLYMERIZATION:** Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

# 11. Toxicological Information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Irritating, and may injure eye tissue if not removed promptly.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** Low hazard for usual industrial handling or commercial handling by trained personnel.

**EFFECTS OF OVEREXPOSURE - INHALATION:** High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist.

EFFECTS OF OVEREXPOSURE - INGESTION: Substance may be harmful if swallowed.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** Contains carbon black. Chronic inflammation, lung fibrosis, and lung tumors have been observed in some rats experimentally exposed for long periods of time to excessive concentrations of carbon black and several insoluble fine dust particles. Tumors have not been observed in other animal species (i.e., mouse and hamster) under similar circumstances and study conditions. Epidemiological studies of North American workers show no evidence of

Date Printed: 2/18/2019 Page 4 / 5

clinically significant adverse health effects due to occupational exposure to carbon black.

Carbon black is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC and is proposed to be listed as A4- "not classified as a human carcinogen" by the American Conference of Governmental Industrial Hygienists. Significant exposure is not anticipated during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of carbon black in the formula.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

#### **ACUTE TOXICITY VALUES**

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
34590-94-8	Dipropylene Glycol Monomethyl Ether	5350 mg/kg Rat	9500 mg/kg Rabbit	>20 mg/L
64-17-5	Ethanol	7060 mg/kg Rat	15,800 mg/kg Rabbit	30,000 mg/l Rat
872-50-4	N-Methyl 2-Pyrrolidone	3914 mg/kg Rat	8000 mg/kg Rabbit	20 mg/L Rat
108-01-0	Dimethylethanolamine	1803 mg/kg Rat	1220 mg/kg Rabbit	N.E.
121-44-8	Triethylamine	460 mg/kg Rat	415 mg/kg Rabbit	N.E.
1336-21-6	Aqueous Ammonia	350 mg/kg Rat	N.Ĕ.	N.E.
1333-86-4	Carbon Black	>15400 mg/kg Rat	N.E.	N.E.

N.E. - Not Established

# 12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components.

#### 13. Disposal Information

**DISPOSAL INFORMATION:** Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

# 14. Transport Information

	Domestic (USDOT)	International (IMDG)	<u>Air (IATA)</u>	TDG (Canada)
UN Number:	N.A.	N.A.	N.A.	N.A.
Proper Shipping Name:	Not Regulated	Not Regulated	Not Regulated	Not Regulated
Hazard Class:	N.A.	N.A.	N.A.	N.A.
Packing Group:	N.A.	N.A.	N.A.	N.A.
Limited Quantity:	No	No	No	No

# 15. Regulatory Information

# U.S. Federal Regulations:

#### **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Reproductive toxicity

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u> <u>CAS-No.</u>

Date Printed: 2/18/2019 Page 5 / 5

N-Methyl 2-Pyrrolidone 872-50-4
Triethylamine 121-44-8
Aqueous Ammonia 1336-21-6

#### **Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

#### U.S. State Regulations:

#### California Proposition 65:

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

#### 16. Other Information

**HMIS RATINGS** 

Health: 2\* Flammability: 1 Physical Hazard: 0 Personal Protection: X

**NFPA RATINGS** 

Health: 2 Flammability: 1 Instability 0

Volatile Organic Compounds 257 g/L SDS REVISION DATE: 2/18/2019

**REASON FOR REVISION:** Substance and/or Product Properties Changed in Section(s):

03 - Composition/Information on Ingredients

11 - Toxicological Information15 - Regulatory Information

Substance Hazard Threshold % Changed Substance Chemical Name Changed Substance Hazardous Flag Changed Revision Statement(s) Changed

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.