### Issuing Date No data available

**SAFETY DATA SHEET** 

Revision Date 23-Mar-2015

Revision Number 1



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier	
Product Name	Ordinary Zinc-Manganese Dry Battery R03
Other means of identification	
Synonyms	None
Recommended use of the chemical	and restrictions on use
Recommended Use	Carbon Zinc Battery
Uses advised against	No information available
Details of the supplier of the safety	data sheet
Supplier Name	Dongguan Large Electronics Co., Ltd.
Supplier Address	Gosun Science Park, Longxi Road 5, Zhouxi, Nancheng District, Dongguan City,Guangdong Dongguang Guangdong 523000 CN
Supplier Phone Number	Phone:+86769-22810105 Contact Phone+86769-22810105
Supplier Email	DongguanLarge@163.com
Emergency telephone number	

# 2. HAZARDS IDENTIFICATION

# **Classification**


This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Gases)	Category 4



Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Specific target organ toxicity (repeated exposure)	Category 2

### GHS Label elements, including precautionary statements



### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Use only outdoors or in a well-ventilated area Do not breathe dust/fume/gas/mist/vapors/spray Wear protective gloves/protective clothing/eye protection/face protection

### **Precautionary Statements - Response**

Immediately call a POISON CENTER or doctor/physician Specific treatment (see supplemental first aid instructions on this label)

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

#### Skin

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower Wash contaminated clothing before reuse

### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell Immediately call a POISON CENTER or doctor/physician

#### Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell Rinse mouth



Do NOT induce vomiting

#### **Precautionary Statements - Storage**

Store locked up

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

Not applicable

### Unknown Toxicity

10% of the mixture consists of ingredient(s) of unknown toxicity

### **Other information**

Very toxic to aquatic life with long lasting effects

### Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS No	Weight-%	Trade Secret
Manganese dioxide	1313-13-9	15 - 40	*
Zinc	7440-66-6	15 - 40	*
Zinc chloride	7646-85-7	3 - 7	*
Iron	7439-89-6	1 - 5	*
Ammonium chloride	12125-02-9	1 - 5	*
Copper	7440-50-8	1 - 5	*

The exact percentage (concentration) of composition has been withheld as a trade secret

# 4. FIRST AID MEASURES

### First aid measures

General Advice	First aid is upon rupture of sealed battery. Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Seek immediate medical attention/advice.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Seek immediate medical attention/advice.
Inhalation	Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If



	breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get medical attention immediately if symptoms occur.
Ingestion	Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Wear personal protective clothing (see section 8).

### Most important symptoms and effects, both acute and delayed

**Most Important Symptoms and** Burning sensation. Coughing and/ or wheezing. Difficulty in breathing. **Effects** 

### Indication of any immediate medical attention and special treatment needed

Notes to PhysicianProduct is a corrosive material. Use of gastric lavage or emesis is<br/>contraindicated. Possible perforation of stomach or esophagus should be<br/>investigated. Do not give chemical antidotes. Asphyxia from glottal edema may<br/>occur. Marked decrease in blood pressure may occur with moist rales, frothy<br/>sputum, and high pulse pressure.

# **5. FIRE-FIGHTING MEASURES**

#### Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

### Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

### Specific hazards arising from the chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors.

# Hazardous Combustion Products

Carbon oxides.

Explosion Data Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.



# **6. ACCIDENTAL RELEASE MEASURES**

#### Personal precautions, protective equipment and emergency procedures

Personal precautions	Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid breathing vapors or mists. Avoid generation of dust. Do not breathe dust.
Other Information	Refer to protective measures listed in Sections 7 and 8.
Environmental precautions	
Environmental precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Should not be released into the environment. Do not allow to enter into soil/subsoil. Prevent product from entering drains.
Methods and material for containme	ent and cleaning up
Methods for containment	Prevent further leakage or spillage if safe to do so.

Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

## Precautions for safe handling

Methods for cleaning up

Handling In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Use only with adequate ventilation and in closed systems. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

### Conditions for safe storage, including any incompatibilities

Storage	Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Store locked up. Keep out of the reach of children. Store away from other materials.

**Incompatible Products** 

Acids. Bases. Oxidizing agent.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### **Control parameters**

#### **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Manganese dioxide 1313-13-9	TWA: 0.02 mg/m³ Mn TWA: 0.1 mg/m³ Mn	(vacated) Ceiling: 5 mg/m³ Ceiling: 5 mg/m³ Mn	IDLH: 500 mg/m³ Mn TWA: 1 mg/m³ Mn STEL: 3 mg/m³ Mn
Zinc 7440-66-6	STEL: 10 mg/m <sup>3</sup> respirable fraction	TWA: 5 mg/m <sup>3</sup> fume TWA: 15 mg/m <sup>3</sup> total dust	IDLH: 500 mg/m <sup>3</sup> Ceiling: 15 mg/m <sup>3</sup> dust



	TWA: 2 mg/m <sup>3</sup> respirable fraction	TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 5 mg/m <sup>3</sup> dust and fume STEL: 10 mg/m <sup>3</sup> fume
Zinc chloride 7646-85-7	STEL: 2 mg/m <sup>3</sup> fume TWA: 1 mg/m <sup>3</sup> fume	TWA: 1 mg/m <sup>3</sup> fume (vacated) TWA: 1 mg/m <sup>3</sup> fume (vacated) STEL: 2 mg/m <sup>3</sup> fume	IDLH: 50 mg/m <sup>3</sup> fume TWA: 1 mg/m <sup>3</sup> fume STEL: 2 mg/m <sup>3</sup> fume
Ammonium chloride 12125-02-9	STEL: 20 mg/m <sup>3</sup> fume TWA: 10 mg/m <sup>3</sup> fume	(vacated) TWA: 10 mg/m³ fume (vacated) STEL: 20 mg/m³ fume	TWA: 10 mg/m³ fume STEL: 20 mg/m³ fume
Copper 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> fume TWA: 1 mg/m <sup>3</sup> Cu dust and mist	TWA: 0.1 mg/m³ fume TWA: 1 mg/m³ dust and mist (vacated) TWA: 0.1 mg/m³ Cu dust, fume, mist	IDLH: 100 mg/m <sup>3</sup> dust, fume and mist TWA: 1 mg/m <sup>3</sup> dust and mist TWA: 0.1 mg/m <sup>3</sup> fume

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

### Appropriate engineering controls

**Other Exposure Guidelines** 

Engineering Measures	Showers
	Eyewash stations Ventilation systems

### Individual protection measures, such as personal protective equipment

Eye/face protection	Face protection shield.
Skin and body protection	Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant apron. Impervious gloves.
Respiratory protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. For environmental protection, remove and wash all contaminated protective equipment before re-use. Do not breathe dust.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

### **Physical and Chemical Properties**

Physical state Appearance Color	Solid containing liquid, Solid Multiple Colors No information available	Odor Odor Threshold	Odorless No information available
Property	Values	Remarks Method	
pH	No data available	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	No data available	None known	
Flash Point	No data available	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		



Lower flammability limit	No data available
Vapor pressure	No data available
Vapor density	No data available
Specific Gravity	No data available
Water Solubility	Insoluble
Solubility in other solvents	No data available
Partition coefficient: n-octanol/wate	er0.001
Autoignition temperature	No data available
Decomposition temperature	No data available
Kinematic viscosity	No data available
Dynamic viscosity	0.001
Explosive properties	No data available
Oxidizing properties	No data available
Other Information	
Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available

None known None known

# **10. STABILITY AND REACTIVITY**

### **Reactivity**

No data available.

**Particle Size Distribution** 

<u>Chemical stability</u> Stable under recommended storage conditions. <u>Possibility of Hazardous Reactions</u> None under normal processing. <u>Hazardous Polymerization</u> Hazardous polymerization does not occur.

<u>Conditions to avoid</u> Exposure to air or moisture over prolonged periods. Excessive heat. Incompatible materials Acids. Bases. Oxidizing agent. <u>Hazardous Decomposition Products</u> Carbon oxides.

# **11. TOXICOLOGICAL INFORMATION**

### Information on likely routes of exposure

Product Information	Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:.
Inhalation	Specific test data for the substance or mixture is not available. Corrosive by inhalation. (based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal. May cause irritation of respiratory tract. Harmful by inhalation.
Eye contact	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause irreversible damage to eyes.

Skin contact	Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns.
Ingestion	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be harmful if swallowed.

## **Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Manganese dioxide 1313-13-9	= 9000 mg/kg (Rat)	-	-
Zinc chloride 7646-85-7	= 350 mg/kg (Rat)	-	-
Iron 7439-89-6	= 984 mg/kg (Rat)	-	-
Ammonium chloride 12125-02-9	= 1410 mg/kg(Rat)	-	-

### Information on toxicological effects

Symptoms Erythema (skin redness). Burning. May cause blindness. Coughing and/ or wheezing.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	No information available.
Mutagenic Effects	No information available.
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.
IARC (International Agency for Re	

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).
Chronic Toxicity	No known effect based on information supplied. Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects. Carcinogenic potential is unknown.
Target Organ Effects	Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Blood. Central Nervous System (CNS). Central Vascular System (CVS). Kidney. Liver. Cardiovascular system. Lungs.

Pancreas. Systemic Toxicity.

**Aspiration Hazard** 

No information available.

### Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 1,196.00 mg/kg ATEmix (inhalation-gas) 14,062.00 ppm (4 hr) ATEmix (inhalation-dust/mist) 4.70 mg/l ATEmix (inhalation-vapor) 34.00 ATEmix



# **12. ECOLOGICAL INFORMATION**

# Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Zinc 7440-66-6	96h EC50: 0.11 - 0.271 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.09 - 0.125 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 2.16 - 3.05 mg/L (Pimephales promelas) 96h LC50: 0.211 - 0.269 mg/L (Pimephales promelas) 96h LC50: = 2.66 mg/L (Pimephales promelas) 96h LC50: = 30 mg/L (Cyprinus carpio) 96h LC50: = 0.45 mg/L (Cyprinus carpio) 96h LC50: = 7.8 mg/L (Cyprinus carpio) 96h LC50: = 3.5 mg/L (Lepomis macrochirus) 96h LC50: = 0.24 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.59 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.41 mg/L (Oncorhynchus mykiss)		48h EC50: 0.139 - 0.908 mg/L
Iron 7439-89-6		96h LC50: = 13.6 mg/L (Morone saxatilis)		
Ammonium chloride 12125-02-9		96h LC50: = 209 mg/L (Cyprinus carpio) 24h LC50: = 725 mg/L (Lepomis macrochirus)		24h LC50: = 202 mg/L
Copper 7440-50-8	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.2 mg/L (Dicorhynchus mykiss) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas)		48h EC50: = 0.03 mg/L

### Persistence and Degradability

No information available.

### **Bioaccumulation**

Chemical Name	Log Pow
Manganese dioxide 1313-13-9	<0

### Other adverse effects

No information available.



# **13. DISPOSAL CONSIDERATIONS**

## Waste treatment methods

Disposal methods	This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.
Contaminated Packaging	Dispose of contents/containers in accordance with local regulations.

### California Hazardous Waste Codes 181

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Zinc 7440-66-6	Ignitable powder Toxic
Zinc chloride 7646-85-7	Toxic Corrosive
Copper 7440-50-8	Тохіс

# 14. TRANSPORT INFORMATION

REGULATED REGULATED		
gulated		
gulated		
gulated		
gulated REGULATED		
gulated		
15. REGULATORY INFORMATION		
lies nponents are listed either on the DSL or NDSL.		



TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

# US Federal Regulations

# SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Manganese dioxide - 1313-13-9	1313-13-9	15 - 40	1.0
Zinc - 7440-66-6	7440-66-6	15 - 40	1.0
Zinc chloride - 7646-85-7	7646-85-7	3 - 7	1.0
Ammonium chloride - 12125-02-9	12125-02-9	1 - 5	1.0
Copper - 7440-50-8	7440-50-8	1 - 5	1.0
SARA 311/312 Hazard Categories Acute Health Hazard	No		
Chronic Health Hazard	No		
Fire Hazard	No		
Sudden release of pressure hazard	No		

# Reactive Hazard CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

No

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Zinc 7440-66-6		X	X	
Zinc chloride 7646-85-7	1000 lb	X		Х
Ammonium chloride 12125-02-9	5000 lb			Х
Copper 7440-50-8		X	X	

# CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Zinc 7440-66-6	1000 lb		RQ 454 kg final RQ RQ 1000 lb final RQ
Zinc chloride 7646-85-7	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Ammonium chloride 12125-02-9	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Copper 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

# US State Regulations

### California Proposition 65

This product does not contain any Proposition 65 chemicals.

### U.S. State Right-to-Know Regulations



Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Manganese dioxide 1313-13-9			Х	Х	Х
Zinc 7440-66-6	Х	Х	Х	Х	
Carbon 7440-44-0			Х		
Zinc chloride 7646-85-7	Х	Х	Х	Х	
Ammonium chloride 12125-02-9	Х	Х	Х	Х	
Copper 7440-50-8	X	Х	Х	Х	Х

## International Regulations

### Mexico

### National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Manganese dioxide 1313-13-9(15-40)		Mexico: TWA= 0.2 mg/m <sup>3</sup>
Zinc chloride 7646-85-7(3 - 7)		Mexico: TWA 1 mg/m <sup>3</sup> Mexico: STEL 2 mg/m <sup>3</sup>
Ammonium chloride 12125-02-9(1-5)		Mexico: TWA 10 mg/m <sup>3</sup> Mexico: STEL 20 mg/m <sup>3</sup>
Copper 7440-50-8(1 - 5)		Mexico: TWA= 1 mg/m <sup>3</sup> Mexico: TWA= 0.2 mg/m <sup>3</sup> Mexico: STEL= 2 mg/m <sup>3</sup>

Mexico - Occupational Exposure Limits - Carcinogens

#### Canada WHMIS Hazard Class Not determined

# 16. OTHER INFORMATION

NFPA HMIS	Health Hazards 1 Health Hazards 0	Flammability 0 Flammability 0	Instability 0 Physical Hazard 0	Physical and Chemical Hazards Personal Protection X
Prepared By Revision Date Revision Note	Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501 23-Mar-2015 No information available			

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

# End of Safety Data Sheet

