

•TRUSTED QUALITY SINCE 1921•
RUST-OLEUM®
 semi-transparent
CONCRETE STAIN

CONCRETE STAIN SPRAYS

DESCRIPTION AND USES

Rust-Oleum® Concrete Stain is a penetrating water-based stain designed for use on bare interior and exterior concrete and masonry surfaces. This convenient spray is ideal for use on small statuary, for adding accent colors to larger projects or for touch up of previously stained projects.

Application works best on bare interior and exterior concrete and masonry surfaces. Existing coatings or sealers must be removed prior to applying Concrete Stain Sprays. Test for a sealer by lightly sprinkling water onto the concrete. If water droplets bead up, rather than soak into the concrete, then a sealer is present and it must be removed prior to staining.

Concrete Stain Sprays features a comfort tip with a wider finger pad to reduce fatigue caused by continuous spraying and an any-angle tip which allows you to spray at any angle.

PRODUCTS

SKU	Description
247129	Burnt Brick
247161	Sienna
247162	Earth Brown
247163	Limestone
247166	Gloss Clear
247167	Matte Clear

SPRAYING CONDITIONS

Apply when ambient air temperature is 50-90°F (10-32°C) and the relative humidity is below 85%. Do not stain outdoors if rain is expected within 48 hours. To minimize overspray, properly mask adjoining areas and avoid staining in windy conditions.

PRODUCT APPLICATION

SURFACE PREPARATION

Proper surface preparation is critical to performance. Allow new concrete to cure for a minimum of 28 days prior to coating. Before staining bare concrete surfaces, remove any oil or grease spots with a heavy duty degreaser, sold separately. Follow manufacturer's directions for use.

When staining small statuary or when using to add and accent color over a previously stained surface, etching is not necessary. Make sure the surface is clean and free of dirt.

PRODUCT APPLICATION (cont.)

APPLICATION

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can upright 10-12" from surface and spray in a circular or figure eight pattern. Apply the basecoat evenly (100% coverage) and allow to dry approximately 1 hour before applying accent color(s). Keep the can the same distance from the surface. Keep the can in motion while spraying. If desired, apply accent color(s) over the basecoat to provide the desired level of contrast. Allow to air dry a minimum of 1 hour before sealing. Note: Final results may vary do to the natural variance that exists in concrete. **Do not use near open flame.**

DRY & RECOAT

Dry and recoat times are based on 70°F (21°C) and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 1 hour and can be recoated in 1 hour.

CLEAN UP

Wipe off tip before storing. Clean-up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

TECHNICAL DATA

CONCRETE STAIN SPRAYS

PHYSICAL PROPERTIES

Physical Properties		CONCRETE STAIN SPRAYS
Resin Type		Water-based Acrylic
Pigment Type		Varies with color
Solvents		Water, Dimethyl Ether, Isopropyl Alcohol
MIR		0.95 Max
Fill Weight		15 ounces
Practical Coverage at Recommended DFT (assumes 15% material loss)		Approximately 12-16 sq.ft./can (1.1-1.5 m ² /can)
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	1 hours
	Recoat	1 hour
Shelf Life		5 years
Flash Point		-156°F (-104°C)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.