



## BEHR PREMIUM® 1-Part Epoxy Concrete & Garage Floor Paint

- Interior/Exterior Satin Finish
- Ready-To-Use, No-Mix Formula
- Resists Chemicals & Hot Tire Pick-up
- Slip-Resistant Finish

No. 900 White Base  
No. 901 Silver Gray  
No. 902 Slate Gray  
No. 930 Deep Base



**Spread Rate:**  
Rough 28-37 m<sup>2</sup>  
Smooth 37-46 m<sup>2</sup>



**Dry Time:**  
1 Hr. Dry to Touch  
4-6 Hr. Recoat



**Clean-Up:**  
Soap & Water



**Protect**  
from Freezing

**CAUTION:** Painted surfaces may become slippery when wet. Follow all label instructions.

### WHERE TO USE

Interior/Exterior surfaces such as: Porous Concrete, Masonry, Stone and Brick. Ideal for horizontal surfaces such as: Garage Floors, Driveways, Basements, Porches and Pool Decks. DO NOT use on vertical surfaces or areas subject to hydrostatic pressure. NOT for industrial use or areas subject to forklifts.

### PREPARATION†

**(Proper surface preparation is required.)** New and Uncoated Concrete or Masonry Surfaces: New concrete must cure for a minimum of 30 days. For proper penetration and adhesion of topcoat, use a product such as BEHR PREMIUM® No. 991 Concrete & Masonry Cleaner & Etcher to clean and etch the surface. Apply a product such as BEHR PREMIUM No. 880 Concrete & Masonry Bonding Primer to increase adhesion of topcoat to the surface. Painted, Stained or Sealed Concrete: Option 1 - To completely strip the entire surface, use a product such as BEHR PREMIUM No. 992 Concrete & Masonry Paint Stripper. Option 2 - To recoat over an existing coating, remove any loose or peeling paint and scuff sand the surface. Use a product such as BEHR PREMIUM No. 990 Concrete & Masonry Degreaser & Cleaner to clean previously coated surfaces in sound condition. Use a product such as BEHR PREMIUM No. 991 Concrete & Masonry Cleaner & Etcher to clean and etch any bare concrete area. Spot prime all bare concrete areas with a product such as BEHR PREMIUM No. 880 Concrete & Masonry Bonding Primer to increase adhesion of topcoat to the surface. Follow all label instructions.

### APPLICATION

DO NOT THIN. Intermix all cans of same product to ensure colour uniformity. Stir before applying. Use product when air and surface temperatures are between 10-32° C. Apply a thin, even coat using a 10 mm nap roller cover, nylon/polyester brush or an airless sprayer (.015" - .021" spray tip, 60 mesh filter). Allow first coat to dry before deciding if a second coat is necessary. For uniformity apply second coat in a criss-cross direction. An annual touch-up may be required in areas subject to tire traffic.

### DRY TIME

Longer dry time required in cooler temperatures and in higher humidity. The floor may be subjected to light foot traffic after 24 hours. Allow 72 hours before subjecting surface to heavy foot traffic or repositioning furniture. Allow 7 days before subjecting to automotive tires. Premature heavy traffic will cause paint failure requiring spot recoating. If necessary, corrugated cardboard may be used underneath automobile tires after 72 hours. Wait at least 30 days before rinsing or cleaning. Use a mild detergent as needed. Abrasive cleaners and pressure-washers should be used carefully to avoid premature paint failure.

### DISPOSAL

Properly dispose of all soiled rags. To recycle or properly dispose of product in your community, contact your household refuse collection service.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead)

**LIMITED WARRANTY** If this product is found to be defective upon inspection by an expert, Behr Process Corporation will, at its option, and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. This warranty is not transferable. If you believe this product is defective, contact Behr Process Corporation at 2750 Centre Avenue N.E., Calgary, AB T2A2L3. The cost of transportation or shipping, if any, are to be assumed by the consumer. The clause of limitation of liability which follows is inapplicable in Quebec: **This warranty excludes (1) labour and costs of labour for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** The above provisions are not intended to operate where prohibited by law. This limited warranty is the only warranty provided by Behr Process Corporation unless extended by a provincial consumer statute.

To consult with a Behr Certified Coatings Professional, call 1-800-661-1591.

**CAUTION! IRRITANT! HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN.** Avoid contact with eyes, skin and clothing. Do not breathe fumes. Wear eye protection and protective clothing. Use only with adequate ventilation. **FIRST AID TREATMENT:** Contains ETHYLENE GLYCOL. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes rinse with water for 20 minutes. If on skin rinse well with water. If inhaled, move person to fresh air. **CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**

**BEHR**  
A Masco Company

©2016 Behr Process Corporation  
Santa Ana, CA 92704 U.S.A. • [behr.com](http://behr.com)  
V.O.C. (C.O.V.) <50 g/L • REV. 08/16