



4700 W. 160th St.
Cleveland, OH 44135
PH:800-321-9532
FX:800-321-9535
www.oatey.com

TECHNICAL SPECIFICATION

SOIL PIPE SEAL



TECHNICAL SPECIFICATION: Oatey Soil Pipe Seal is a permanent caulking lead substitute for sealing cast iron soil pipe joints and cracks.



PHYSICAL/CHEMICAL PROPERTIES

Solubility in Water	Insoluble
Appearance	Gray Paste
Shelf Life	2 years from manufacture date

DIRECTIONS FOR USE

With joint packed with sufficient amount of oakum, pack Soil Pipe Seal in the joint generously with a putty knife working rapidly to avoid drying. Smooth off the top of the joint and allow the seal to set.

PRECAUTIONS

Read all cautions and directions carefully before using this product. Avoid contact with eyes and skin. Wear gloves when working with Pipe Seal. Do not smoke, eat or drink when working with Pipe Seal. Keep container closed when not in use. **DO NOT USE PIPE SEAL ON PLASTIC. DO NOT REUSE EMPTY CONTAINER. KEEP OUT OF REACH OF CHILDREN.**

DANGER: EXTREMELY FLAMMABLE. VAPORS MAY CAUSE FLASH FIRES. MAY IRRITATE EYES AND SKIN. VAPOR HARMFUL. MAY IRRITATE RESPIRATORY TRACT AND CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. HARMFUL OR FATAL IF SWALLOWED.

PRECAUTIONS (CONTINUED)

May cause irritation to the eyes, skin and nose, throat and respiratory tract. May cause coughing, sore throat, difficulty breathing, headache, dizziness, nausea. Long term repeated overexposures to solvents may cause damage to the brain, nervous system, reproductive system, respiratory system, mucous membranes, liver and kidneys.

FIRST AID: If swallowed, DO NOT INDUCE VOMITING.

Drink water and call a doctor or poison control center immediately. This product may be aspirated into the lungs and cause chemical pneumonitis, a potentially fatal condition. If contact with eyes, flush with water for 15 minutes and seek medical attention if irritation persists. If contact with skin, flush with water then use baby oil or Oatey hand cleaner to remove residue. If inhaled and ill feelings develop, get fresh air and obtain medical attention if ill feelings persist.

FIRE: Use dry chemical, foam or carbon dioxide extinguisher. Water spray may be applied to reduce potential vapors or for cooling. Burning liquid extinguished with water will float and may re-ignite on surface of water.

SPILLS: Remove all sources of ignition and ventilate area. Personnel cleaning up the spill should wear appropriate personal protective equipment, including respirators if vapor concentrations are high. Soak up with absorbent material. Put absorbent material in covered, labeled containers. Dispose of in accordance with local regulations.

Refer to material safety data sheet for more information. For emergency first aid help, call 1-303-623-5716 COLLECT.

COMMON APPLICATIONS

Oatey Pipe Seal is an excellent lead substitute for caulking cast iron soil pipe joints.

Consult Oatey Technical Department for applications not specifically referenced above.

INGREDIENTS (CAS Number)

Kaolin clay (1332-58-7)
Methyl Ethyl Ketone (78-93-3)
Vinyl Chloride Acetate Resin (25085-82-9)
Amorphous Silica (112945-52-5)
Black Pigment (Non-Hazardous)

PRODUCT NUMBER	DESCRIPTION	PACK	CARTON WEIGHT
30614	16 fl. oz. Pipe Seal	12	20 lbs.