

## In-Wall Timer - Spring Wound Countdown Timer - Commercial

Item SW30MK / EAN-Code



### APPLICATIONS

- ▶ Bathroom Fans
- ▶ Spas
- ▶ Hot Tubs
- ▶ Storage Closets
- ▶ Garage Lights

### TECHNICAL DATA

#### General

Application Compatibilities	Incandescent
	Fluorescent
	Compact Fluorescent
	LED
Warranty	1-year limited
Mechanism Type	Analog/Mechanical
UPC Code	078275143524
Description	Spring Wound Countdown Timer - Commercial
Model Number	SW30MK
Brand	Intermatic
Harmonized Code	9107.00.4080
Country of Origin (Intermatic)	TUNISIA

#### Mechanical Specifications

Wall Plate Configurations	Single-Gang
	Multi-Gang

#### Electrical Specifications

Neutral Connection Required	False
Wiring Configurations	Single
Input Voltages	125-277 VAC, 50 Hz;125-277 VAC, 60 Hz
Switch Type	SPST

#### Material Specifications

Includes Wall Plate	True
Color	Brushed Metal
Shipping Weight (kg)	0.159
Shipping Weight (lbs)	0.35

#### Control Specifications

Hold Mode Included	False
--------------------	-------

Operation Mode	Countdown
Countdown Time	30 min

#### Environmental Specifications

Operating Temperature Min (°C)	0
Operating Temperature Min (°F)	32
Operating Temperature Max (°C)	40
Operating Temperature Max (°F)	104
California Proposition 65	DEHP

#### Load Ratings

Incandescent Load Ratings (Single-Gang)	7 A, 125 VAC, 50 Hz
	7 A, 125 VAC, 60 Hz
Incandescent Load Ratings (Multi-Gang)	7 A, 125 VAC, 50 Hz; 7 A, 125 VAC, 60 Hz
Resistive	20 A, 125 VAC, 50 Hz; 10 A, 250-277 VAC, 50 Hz; 20 A, 125 VAC, 60 Hz; 10 A, 250-277 VAC, 60 Hz
Motor	1 HP, 125 VAC, 50 Hz; 2 HP, 250 VAC, 50 Hz; 1 HP, 125 VAC, 60 Hz; 2 HP, 250 VAC, 60 Hz
Resistive Range(s)	20 A, 125 VAC, 50/60 Hz; 10 A, 250/277 VAC, 50/60 Hz
Motor Range(s)	1 HP, 125 VAC, 50/60 Hz; 2 HP, 250 VAC, 50/60 Hz
Incandescent SingleGang LoadRatings Range(s)	7 A, 125 VAC, 50/60 Hz
Incandescent MultiGang LoadRatings Range(s)	7 A, 125 VAC, 50/60 Hz

#### Standards and Certifications

Other Certifications	cRUus
CSA Certification	cCSAus

#### Dimensions

Dimension	44.5x104.8x31.8mm
Product Width (in)	1.75
Product Height (in)	4.125
Product Height (mm)	104.8
Product Depth (mm)	31.8
Product Depth (in)	1.25
Unit Carton Height (in)	7
Unit Carton Width (in)	4
Unit Carton Length (in)	2.5