

## VinylFix Use and Care Manual

Mix2Match™

# VinylFix

For LVT, VCT, Vinyl, Linoleum & WPC

**All surfaces should be clean and dry.**

**Shake pigment bottles thoroughly before and during use.**

### Mix Formula

1. Choose a color from the formula chart found *inside front label* that most closely matches the tile.
  - For a more realistic repair, match the background color (usually much lighter) first, then add foreground graining or marbling
2. Measure the required amount of putty onto the mixing board.
3. Follow directions for the Mixing Method (A or B) which applies to your formula.

### HEALTH AND SAFETY

#### KEEP OUT OF REACH OF CHILDREN

• Irritating to eye and skin.

In case of contact with skin, wash with soap and water.

In case of contact with eyes, rinse immediately with plenty of clean, fresh

water. • If swallowed, rinse mouth and throat with cold water.

Immediately seek professional medical advice. Take this label with you. Do not induce vomiting.

### Application

1. Apply mixture to tile with the plastic spatula, slightly overfilling the area of repair. Scrape off any surrounding excess with spatula. Allow to dry 2-3 hours.
2. When the mixture is freshly dry, gently rub away the excess of the surrounding area with a damp cloth until the surface is smooth.
3. If shrinkage occurs, re-apply the above mixture.
4. Once the repair is completely dry (8-12hrs) and graining or marbling is finished, apply clear lacquer over the area using the brush.
5. Allow to fully cure before heavy use (2-3 days).