

TRIMFINITY™

MOULDINGS THAT LAST

NO MOISTURE ♻ NO MOLD ♻ NO MILDEW ♻ NO TERMITES

Manufactured By MCS Industries, Inc.

Trimfinity designer line fits the needs of everyone whether you are a do-it-yourselfer or a professional contractor

- Ready and Easy to install
- Great alternative to wood
- Use in new or existing construction

Cut it! - Cuts and Copes with Precision

- For power saws, use a 7.5 in. blade with 24 teeth, or a 10 in. blade with 50 teeth.
- Make a quick cut for precision.



Nail it/Shoot it!

- Hand nail with #3 or #4 bright finish nails.
- With a nail gun, use 16 or 18 gauge finishing brads. Set pressure between 70 and 90 PSI.

Glue it!

- Gluing Tip: Use any non-solvent based glue.



Caulk it!

- Use a flexible latex based caulk.
- We suggest products such as DAP: Elastopatch, Dynaflex, 230 or Kwik Seal.

Paint it!

- Use any water based interior paint.
- For long - lasting results, consider using a primer to help your final coat of paint adhere longer. .



Stain it!

- Stainable surface makes unlimited possibilities to what finish you can create.



CAUTION: Recommend to stain product as prescribed by the stain manufacturer. However, you may have some limitations when trying to achieve large variations in desired finishes. You may need to select darker stains to achieve desired finish or a desired finish may not be achievable if the variation is too large. It is common that stains will differ in final finish depending upon what you have applied the stain to including Oak, Pine, other wood species and plastic products. Please contact Trimfinity Customer Service if questions arise at 1-800-833-3058.