



QC ES-4700
QuietCool Energy Saver Line

QC ES-4700 Specifications

Motor Voltage	120 VAC, 60 Hz	
Energy Use	Hi: 415 Watts / Low: 75 Watts	
Air Flow	Hi: 4195 CFM / Low: 2304 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	3080 CFM	
Recommended SQFT Coverage @ 2 CFM per SQ FT	Covers up to 2100 SQ FT	
# of Speeds	2	
Duct Diameter	18"	
Duct Length	9 feet	
Motor Head Diameter	18 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls (Not Included)	Recommended 8 Hour Electronic Timer (IT-30070) and HI-LOW-OFF Switch (IT-35000)	
Warranty	10 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	5.6 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 30 1/4"	
Removable Grille Outside Dimension	16" x 32"	
Shipping Weight	75 lbs.	
Box Dimensions	36" x 22" x 40"	
In The Box	-QC ES-4700 Motorhead -Ceiling Grille -Cut-out Template -Window Locks	-Damper Box -9 Foot Duct -Accessory Bag



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM