

WATERPROOFING REPAIR TAPE

SPECIALTY TAPE



Backing: Aluminum Foil **Adhesive:** Butyl Rubber

Liner: Blue Polyethylene Film

Specifications: N/A

Colors: Aluminum

Available Size: 1.89 in x 10.9 yd (48 mm x 10 m)

Applications

- Permanent waterproofing and sealing uses
- Seals cracks and seams in gutters, roof alleys, eaves, hips, and ridges
- Sealing leaking pipes and hoses

- Repair gouges, rips, and tears in metal panels of trailers, shipping containers, and metal buildings
- Greenhouse patch and repair

Features Benefits

Butyl Rubber Adhesive	 Excellent resistance to cold and hot conditions Forms an instant air-tight and waterproof seals Permanent bond Non-staining
Aluminum Foil Backing	Resists UV exposure outdoorsConformable and paintableTough and durable

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	11 mils	279 μm	ASTM D-1000
Adhesion to Steel	75 oz/in	8.21 N/cm	PSTC-101
Tensile Strength	20 lb/in	35.03 N/cm	ASTM D-1000
Operating Temperature	20 to 200 °F	-6 to 93 °C	
Recommended Storage Conditions: 60 - 80 °F at 40-60% RH			
Standard Shelf Life (at 25 °C): 36 months from date of manufacture			

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

