



USG DUROCK® BRAND CEMENT BOARD WITH EDGEGUARD™

DESCRIPTION

Backerboard for tile and exterior finish systems

- Enhanced proprietary edge performance prevents spinout and crumbling
- Easy to cut and fasten
- Water durable and mold resistant
- Warranted for interior and exterior applications
- Exceptional tile bond
- Noncombustible

USG Durock® Brand Cement Board with EdgeGuard™ offers architects, builders and tile contractors a strong, water-durable tile base for tub and shower areas. Also an ideal underlayment for tile on floors and countertops in new construction and remodeling. Board is readily applied over wood or steel framing spaced 16 in. (406 mm) o.c. with corrosion-resistant wood screws, steel screws or hot-dipped galvanized roofing nails. After joints are treated, wall or floor tile is applied using latex-fortified mortar or Type I organic adhesive.

USG Durock® Brand Cement Board with EdgeGuard is preferred by many applicators as a base for directly applied finishes, tile, stone and thin brick used in building exteriors.

The 1/2 in. (12.7 mm) and 5/8 in. (15.9 mm) panels are Underwriters Laboratories Inc. (UL) Classified for fire resistance, and may be used in any UL Design where Type DCB panels are listed.

PRODUCT DATA

SIZES AND PACKAGING

| Size (thickness x width x length) ¹ | Units (pcs) ² |
|-------------------------------------------------------|--------------------------|
| 1/4 in. x 3 ft. x 5 ft. (6.4 mm x 915 mm x 1525 mm) | 60 |
| 1/2 in. x 32 in. x 5 ft. (12.7 mm x 813 mm x 1525 mm) | 50 |
| 1/2 in. x 3 ft. x 5 ft. (12.7 mm x 915 mm x 1525 mm) | 50 |
| 1/2 in. x 4 ft. x 8 ft. (12.7 mm x 1220 mm x 2440 mm) | 40 |
| 5/8 in. x 3 ft. x 5 ft. (15.9 mm x 915 mm x 1525 mm) | 40 |
| 5/8 in. x 4 ft. x 8 ft. (15.9 mm x 1220 mm x 2440 mm) | 32 |

1. Other lengths available. Contact your USG Sales Representative.
2. Shipped in packaging units as shown.

STANDARDS

USG Durock® Brand Cement Board with EdgeGuard exceeds ANSI standards for cementitious backer units (CBU). See ANSI A118.9 for test methods and specifications for CBU and ANSI A108.11 for interior installation of CBU. Exceeds industry standards as an exterior substrate for exterior finishes. Exceeds ASTM C1325 standards for nonasbestos fiber-mat reinforced cementitious backer units.

AVAILABILITY

USG Durock® Brand Cement Board with EdgeGuard is distributed throughout the United States. Contact a USG sales office or sales person for additional information.

COMPOSITION AND MATERIALS

USG Durock® Brand Cement Board with EdgeGuard is formed in a continuous process of aggregated portland cement slurry with polymer-coated, glass-fiber mesh completely encompassing edges, back and front surfaces. The edges are formed smooth with a patented poly-propylene fabric-wrapped edge. The ends are square cut.

DELIVERY AND STORAGE OF MATERIALS

All materials should be delivered and stored in their original unopened package and stored in an enclosed shelter providing protection from damage and exposure to the elements. Even though the stability and durability of USG Durock® Brand Cement Board with EdgeGuard is unaffected by the elements, moisture and temperature variations may have an effect on the bonding effectiveness of basecoats and adhesives. Store all USG Durock® Brand Cement Board with EdgeGuard panels flat.

ENVIRONMENTAL CONDITIONS

In cold weather and during USG Durock® Brand Cement Board with EdgeGuard panel and tile installation, temperatures within the building shall be maintained within the range of 40 to 100°F (5 to 38°C). Adequate ventilation shall be provided to carry off excess moisture.

INTERIOR APPLICATIONS

The building shall be enclosed and the HVAC system operating so that wood framing shall reach the moisture content it will reach in service. Do not install board when the board is wet.

EXTERIOR APPLICATIONS

In exterior applications, USG Durock® Brand Cement Board with EdgeGuard should not be left uncovered for a period of time exceeding 90 days. Discoloration or staining may occur due to exposure to the elements which will not affect performance of the panel. Finishes, leveling/skim coats and basecoats should not be applied to USG Durock® Brand Cement Board with EdgeGuard panel that is wet or frozen or that contains frost. After application, and for at least 24 hours, finishes, leveling/skim coats and basecoats should be effectively protected from rain and excessive moisture. In cold weather and during finish applications, USG Durock® Brand Cement Board with EdgeGuard panel, skim or basecoat, mortar, finish material and air temperature must be at least 40°F (5°C) and must remain at this temperature or higher for at least 24 hours after application. Hot and dry weather may affect working time of leveling/skim or basecoat and finish materials. Under rapid drying conditions, dampening or light fogging of board, leveling/skim or basecoat surface may be required to improve workability.

PANEL MICROCRACKING

USG Durock® Brand Cement Board with EdgeGuard is formulated to develop fine microcracking (also called multiple cracking) in the panel. The microcracking process helps to evenly relieve the stored strain energy in the product due to handling and installation, external loads and/or panel restrained movement. The presence of microcracks in the panel should not be considered a product defect.

INSTALLATION

- A.** Install cement board with ends and edges closely abutted, but not forced together. Stagger end joints in successive courses.
- B.** For flooring applications over a wood-based substrate, laminate USG Durock® Brand Cement Board with EdgeGuard to subfloor using Type 1 organic adhesive or latex-modified thin-set mortar suitable for bonding cement board. Fasten to subfloor with 1-1/4 in. (32 mm) USG Durock™ Brand Tile Backer Screws for wood framing (or equivalent) or 1-1/2 in. (38 mm) hot-dipped galvanized roofing nails spaced 8 in. (203 mm) o.c. in both directions with perimeter fasteners at least 3/8 in. (10 mm) and less than 5/8 in. (16 mm) from ends and edges. Drive nails and screws so that bottoms of heads are flush with panel surface to ensure firm panel contact with subfloor. Do not overdrive fasteners. Prefill joints with tile-setting mortar or adhesive and then immediately embed USG Durock™ Brand Tile Backer Tape and level joints.
- C.** For wall application, fasten USG Durock® Brand Cement Board with EdgeGuard panels to framing with specified fasteners. Drive fasteners into field of panels first, working toward ends and edges. Hold panels in firm contact with framing while driving fasteners. Space fasteners maximum 8 in. (203 mm) o.c. for walls, 6 in. (152 mm) o.c. for ceilings, with perimeter fasteners at least 3/8 in. (10 mm) and less than 5/8 in. (16 mm) from ends and edges. Drive nails and screws so bottoms of heads are flush with panel surface to ensure firm panel contact with framing. Do not overdrive fasteners. Approved fasteners include: USG Durock™ Brand Tile Backer Screws for steel framing (or equivalent), 1-1/4 in. (32 mm) and 1-5/8 in. (41 mm) for 14- to 20-gauge steel framing; USG Durock™ Brand Tile Backer Screws for wood framing (or equivalent), 1-1/4 in. (32 mm), 1-5/8 in. (41 mm) and 2-1/4 in. (57 mm) for wood framing. Nails (1-1/2 in. [38 mm] hot-dipped galvanized roofing nails). Prefill joints with tile-setting mortar or adhesive and then immediately embed USG Durock™ Brand Tile Backer Tape and level joints.

INSTALLATION CONT.

-
- D. Cement board should be cut to size with a knife and straight edge. A power saw should be used only if it is equipped with a dust-collection device. Installer should wear NIOSH/MSHA-approved dust mask.
 - E. If waterproofing is desired, use USG Durock™ Brand Waterproofing Membrane or USG Durock™ Brand Liquid Waterproofing Membrane. See *USG Durock™ Brand Waterproofing Membrane* submittal sheet (CB595) or *USG Durock™ Brand Liquid Waterproofing Membrane* submittal sheet (CB817) for product information.

Refer to *USG Durock® Brand Cement Board System Guide* (SA932EG) for complete installation information, including good design practices. For technical assistance, call USG Technical Service at 800.USG.4YOU (874-4968).

LIMITATIONS

1. Designed for positive or negative uniform loads up to 60 psf. For complete information on the use of USG Durock® Brand panels in exterior systems, consult uniform load table on Page 4 for applicable positive or negative uniform loads on wall systems.
2. Wall applications: Maximum stud spacing: 16 in. (406 mm) o.c. (24 in. [610 mm] o.c. for cavity shaft wall assembly). Framing shall be designed (based on stud properties alone) not to exceed L/360 deflection for tile and thin brick, L/240 for direct-applied exterior finish systems. Maximum fastener spacing: 8 in. (203 mm) o.c. for wood and steel framing; 6 in. (152 mm) o.c. for ceiling applications.
3. Floor applications: Maximum joist spacing 24 in. (610 mm) o.c. The subfloor system should be designed with a minimum deflection limit of L/360 for the span. Some finish materials may require a more rigid subassembly (such as large format tile and natural stone products). In these cases, follow the manufacturer's minimum requirements. The subfloor should be APA Span-Rated Plywood or OSB with an Exposure 1 classification or better with tongue and groove or back blocked at the unsupported edges.
4. In exterior applications, USG Durock® Brand Cement Board with EdgeGuard should not be left uncovered for a period of time exceeding 90 days. Discoloration or staining may occur due to exposure to the elements which will not affect performance of the panel.
5. Brittle coatings, such as epoxy coatings, are not recommended for use with USG Durock® Brand Cement Board with EdgeGuard. USG Durock® Brand Cement Board with EdgeGuard is intended for use with tile, thin brick and exterior stucco coatings only.
6. Maximum dead load for ceiling system is 7.5 psf.
7. Steel framing must be 20-gauge or heavier.
8. Do not use drywall screws or drywall nails. Do not use drywall joint tape.
9. Do not use 1/4 in. (6.4 mm) USG Durock® Brand Cement Board with EdgeGuard for wall or ceiling applications. 1/4 in. (6.4 mm) USG Durock® Cement Board with EdgeGuard is for use in interior applications only.
10. Do not use USG Durock® Brand Cement Board with EdgeGuard with vinyl flooring.
11. USG Durock® Brand Cement Board with EdgeGuard is not designed for use as a structural panel.
12. Maximum installed weight of the finish system should not exceed 15 psf.
13. USG Durock® Brand Cement Board with EdgeGuard panels should not be used in areas where they are exposed to temperatures that exceed 200°F (93°C).
14. In locations close to salt water or other challenging environments, design professionals should consider the use of stainless steel fasteners.
15. Do not use lightweight setting-type joint compounds or ready-mix joint compounds directly over USG Durock® Brand Cement Board with EdgeGuard.

TECHNICAL DATA

| Property | Unit of Measure | ASTM Test Method | 5/8 in. (15.9 mm) USG Durock® Brand Cement Board with EdgeGuard™ | 1/2 in. (12.7 mm) USG Durock® Brand Cement Board with EdgeGuard™ | 1/4 in. (6.4 mm) USG Durock® Brand Cement Board with EdgeGuard™ Underlayment |
|-------------------------------------------------------------------------------|---------------------------------------------------------------|------------------|------------------------------------------------------------------|------------------------------------------------------------------|------------------------------------------------------------------------------|
| Flexural strength | psi (MPa) | C947 | > 480 | > 750 | > 1000 (6.9) |
| Indentation strength | psi (MPa) | D2394 | > 1250 | > 1250 | > 1250 (8.6) |
| Shear bond strength | psi | ANSI A118.4 | > 50 | > 50 | > 50 |
| Water absorption | % by wt. 24 hrs. | C473 | 15 | 15 | 15 |
| Nail-pull resistance | lb. (0.375 in. [10 mm] head diameter, wet or dry) | C473 | > 90 | > 90 | — |
| Weight | psf (kg/m²) | C473 | 3 | 2.4 | < 1.9 (1.9) |
| Freeze/thaw resistance | procedure B, number of cycles with no deterioration | C666 | 100 | 100 | 100 |
| Mold resistance | — | G21 D3273 | Rating 0, No growth 10/10 | Rating 0, No growth 10/10 | Rating 0, No growth 10/10 |
| Noncombustibility | Pass/Fail | E136 | Pass | Pass | Pass |
| Surface-burning characteristics | flame/smoke | E84 | 0/0 | 0/0 | 0/0 |
| Thermal | "R"/k value | C518 | .49/1.27 | 0.39/1.27 | — |
| Standard method for evaluating ceramic floor tile installation systems | Passes cycles 1-6 | C627 | Light commercial | Light commercial | Light commercial |
| Minimum bending radius | ft. (requires special framing details available upon request) | — | 6 | 6 | — |

PRODUCT INFORMATION

See usg.com for the most up-to-date product information.

DANGER

Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause respiratory irritation. May cause cancer by inhalation of respirable crystalline silica. Do not handle until all safety precautions have been read and understood. Avoid breathing dust. Use only in a well-ventilated area, wear a NIOSH/MSHA-approved respirator. Wear protective gloves/protective clothing/eye protection. If swallowed, inhaled, or skin irritation occurs get medical attention. If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses and continue rinsing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Dispose of in accordance with local, state, and federal regulations. For more information call Product Safety: 800 507-8899 or see the SDS at usg.com

KEEP OUT OF REACH OF CHILDREN.

TRADEMARKS

The trademarks USG, DUROCK, EDGEGUARD, IT'S YOUR WORLD. BUILD IT., the USG logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

NOTE

The information in this document is subject to change without notice. USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document. Consult your USG Company sales office or representative for information. Products described here may not be available in all geographic markets.

NOTICE

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

UNIFORM LOAD—1/2 IN. (12.7 MM) USG DUROCK® BRAND CEMENT BOARD WITH EDGE GUARD™

| Stud Spacing | Fastener Spacing | Design Wind Load (1/240) | Design Wind Load (1/360) |
|-------------------------------------------------------|---------------------|--------------------------|--------------------------|
| 12 in. (305 mm) o.c. | 8 in. (203 mm) o.c. | 45 psf | 45 psf |
| | 6 in. (152 mm) o.c. | 60 psf | 60 psf |
| 16 in. (406 mm) o.c. | 8 in. (203 mm) o.c. | 33 psf | 30 psf |
| | 6 in. (152 mm) o.c. | 45 psf | 30 psf |
| 24 in. (610 mm) o.c. (for shaft wall assemblies only) | 8 in. (203 mm) o.c. | 13 psf | 9 psf |
| | 6 in. (152 mm) o.c. | 13 psf | 9 psf |

SUBMITTAL APPROVALS

| | |
|-------------------|-------------|
| Job Name | |
| Contractor | Date |

800 USG.4YOU
800 (874-4968)
usg.com

Manufactured by
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

CB399EG-USA-ENG/1-18
© 2018 USG Corporation and/or
its affiliates. All rights reserved.
Printed in USA

USG
IT'S YOUR WORLD. BUILD IT.®