

Matrix Wall Art



Matrix Wall Art offers the perfect blend of contemporary styling, durability and low maintenance. The versatility and style of these decorative panels make them suitable for installation both indoors and outdoors, and creating an interesting feature in what may be a blank space.

Matrix Wall Art is suited to all climatic conditions and will never rot, rust, swell or leach out their colour. These panels are not affected by continuous exposure to moist, salty air and will not stain walls or paving.

Fade resistant materials are used to ensure that Matrix Wall Art will never need painting. Painting is not recommended as conventional paints will not adhere to Matrix Wall Art.

Attractive designs of Matrix Wall Art allow an artistic installation suited to residential and commercial properties. All Matrix Wall Art can be further enhanced with background or recessed lighting.

- Available in 8 attractive contemporary designs •
- Made in Australia from 100% recycled plastic
- Will not rot, rust or need painting
- Do not contain harmful chemicals
- Resistant to mould and insects
- No sharp edges
- Covered by a 15 year structural warranty

THERMAL EXPANSION AND CONTRACTION

All plastic products will expand and contract with changes in temperature. If no allowance is made for thermal expansion and contraction during installation, this may cause damage to the product and void the warranty. The figures below show approximate panel size variation due to temperature changes:

	22.8" x 22.8"	45.7" x 22.8"
At 32°F	22.7" x 22.7"	45.5" x 22.7"
At 68°F	22.8" x 22.8"	45.7" x 22.8"
At 104°F	22.9" x 22.9"	45.9" x 22.9"
Expansion Gap:	0.2" x 0.2"	0.4" x 0.2"

Detailed instructions are available on our website: www.designflow.com.au

NOTE: These products are not approved for use as pool fencing.

INSTALLATION:

VERSATILE IN APPLICATION. EASY TO INSTALL.

Whatever your application, there is a simple installation method to provide the flexibility and ease of installation you need to create your outdoor masterpiece.

Installation in a flat (ceiling) position is not recommended and any resulting distortion will not be covered by the warranty.

FIXING METHODS

Installing Matrix Wall Asrt Panel using one of our recommended methods will ensure a professional and durable finish.

Note: Our 15 year Warranty only applies when the panel has been installed in accordance with our installation instructions.

Detailed installation instructions can be downloaded from www.designflow.com.au; these instructions must be carefully followed in accordance with the Warranty conditions.

INSTALLATION OPTIONS


There are several simple installation options that will ensure a professional and durable finish:

- Using a ball chain (supplied). Attach clips to the end of the ball chain. Mark the centre of the panel on the back using a tape measure, then mark screw positions equal distance from the centre. Secure the ball chain to the panel using the supplied screws.
- Using screws and washers - screw holes in the panel must be larger than the screws by 1/8" to allow fthe panel to expand and contract.
- Within a timber frame with grooved timbers or beading. Use 3/8" minimum groove depth and allow at least 1/4" for vertical and 1/8" for horizontal thermal expansion.

Using spacers to set the panel off the wall or fence will create a more 3-dimensional installation with shadow effects. Backlighting can be used to further enhance this effect.

INSTALLATION OPTIONS:






BALL CHAIN WITH PAN HEAD SCREWS

WIRE ROPE SLING WITH HOOK SCREWS



OVERSIZED HOLE WITH PAN HEAD SCREWS



OVERSIZED HOLE WITH SPACER AND PAN HEAD SCREWS



www.designflow.com.au

8 Silkwood Rise Carrum Downs Vic 3201 Australia

Tel:	(630) 851 2111
Fax:	(630) 851 7744
Email:	sales@designflow.com.au