

WIDE-FLEX 4 Product Code WF-100

DESCRIPTION	Detanted DVC tight fibered action composite common tang with diamond numbed name
(Speed,	Patented PVC tight fibered cotton composite corner tape with diamond-punched paper edging that is 4" wide, .025" thick and comes in 100' rolls.
` • ′	
Perfection and	Strait-Flex Wide-Flex 4 has PUR-laminated nose to protect against paper fuzz-ups during
Longevity)	finishing and sanding.
A DATA NIELA GEG	
ADVANTAGES	• Hard-to-Straighten Vaults, Butterfly Vaults, Outside Corners and Obtuse Angles.
	• Straightens small framing irregularities.
	 Memory-free hinge design allows for ease of installation and straighter corners.
	• Installs fast using standard compounds. No special tools or fasteners needed. No
	nail pops.
	• Inside 90 ° corners where a large fill or straightening is required, or where strength
	and speed of finish are required.
	Diamond-punched paper ensures ultimate bonding and faster drying.
	• Second coat of compound can be applied immediately-very light skim coat to finish.
	• Use in place of metal cornerbead.
	• Rustproof.
	No. Cracks. No Callbacks.
WARRANTY	Strait-Flex products are backed by a lifetime warranty. When applied to a sound structure,
WAKKANII	built on a permanent foundation using recommended application techniques, we warrant that
	these products will not edge-crack for the lifetime of the structure. Contact Strait-Flex
DIDECTIONS	International Inc for complete details.
DIRECTIONS	• Cut Strait-Flex to desired length. Adjust to desired angle.
	• Apply using a liberal coat of all-purpose compound with joint knife. Use tile
	setting compounds in wet areas.
	• Press Strait-Flex into wet compound. Adjust if necessary to create straight line
	and wipe down with joint knife. Immediately apply light skim coat and let dry.
	Apply final coat, let dry and sand.
STORAGE	Store in dry place protected from moisture.
Submittal Approva	ıls:
Joh Name:	

Job Name:	
Contractor:	Date: