

Safety Data Shee

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 12/30/2013 Date of issue: 12/30/2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

Product Identifier

Product Name: BBQ Cleaner Product Code: 57700

Intended Use of the Product

Use of the Substance/Mixture: Cleaner.

Name, Address, and Telephone of the Responsible Party

Company

STAR BRITE INC. 4041 SW 47th Avenue Fort Lauderdale, FL 33314 (954)587-6280

www.starbrite.com

Emergency Telephone Number

Emergency number : US: (800) 424-9300; International: (703) 527-3887 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Flam. Liq. 4 H227 Met. Corr. 1 H290 Acute Tox. 4 (Oral) H302 Skin Corr. 1A H314 Eye Dam. 1 H318

<u>Label Elements</u>

GHS-US Labeling

Hazard Pictograms (GHS-US)





Signal Word (GHS-US) : Danger

Hazard Statements (GHS-US) : H227 - Combustible liquid

H290 - May be corrosive to metals H302 - Harmful if swallowed

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

Precautionary Statements (GHS-US) : P210 - Keep away from heat, hot surfaces, open flames, sparks - No smoking.

P234 - Keep only in original container. P260 - Do not breathe vapors, spray, mist.

P264 - Wash hands, forearms, and exposed areas thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P280 - Wear eye protection, protective gloves, protective clothing.

P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER or doctor.

12/30/2013 EN (English US) 1/14

Version: 1.0

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P321 - Specific treatment (see Section 4).

P330 - If swallowed, rinse mouth.

P363 - Wash contaminated clothing before reuse.

P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO_2) for extinction.

P390 - Absorb spillage to prevent material damage.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P406 - Store in corrosive resistant container with a resistant inner liner.

P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Aquatic Acute 3

H402 - Harmful to aquatic life

P273 - Avoid release to the environment

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product identifier	% (w/w)	Classification (GHS-US)
Potassium hydroxide	(CAS No) 1310-58-3	7 - 13	Met. Corr. 1, H290
			Acute Tox. 3 (Oral), H301
			Skin Corr. 1A, H314
			Eye Dam. 1, H318
2-Butoxyethanol	(CAS No) 111-76-2	1-5	Flam. Liq. 4, H227
			Acute Tox. 4 (Oral), H302
			Acute Tox. 4 (Dermal), H312
			Acute Tox. 4 (Inhalation:vapour), H332
			Skin Irrit. 2, H315
			Eye Irrit. 2A, H319
Isopropyl alcohol	(CAS No) 67-63-0	1-5	Flam. Liq. 2, H225
			Eye Irrit. 2A, H319
			STOT SE 3, H336
Tetrasodium EDTA	(CAS No) 64-02-8	1 - 5	Acute Tox. 4 (Oral), H302
			Acute Tox. 4 (Inhalation:dust), H332
			Eye Dam. 1, H318
			Aquatic Acute 2, H401
D-Glucopyranose, oligomeric, decyl octyl glycosides	(CAS No) 68515-73-1	1-5	Eye Dam. 1, H318
Tetrapotassium pyrophosphate	(CAS No) 7320-34-5	0.5 - 1.5	Eye Irrit. 2A, H319

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible). **Inhalation:** If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persist.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Harmful if swallowed. Corrosive to eyes, respiratory system and skin.

12/30/2013 EN (English US) 2/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Inhalation: May be harmful if inhaled. **Skin Contact:** Corrosive. Causes burns. **Eye Contact:** Causes serious eye damage.

Ingestion: Harmful if swallowed. **Chronic Symptoms:** Not available

Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂).

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Flammable liquid and vapor.

Explosion Hazard: May form flammable/explosive vapor-air mixture.

Reactivity: Corrosive to metals. Reacts with (strong) oxidizers: (increased) risk of fire. Adding water to solution may generate large amounts of heat.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Do not allow run-off from fire fighting to enter drains or water courses.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Potassium oxides. Sodium oxides. Phosphorus oxides.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Use special care to avoid static electric charges. Keep away from heat/sparks/open flames/hot surfaces – No smoking. Do not get in eyes, on skin, or on clothing. Do not breathe vapour or mist. Do not allow contact with metals.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Eliminate ignition sources. Ventilate area. Stop leak if safe to do so.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material. Cautiously neutralize spilled liquid.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Use only non-sparking tools.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Contaminated work clothing should not be allowed out of the workplace.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations.

12/30/2013 EN (English US) 3/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep in fireproof place. Storage areas should be periodically checked for corrosion and integrity.

Incompatible Materials: Strong acids. Strong oxidizers.

Special Rules on Packaging: Store in original container or corrosive resistant and/or lined container. Corrosive to metal.

Specific End Use(s)

Cleaner.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Potassium hydroxide (1310-	58-3)	
USA ACGIH	ACGIH Ceiling (mg/m³)	2 mg/m³
USA NIOSH	NIOSH REL (ceiling) (mg/m³)	2 mg/m³
Alberta	OEL Ceiling (mg/m³)	2 mg/m³
British Columbia	OEL Ceiling (mg/m³)	2 mg/m³
Manitoba	OEL Ceiling (mg/m³)	2 mg/m³
New Brunswick	OEL Ceiling (mg/m³)	2 mg/m³
Newfoundland & Labrador	OEL Ceiling (mg/m³)	2 mg/m³
Nova Scotia	OEL Ceiling (mg/m³)	2 mg/m³
Nunavut	OEL Ceiling (mg/m³)	2 mg/m³
Northwest Territories	OEL Ceiling (mg/m³)	2 mg/m³
Ontario	OEL Ceiling (mg/m³)	2 mg/m³
Prince Edward Island	OEL Ceiling (mg/m³)	2 mg/m³
Québec	PLAFOND (mg/m³)	2 mg/m³
Saskatchewan	OEL Ceiling (mg/m³)	2 mg/m³
Yukon	OEL Ceiling (mg/m³)	2 mg/m³
2-Butoxyethanol (111-76-2)	, 5, 5, 7	
Mexico	OEL TWA (mg/m³)	120 mg/m³
Mexico	OEL TWA (ppm)	26 ppm
Mexico	OEL STEL (mg/m³)	360 mg/m³
Mexico	OEL STEL (ppm)	75 ppm
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	240 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	24 mg/m³
USA NIOSH	NIOSH REL (TWA) (ppm)	5 ppm
USA IDLH	US IDLH (ppm)	700 ppm
Alberta	OEL TWA (mg/m³)	97 mg/m³
Alberta	OEL TWA (ppm)	20 ppm
British Columbia	OEL TWA (ppm)	20 ppm
Manitoba	OEL TWA (ppm)	20 ppm
New Brunswick	OEL TWA (mg/m³)	121 mg/m³
New Brunswick	OEL TWA (ppm)	25 ppm
Newfoundland & Labrador	OEL TWA (ppm)	20 ppm
Nova Scotia	OEL TWA (ppm)	20 ppm
Nunavut	OEL STEL (mg/m³)	360 mg/m³
Nunavut	OEL STEL (ppm)	75 ppm
Nunavut	OEL TWA (mg/m³)	120 mg/m³
Nunavut	OEL TWA (ppm)	25 ppm
Northwest Territories	OEL STEL (mg/m³)	360 mg/m³
Northwest Territories	OEL STEL (ppm)	75 ppm
Northwest Territories	OEL TWA (mg/m³)	120 mg/m³

12/30/2013 EN (English US) 4/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Northwest Territories OEL TWA (ppm) 25 ppm Ontario OEL TWA (ppm) 20 ppm Prince Edward Island OEL TWA (ppm) 20 ppm Ouebec VEMP (mg/m²) 97 mg/m² Québec VEMP (mg/m²) 30 ppm Saskatchewan OEL TWA (ppm) 20 ppm Saskatchewan OEL TWA (ppm) 20 ppm Yukon OEL STEL (ppm) 150 ppm Yukon OEL STEL (ppm) 150 ppm Yukon OEL TWA (mg/m²) 240 mg/m² Yukon OEL TWA (mg/m²) 980 mg/m² Wexico OEL TWA (mg/m²) 980 mg/m² Mexico OEL TWA (mg/m²) 980 mg/m² Mexico OEL STEL (mg/m²) 1225 mg/m² Mexico OEL STEL (mg/m²) 1225 mg/m² USA ACGIH ACGIH TWA (ppm) 200 ppm USA ACGIH ACGIH TWA (ppm) 400 ppm USA OSHA OSHA PEL (TWA) (mg/m²) 980 mg/m² USA OSHA OSHA PEL (TWA) (mg/m²) 980 mg/m² USA NIOSH NIOSH REL (STEL (p	No who we at Townit and a	OFL TIMA (nome)	25
Prince Edward Island OEL TWA (ppm) 20 ppm Ouébec VEMP (mpm)* 20 rm/m² Ouébec VEMP (ppm) 20 ppm Saskatchewan OEL TWA (ppm) 20 ppm Saskatchewan OEL TWA (ppm) 20 ppm Yukon OEL STEL (mg/m²) 720 mg/m² Yukon OEL STEL (ppm) 150 ppm Yukon OEL TWA (mg/m²) 240 mg/m² Yukon OEL TWA (ppm) 50 ppm Mexico OEL TWA (ppm) 400 ppm Mexico OEL TWA (mg/m²) 980 mg/m² Mexico OEL STEL (mg/m²) 1225 mg/m² Mexico OEL STEL (ppm) 500 ppm Mexico OEL STEL (ppm) 500 ppm Mexico OEL STEL (ppm) 400 ppm USA ACGIH ACGIH TWA (ppm) 400 ppm USA ACGIH ACGIH TWA (ppm) 400 ppm USA OSHA OSHA PEL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (STEL) (ppm) 400 ppm USA NIOSH NIOSH REL (STEL) (mg/m²) 980 mg			
Québec VEMP (ppm) 20 ppm Québec VEMP (ppm) 20 ppm Saskatchewan OEL STEL (ppm) 30 ppm Saskatchewan OEL STEL (ppm) 20 ppm Yukon OEL STEL (ppm) 150 ppm Yukon OEL STEL (ppm) 150 ppm Yukon OEL TWA (ppm) 50 ppm Vakon OEL TWA (ppm) 50 ppm Isopropyl alcohol (67-63-0) Image: Ima			
Québec VEMP (ppm) 20 ppm Saskatchewan OEL STEL (ppm) 30 ppm Saskatchewan OEL TWA (ppm) 20 ppm Yukon OEL STEL (pm) 150 ppm Yukon OEL TWA (ppm) 150 ppm Yukon OEL TWA (ppm) 50 ppm Yukon OEL TWA (ppm) 50 ppm Yukon OEL TWA (ppm) 240 mg/m² Yukon OEL TWA (ppm) 50 ppm Mexico OEL TWA (mg/m²) 980 mg/m² Mexico OEL TWA (ppm) 400 ppm Mexico OEL STEL (mg/m²) 1225 mg/m² Mexico OEL STEL (ppm) 500 ppm USA ACGIH ACGIH TWA (ppm) 200 ppm USA ACGIH ACGIH STEL (ppm) 400 ppm USA NIOSH OSHA PEL (TWA) (mg/m²) 980 mg/m² USA NIOSH NIOSH REL (TWA) (mg/m²) 980 mg/m² USA NIOSH NIOSH REL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (STEL) (ppm) 500 ppm USA DIL USA NIOSH NIOSH REL (STEL)			· ·
Saskatchewan OEL STEL (ppm) 30 ppm Saskatchewan OEL TWA (ppm) 20 ppm Yukon OEL STEL (ppm) 150 ppm Yukon OEL TWA (mg/m²) 240 mg/m² Yukon OEL TWA (ppm) 30 ppm Isopropyl alcohol (67-63-0) Westico OEL TWA (ppm) 400 ppm Mexico OEL TWA (ppm) 400 ppm Mexico OEL STEL (mg/m²) 1225 mg/m² Mexico OEL STEL (mg/m²) 1225 mg/m² Mexico OEL STEL (mpm) 500 ppm USA AGGIH AGGIH TWA (ppm) 200 ppm USA AGGIH AGGIH TWA (ppm) 400 ppm USA OSHA OSHA PEL (TWA) (mg/m²) 980 mg/m² USA NIOSH NIOSH REL (TWA) (mg/m²) 980 mg/m² USA NIOSH NIOSH REL (STEL) (mg/m²) 400 ppm USA NIOSH NIOSH REL (STEL) (mg/m²) 400 ppm USA NIOSH NIOSH REL (STEL) (mg/m²) 400 ppm USA NIOSH NIOSH REL (STEL) (mg/m²) 1225 mg/m² USA NIOSH NIOSH REL (STEL) (mg/m²) 400			
Saskatchewan OEL TWA (ppm) 20 ppm Yukon OEL STEL (ng/m²) 720 mg/m² Yukon OEL TWA (mg/m²) 240 mg/m² Yukon OEL TWA (ppm) 50 ppm Isopropyl alcohol (67-63-0) Wexico OEL TWA (mg/m²) 980 mg/m² Mexico OEL TWA (ppm) 400 ppm Mexico OEL STEL (mg/m²) 1225 mg/m² Mexico OEL STEL (ppm) 500 ppm Mexico OEL STEL (ppm) 200 ppm Mexico OEL STEL (ppm) 200 ppm USA ACGIH ACGIH STEL (ppm) 400 ppm USA ACGIH ACGIH STEL (ppm) 400 ppm USA OSHA OSHA PEL (TWA) (mg/m²) 980 mg/m² USA NIOSH NIOSH REL (TWA) (mg/m²) 980 mg/m² USA NIOSH NIOSH REL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (STEL) (mg/m²) 1225 mg/m² USA NIOSH NIOSH REL (STEL) (mg/m²) 1225 mg/m² USA IDLH US IDLH (ppm) 200 ppm USA IDLH US IDLH (ppm) 200 ppm <t< td=""><td></td><td></td><td>1 1</td></t<>			1 1
Yukon OEL STEL (ng/m³) 720 mg/m³ Yukon OEL TWA (ng/m²) 240 mg/m³ Yukon OEL TWA (ppm) 50 ppm Isopropyl alcohol (67-63-0) Wexico OEL TWA (mg/m²) 980 mg/m³ Mexico OEL TWA (ppm) 400 ppm Mexico OEL STEL (mg/m²) 1225 mg/m² Mexico OEL STEL (mg/m²) 200 ppm USA ACGIH ACGIH TWA (ppm) 200 ppm USA ACGIH ACGIH TWA (ppm) 200 ppm USA OSHA OSHA PEL (TWA) (mg/m²) 980 mg/m³ USA OSHA OSHA PEL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (TWA) (mg/m²) 980 mg/m³ USA NIOSH NIOSH REL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (STEL) (mg/m³) 1225 mg/m³ USA NIOSH NIOSH REL (STEL) (mg/m³) 1220 mg/m³ USA DICH (ppm) 200			
Vukon OEL STEL (ppm) 150 ppm Yukon OEL TWA (mg/m³) 240 mg/m³ Yukon OEL TWA (mg/m³) 240 mg/m³ Vikon OEL TWA (mg/m³) 50 ppm Mexico OEL TWA (mg/m³) 980 mg/m³ Mexico OEL STEL (mg/m³) 1225 mg/m³ Mexico OEL STEL (mg/m³) 1225 mg/m³ Mexico OEL STEL (ppm) 500 ppm USA ACGIH ACGIH TWA (ppm) 200 ppm USA ACGIH ACGIH STEL (ppm) 400 ppm USA OSHA OSHA PEL (TWA) (mg/m³) 980 mg/m³ USA NIOSH NIOSH REL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (TWA) (mg/m³) 980 mg/m³ USA NIOSH NIOSH REL (STEL) (mg/m³) 1225 mg/m³ USA NIOSH NIOSH REL (STEL) (mg/m³) 1225 mg/m³ USA NIOSH NIOSH REL (STEL) (mg/m³) 1225 mg/m³ Alberta OEL STEL (mg/m³) 200 ppm Alberta OEL STEL (mg/m³) 984 mg/m³ Alberta OEL TWA (ppm) 200 ppm British			
Yukon OEL TWA (mg/m²) 240 mg/m³ Yukon OEL TWA (ppm) 50 ppm Isopropyl alcohol (67-63-0) Soppopyl alcohol (67-63-0) Mexico OEL TWA (ppm) 400 ppm Mexico OEL STEL (ppm) 400 ppm Mexico OEL STEL (ppm) 500 ppm USA ACGIH ACGIH TWA (ppm) 200 ppm USA ACGIH ACGIH STEL (ppm) 400 ppm USA OSHA OSHA PEL (TWA) (ppm) 400 ppm USA OSHA OSHA PEL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (STEL) (ppm) 500 ppm USA NIOSH NIOSH REL (STEL) (ppm) 200 ppm USA NIOSH NIOSH REL (STEL) (ppm) 400 ppm USA NIOSH NIOSH REL (STEL) (ppm) 200 ppm		, ,	
Soppy alcohol (67-63-0)			
Isopropy alcohol (67-63-0) Mexico		, . ,	
Mexico OEL TWA (ng/m³) 980 mg/m³ Mexico OEL TWA (ppm) 400 ppm Mexico OEL STEL (mg/m²) 1225 mg/m³ Mexico OEL STEL (ppm) 500 ppm USA ACGIH ACGIH TWA (ppm) 200 ppm USA ACGIH ACGIH STEL (ppm) 400 ppm USA OSHA OSHA PEL (TWA) (mg/m²) 980 mg/m² USA OSHA OSHA PEL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (STEL) (ppm) 500 ppm USA NIOSH NIOSH REL (STEL) (ppm) 200 ppm USA NIOSH NIOSH REL (STEL) (ppm) 400 ppm	Yukon	OEL TWA (ppm)	50 ppm
Mexico OEL TWA (ppm) 400 ppm Mexico OEL STEL (mg/m³) 1225 mg/m³ Mexico OEL STEL (ppm) 500 ppm USA ACGIH ACGIH TWA (ppm) 200 ppm USA ACGIH ACGIH STEL (ppm) 400 ppm USA OSHA OSHA PEL (TWA) (mg/m³) 980 mg/m³ USA OSHA OSHA PEL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (STEL) (ppm) 500 ppm USA NIOSH NIOSH REL (STEL) (ppm) 500 ppm USA DILH US IDLH (ppm) 2000 ppm (10% LEL) Alberta OEL STEL (mg/m³) 984 mg/m³ Alberta OEL STEL (ppm) 400 ppm Alberta OEL TWA (mg/m³) 492 mg/m³ Alberta OEL TWA (ppm) 200 ppm British Columbia OEL TWA (ppm) 200 ppm British Columbia OEL TWA (ppm) 200 ppm Manitoba OEL STEL (ppm) 400 ppm Manito	Isopropyl alcohol (67-63-0)		
Mexico OEL STEL (mg/m³) 1225 mg/m³ Mexico OEL STEL (ppm) 500 ppm USA ACGIH ACGIH TWA (ppm) 200 ppm USA ACGIH ACGIH STEL (ppm) 400 ppm USA OSHA OSHA PEL (TWA) (mg/m³) 980 mg/m³ USA OSHA OSHA PEL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (STEL) (mg/m³) 1225 mg/m³ USA NIOSH NIOSH REL (STEL) (ppm) 500 ppm USA NIOSH NIOSH REL (TWA) (ppm) 200 ppm USA NIOSH NIOSH REL (TWA) (ppm) 200 ppm USA NIOSH NIOSH REL (TWA) (ppm) 200 ppm Alberta OEL TWA (ppm) 2	Mexico	OEL TWA (mg/m³)	980 mg/m³
Mexico OEL STEL (ppm) 500 ppm USA ACGIH ACGIH TWA (ppm) 200 ppm USA ACGIH ACGIH STEL (ppm) 400 ppm USA OSHA OSHA PEL (TWA) (mg/m³) 980 mg/m³ USA OSHA OSHA PEL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (STEL) (mg/m³) 1225 mg/m³ USA NIOSH NIOSH REL (STEL) (ppm) 500 ppm USA NIOSH NIOSH REL (STEL) (ppm) 500 ppm USA NIOSH NIOSH REL (STEL) (ppm) 2000 ppm (10% LEL) USA NIOSH NIOSH REL (STEL) (ppm) 2000 ppm USA NIOSH NIOSH REL (STEL) (ppm) 200 ppm USA NIOSH NIOSH REL (STEL) (ppm) 400 ppm USA NIOSH NIOSH REL (STEL) (ppm) 400 ppm USA NIOSH OEL STEL (ppm) 400 ppm Alberta OEL STEL (mg/m³) 492 mg/m³ Alberta OEL STEL (ppm) 400 ppm British Columbia OEL STEL (ppm)	Mexico	OEL TWA (ppm)	
Mexico OEL STEL (ppm) 500 ppm USA ACGIH ACGIH TWA (ppm) 200 ppm USA ACGIH ACGIH STEL (ppm) 400 ppm USA OSHA OSHA PEL (TWA) (mg/m³) 980 mg/m³ USA OSHA OSHA PEL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (STEL) (mg/m³) 1225 mg/m³ USA NIOSH NIOSH REL (STEL) (ppm) 500 ppm USA NIOSH NIOSH REL (STEL) (ppm) 500 ppm USA NIOSH NIOSH REL (STEL) (ppm) 2000 ppm (10% LEL) USA NIOSH NIOSH REL (STEL) (ppm) 2000 ppm USA NIOSH NIOSH REL (STEL) (ppm) 200 ppm USA NIOSH NIOSH REL (STEL) (ppm) 400 ppm USA NIOSH NIOSH REL (STEL) (ppm) 400 ppm USA NIOSH OEL STEL (ppm) 400 ppm Alberta OEL STEL (mg/m³) 492 mg/m³ Alberta OEL STEL (ppm) 400 ppm British Columbia OEL STEL (ppm)	Mexico	OEL STEL (mg/m³)	1225 mg/m³
USA ACGIH ACGIH TWA (ppm) 200 ppm USA ACGIH ACGIH STEL (ppm) 400 ppm USA OSHA OSHA PEL (TWA) (mg/m³) 980 mg/m³ USA OSHA OSHA PEL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (STEL) (mg/m³) 1225 mg/m³ USA NIOSH NIOSH REL (STEL) (ppm) 500 ppm USA NIOSH NIOSH REL (STEL) (ppm) 2000 ppm (10% LEL) USA DIDH US IDIH (ppm) 2000 ppm (10% LEL) Alberta OEL STEL (pg/m³) 984 mg/m³ Alberta OEL STEL (ppm) 400 ppm Alberta OEL TWA (mg/m³) 492 mg/m³ Alberta OEL TWA (mg/m³) 492 mg/m³ Alberta OEL TWA (ppm) 200 ppm British Columbia OEL TWA (ppm) 200 ppm British Columbia OEL STEL (ppm) 400 ppm Manitoba OEL STEL (ppm) 400 ppm New Brunswick OEL STEL (ppm) 500 ppm	Mexico	OEL STEL (ppm)	
USA ACGIH ACGIH STEL (ppm) 400 ppm USA OSHA OSHA PEL (TWA) (mg/m³) 980 mg/m³ USA OSHA OSHA PEL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (TWA) (mg/m³) 980 mg/m³ USA NIOSH NIOSH REL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (STEL) (mg/m³) 1225 mg/m³ USA NIOSH NIOSH REL (STEL) (mg/m³) 500 ppm USA NIOSH NIOSH REL (STEL) (mg/m³) 984 mg/m³ Alberta OEL STEL (mg/m³) 984 mg/m³ Alberta OEL STEL (mg/m³) 492 mg/m³ Alberta OEL STEL (mg/m³) 492 mg/m³ Alberta OEL TWA (ppm) 200 ppm British Columbia OEL STEL (ppm) 400 ppm Manitoba OEL STEL (ppm) 400 ppm Mew Brunswick OEL STEL (mg/m³) 1230 mg/m³ New Brunswick OEL STEL (mg/m³)	USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA OSHA OSHA PEL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (TWA) (mg/m³) 980 mg/m³ USA NIOSH NIOSH REL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (STEL) (mg/m³) 1225 mg/m³ USA NIOSH NIOSH REL (STEL) (ppm) 500 ppm USA DILH US IDLH (ppm) 2000 ppm (10% LEL) Alberta OEL STEL (mg/m³) 984 mg/m³ Alberta OEL STEL (ppm) 400 ppm Alberta OEL TWA (mg/m³) 492 mg/m³ Alberta OEL STEL (ppm) 400 ppm British Columbia OEL STEL (ppm) 400 ppm British Columbia OEL TWA (ppm) 200 ppm Manitoba OEL TWA (ppm) 200 ppm Manitoba OEL TWA (ppm) 200 ppm New Brunswick OEL STEL (mg/m³) 1230 mg/m³ New Brunswick OEL STEL (ppm) 500 ppm New Brunswick OEL TWA (mg/m³) 983 mg/m³ New Brunswick OEL TWA (mg/m³) 983 mg/m³ New Gotia OEL STEL (ppm) 400 ppm	USA ACGIH	ACGIH STEL (ppm)	400 ppm
USA NIOSH NIOSH REL (TWA) (mg/m³) 980 mg/m³ USA NIOSH NIOSH REL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (STEL) (mg/m³) 1225 mg/m³ USA NIOSH NIOSH REL (STEL) (ppm) 500 ppm USA NIOSH NIOSH REL (STEL) (ppm) 400 ppm Alberta OEL STEL (ppm) 400 ppm Alberta OEL TWA (mg/m³) 492 mg/m³ Alberta OEL TWA (mg/m³) 492 mg/m³ Alberta OEL TWA (ppm) 200 ppm British Columbia OEL STEL (ppm) 400 ppm British Columbia OEL STEL (ppm) 400 ppm Manitoba OEL STEL (ppm) 400 ppm Manitoba OEL STEL (ppm) 500 ppm New Brunswick OEL TWA (mg/m³) 933 mg/m³	USA OSHA	OSHA PEL (TWA) (mg/m³)	980 mg/m³
USA NIOSH NIOSH REL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (STEL) (mg/m³) 1225 mg/m³ USA NIOSH NIOSH REL (STEL) (ppm) 500 ppm USA IDLH US IDLH (ppm) 2000 ppm (10% LEL) Alberta OEL STEL (mg/m³) 984 mg/m³ Alberta OEL STEL (ppm) 400 ppm Alberta OEL TWA (mg/m³) 492 mg/m³ Alberta OEL TWA (ppm) 200 ppm British Columbia OEL STEL (ppm) 400 ppm British Columbia OEL STEL (ppm) 400 ppm Manitoba OEL STEL (ppm) 400 ppm Manitoba OEL STEL (ppm) 400 ppm New Brunswick OEL STEL (mg/m³) 1230 mg/m³ New Brunswick OEL STEL (ppm) 500 ppm New Brunswick OEL TWA (mg/m³) 983 mg/m³ New Foundland & Labrador OEL STEL (ppm) 400 ppm Newfoundland & Labrador OEL STEL (ppm) 400 ppm Nova Scotia OEL STEL (ppm) 200 ppm Nunavut OEL STEL (mg/m³) 1228 mg/m³ </td <td>USA OSHA</td> <td>OSHA PEL (TWA) (ppm)</td> <td>400 ppm</td>	USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm
USA NIOSH NIOSH REL (TWA) (ppm) 400 ppm USA NIOSH NIOSH REL (STEL) (mg/m³) 1225 mg/m³ USA NIOSH NIOSH REL (STEL) (ppm) 500 ppm USA IDLH US IDLH (ppm) 2000 ppm (10% LEL) Alberta OEL STEL (mg/m³) 984 mg/m³ Alberta OEL STEL (ppm) 400 ppm Alberta OEL TWA (mg/m³) 492 mg/m³ Alberta OEL TWA (ppm) 200 ppm British Columbia OEL STEL (ppm) 400 ppm British Columbia OEL STEL (ppm) 400 ppm Manitoba OEL STEL (ppm) 400 ppm Manitoba OEL STEL (ppm) 400 ppm New Brunswick OEL STEL (mg/m³) 1230 mg/m³ New Brunswick OEL STEL (ppm) 500 ppm New Brunswick OEL TWA (mg/m³) 983 mg/m³ New Foundland & Labrador OEL STEL (ppm) 400 ppm Newfoundland & Labrador OEL STEL (ppm) 400 ppm Nova Scotia OEL STEL (ppm) 200 ppm Nunavut OEL STEL (mg/m³) 1228 mg/m³ </td <td>USA NIOSH</td> <td>NIOSH REL (TWA) (mg/m³)</td> <td>980 mg/m³</td>	USA NIOSH	NIOSH REL (TWA) (mg/m³)	980 mg/m³
USA NIOSH NIOSH REL (STEL) (mg/m³) 1225 mg/m³ USA NIOSH NIOSH REL (STEL) (ppm) 500 ppm USA IDLH US IDLH (ppm) 2000 ppm (10% LEL) Alberta OEL STEL (mg/m³) 984 mg/m³ Alberta OEL STEL (ppm) 400 ppm Alberta OEL TWA (ppm) 200 ppm British Columbia OEL TWA (ppm) 200 ppm British Columbia OEL STEL (ppm) 400 ppm Manitoba OEL STEL (ppm) 400 ppm Manitoba OEL STEL (mg/m³) 1230 mg/m³ New Brunswick OEL STEL (ppm) 500 ppm New Brunswick OEL STEL (ppm) 500 ppm New Brunswick OEL TWA (mg/m³) 983 mg/m³ New Brunswick OEL TWA (ppm) 400 ppm New Brunswick OEL TWA (ppm) 400 ppm New Brunswick OEL TWA (ppm) 400 ppm New Goundland & Labrador OEL TWA (ppm) 400 ppm Nova Scotia OEL STEL (ppm) 400 ppm Nova Scotia OEL STEL (mg/m³) 1228 mg/m³ <td>USA NIOSH</td> <td>NIOSH REL (TWA) (ppm)</td> <td></td>	USA NIOSH	NIOSH REL (TWA) (ppm)	
USA NIOSH NIOSH REL (STEL) (ppm) 500 ppm USA IDLH US IDLH (ppm) 2000 ppm (10% LEL) Alberta OEL STEL (mg/m³) 984 mg/m³ Alberta OEL TWA (mg/m³) 492 mg/m³ Alberta OEL TWA (ppm) 200 ppm British Columbia OEL STEL (ppm) 400 ppm British Columbia OEL STEL (ppm) 400 ppm Manitoba OEL STEL (ppm) 400 ppm Manitoba OEL TWA (ppm) 200 ppm Mew Brunswick OEL STEL (mg/m³) 1230 mg/m³ New Brunswick OEL STEL (ppm) 500 ppm New Brunswick OEL TWA (mg/m³) 983 mg/m³ New Brunswick OEL TWA (mg/m³) 983 mg/m³ New Gundland & Labrador OEL STEL (ppm) 400 ppm Newfoundland & Labrador OEL STEL (ppm) 400 ppm Nova Scotia OEL TWA (ppm) 200 ppm Nova Scotia OEL STEL (mg/m³) 1228 mg/m³ Nunavut OEL STEL (mg/m³) 1228 mg/m³ Nunavut OEL STEL (mg/m³) 983 mg/m³	USA NIOSH		
USA IDLH US IDLH (ppm) 2000 ppm (10% LEL) Alberta OEL STEL (mg/m³) 984 mg/m³ Alberta OEL STEL (ppm) 400 ppm Alberta OEL TWA (mg/m³) 492 mg/m³ Alberta OEL TWA (ppm) 200 ppm British Columbia OEL STEL (ppm) 400 ppm British Columbia OEL TWA (ppm) 200 ppm Manitoba OEL STEL (ppm) 400 ppm Manitoba OEL TWA (ppm) 200 ppm Manitoba OEL STEL (mg/m³) 1230 mg/m³ New Brunswick OEL STEL (mg/m³) 1230 mg/m³ New Brunswick OEL STEL (ppm) 500 ppm New Brunswick OEL TWA (mg/m³) 983 mg/m³ New Brunswick OEL TWA (ppm) 400 ppm New Brunswick OEL STEL (ppm) 400 ppm New Brunswick OEL STEL (ppm) 400 ppm New Groundland & Labrador OEL STEL (ppm) 400 ppm Nova Scotia OEL STEL (ppm) 400 ppm Nova Scotia OEL STEL (ppm) 500 ppm			
Alberta OEL STEL (ng/m³) 984 mg/m³ Alberta OEL STEL (ppm) 400 ppm Alberta OEL TWA (ng/m³) 492 mg/m³ Alberta OEL TWA (ppm) 200 ppm British Columbia OEL STEL (ppm) 400 ppm British Columbia OEL TWA (ppm) 200 ppm Manitoba OEL STEL (ppm) 400 ppm Manitoba OEL TWA (ppm) 200 ppm New Brunswick OEL STEL (ng/m³) 1230 mg/m³ New Brunswick OEL STEL (ppm) 500 ppm New Brunswick OEL TWA (mg/m³) 983 mg/m³ New Brunswick OEL TWA (mg/m³) 983 mg/m³ New Funswick OEL TWA (ppm) 400 ppm Newfoundland & Labrador OEL STEL (ppm) 400 ppm Newfoundland & Labrador OEL TWA (ppm) 200 ppm Nova Scotia OEL STEL (ppm) 400 ppm Nova Scotia OEL STEL (mg/m³) 1228 mg/m³ Nunavut OEL STEL (ppm) 500 ppm Nunavut OEL TWA (mg/m³) 983 mg/m³	USA IDLH		
Alberta OEL STEL (ppm) 400 ppm Alberta OEL TWA (mg/m³) 492 mg/m³ Alberta OEL TWA (ppm) 200 ppm British Columbia OEL STEL (ppm) 400 ppm Manitoba OEL STEL (ppm) 400 ppm Manitoba OEL STEL (ppm) 200 ppm Manitoba OEL STEL (ppm) 400 ppm New Brunswick OEL STEL (ppm) 500 ppm New Brunswick OEL STEL (ppm) 400 ppm New Brunswick OEL STEL (ppm) 500 ppm New Brunswick OEL TWA (ppm) 400 ppm New Brunswick OEL TWA (ppm) 400 ppm New Brunswick OEL TWA (ppm) 400 ppm Newfoundland & Labrador OEL STEL (ppm) 400 ppm Nova Scotia OEL STEL (ppm) 200 ppm Nova Scotia OEL STEL (ppm) 400 ppm Nova Scotia OEL STEL (ppm) 200 ppm Nunavut OEL STEL (ppm) 500 ppm Nunavut OEL STEL (ppm) 900 ppm Nunavut OEL STEL (ppm) 500 ppm Nunavut OEL TWA (ppm) 983 mg/m³ Nunavut OEL TWA (ppm) 400 ppm Northwest Territories OEL STEL (ppm) 500 ppm Northwest Territories OEL STEL (ppm) 500 ppm	Alberta	*** ***	,
Alberta OEL TWA (mg/m³) 492 mg/m³ Alberta OEL TWA (ppm) 200 ppm British Columbia OEL STEL (ppm) 400 ppm British Columbia OEL TWA (ppm) 200 ppm Manitoba OEL STEL (ppm) 400 ppm Manitoba OEL TWA (ppm) 200 ppm New Brunswick OEL STEL (mg/m³) 1230 mg/m³ New Brunswick OEL STEL (ppm) 500 ppm New Brunswick OEL TWA (mg/m³) 983 mg/m³ New Brunswick OEL TWA (ppm) 400 ppm Newfoundland & Labrador OEL STEL (ppm) 400 ppm Newfoundland & Labrador OEL TWA (ppm) 200 ppm Nova Scotia OEL TWA (ppm) 200 ppm Nova Scotia OEL TWA (ppm) 200 ppm Nunavut OEL STEL (mg/m³) 1228 mg/m³ Nunavut OEL STEL (ppm) 500 ppm Nunavut OEL STEL (mg/m³) 983 mg/m³ Nunavut OEL TWA (mg/m³) 983 mg/m³ Northwest Territories OEL STEL (ppm) 500 ppm	Alberta		
Alberta OEL TWA (ppm) 200 ppm British Columbia OEL STEL (ppm) 400 ppm British Columbia OEL TWA (ppm) 200 ppm Manitoba OEL STEL (ppm) 400 ppm Manitoba OEL STEL (ppm) 200 ppm Manitoba OEL STEL (ppm) 200 ppm Mew Brunswick OEL STEL (mg/m³) 1230 mg/m³ New Brunswick OEL STEL (ppm) 500 ppm New Brunswick OEL TWA (ppm) 400 ppm New Brunswick OEL TWA (ppm) 400 ppm New Brunswick OEL TWA (ppm) 400 ppm Newfoundland & Labrador OEL STEL (ppm) 400 ppm Nova Scotia OEL STEL (ppm) 400 ppm Nova Scotia OEL STEL (ppm) 400 ppm Nunavut OEL STEL (ppm) 500 ppm Nunavut OEL STEL (ppm) 900 ppm Nunavut OEL STEL (ppm) 500 ppm Nunavut OEL STEL (ppm) 500 ppm Nunavut OEL STEL (mg/m³) 983 mg/m³ Nunavut OEL TWA (ppm) 400 ppm Northwest Territories OEL STEL (mg/m³) 1228 mg/m³ Northwest Territories OEL STEL (ppm) 500 ppm	Alberta		• •
British Columbia OEL STEL (ppm) 400 ppm British Columbia OEL TWA (ppm) 200 ppm Manitoba OEL STEL (ppm) 400 ppm Manitoba OEL TWA (ppm) 200 ppm Manitoba OEL TWA (ppm) 200 ppm New Brunswick OEL STEL (mg/m³) 1230 mg/m³ New Brunswick OEL STEL (ppm) 500 ppm New Brunswick OEL TWA (mg/m³) 983 mg/m³ New Brunswick OEL TWA (ppm) 400 ppm Newfoundland & Labrador OEL STEL (ppm) 200 ppm Newfoundland & Labrador OEL STEL (ppm) 400 ppm Nova Scotia OEL TWA (ppm) 200 ppm Nova Scotia OEL TWA (ppm) 200 ppm Nunavut OEL STEL (mg/m³) 1228 mg/m³ Nunavut OEL STEL (ppm) 500 ppm Nunavut OEL STEL (ppm) 500 ppm Nunavut OEL TWA (ppm) 983 mg/m³ Nunavut OEL STEL (ppm) 400 ppm Nunavut OEL STEL (mg/m³) 1228 mg/m³ Nunavut OEL TWA (ppm) 400 ppm Nunavut OEL TWA (ppm) 400 ppm Nunavut OEL TWA (ppm) 500 ppm Nunavut OEL TWA (ppm) 400 ppm Northwest Territories OEL STEL (mg/m³) 1228 mg/m³ Northwest Territories OEL STEL (ppm) 500 ppm Northwest Territories OEL STEL (ppm) 500 ppm Northwest Territories OEL STEL (ppm) 500 ppm	Alberta		
British Columbia OEL TWA (ppm) 200 ppm Manitoba OEL STEL (ppm) 400 ppm Manitoba OEL TWA (ppm) 200 ppm New Brunswick OEL STEL (mg/m³) 1230 mg/m³ New Brunswick OEL STEL (ppm) 500 ppm New Brunswick OEL TWA (mg/m³) 983 mg/m³ New Brunswick OEL TWA (ppm) 400 ppm Newfoundland & Labrador OEL STEL (ppm) 400 ppm Newfoundland & Labrador OEL TWA (ppm) 200 ppm Nova Scotia OEL STEL (ppm) 400 ppm Nova Scotia OEL TWA (ppm) 200 ppm Nunavut OEL STEL (mg/m³) 1228 mg/m³ Nunavut OEL STEL (ppm) 500 ppm Nunavut OEL TWA (mg/m³) 983 mg/m³ Nunavut OEL TWA (ppm) 400 ppm Northwest Territories OEL STEL (mg/m³) 1228 mg/m³ Northwest Territories OEL STEL (ppm) 500 ppm Northwest Territories OEL TWA (mg/m³) 983 mg/m³	British Columbia		
ManitobaOEL STEL (ppm)400 ppmManitobaOEL TWA (ppm)200 ppmNew BrunswickOEL STEL (mg/m³)1230 mg/m³New BrunswickOEL STEL (ppm)500 ppmNew BrunswickOEL TWA (mg/m³)983 mg/m³New BrunswickOEL TWA (ppm)400 ppmNewfoundland & LabradorOEL STEL (ppm)400 ppmNewfoundland & LabradorOEL TWA (ppm)200 ppmNova ScotiaOEL STEL (ppm)400 ppmNova ScotiaOEL TWA (ppm)200 ppmNunavutOEL STEL (mg/m³)1228 mg/m³NunavutOEL STEL (ppm)500 ppmNunavutOEL TWA (mg/m³)983 mg/m³NunavutOEL TWA (ppm)400 ppmNorthwest TerritoriesOEL STEL (mg/m³)1228 mg/m³Northwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL STEL (ppm)500 ppm	British Columbia		
ManitobaOEL TWA (ppm)200 ppmNew BrunswickOEL STEL (mg/m³)1230 mg/m³New BrunswickOEL STEL (ppm)500 ppmNew BrunswickOEL TWA (mg/m³)983 mg/m³New BrunswickOEL TWA (ppm)400 ppmNewfoundland & LabradorOEL STEL (ppm)400 ppmNewfoundland & LabradorOEL TWA (ppm)200 ppmNova ScotiaOEL STEL (ppm)400 ppmNova ScotiaOEL TWA (ppm)200 ppmNunavutOEL STEL (mg/m³)1228 mg/m³NunavutOEL STEL (ppm)500 ppmNunavutOEL TWA (mg/m³)983 mg/m³NunavutOEL TWA (ppm)400 ppmNorthwest TerritoriesOEL STEL (mg/m³)1228 mg/m³Northwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL STEL (ppm)500 ppm			• • •
New BrunswickOEL STEL (mg/m³)1230 mg/m³New BrunswickOEL STEL (ppm)500 ppmNew BrunswickOEL TWA (mg/m³)983 mg/m³New BrunswickOEL TWA (ppm)400 ppmNewfoundland & LabradorOEL STEL (ppm)200 ppmNewfoundland & LabradorOEL TWA (ppm)200 ppmNova ScotiaOEL STEL (ppm)400 ppmNova ScotiaOEL TWA (ppm)200 ppmNunavutOEL STEL (mg/m³)1228 mg/m³NunavutOEL STEL (ppm)500 ppmNunavutOEL TWA (mg/m³)983 mg/m³NunavutOEL TWA (ppm)400 ppmNorthwest TerritoriesOEL STEL (mg/m³)1228 mg/m³Northwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL STEL (ppm)500 ppm			
New BrunswickOEL STEL (ppm)500 ppmNew BrunswickOEL TWA (mg/m³)983 mg/m³New BrunswickOEL TWA (ppm)400 ppmNewfoundland & LabradorOEL STEL (ppm)200 ppmNova ScotiaOEL STEL (ppm)400 ppmNova ScotiaOEL TWA (ppm)200 ppmNunavutOEL STEL (mg/m³)1228 mg/m³NunavutOEL STEL (ppm)500 ppmNunavutOEL TWA (mg/m³)983 mg/m³NunavutOEL TWA (ppm)400 ppmNunavutOEL TWA (ppm)400 ppmNorthwest TerritoriesOEL STEL (mg/m³)1228 mg/m³Northwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL STEL (ppm)500 ppm		,	
New BrunswickOEL TWA (mg/m³)983 mg/m³New BrunswickOEL TWA (ppm)400 ppmNewfoundland & LabradorOEL STEL (ppm)400 ppmNewfoundland & LabradorOEL TWA (ppm)200 ppmNova ScotiaOEL STEL (ppm)400 ppmNova ScotiaOEL TWA (ppm)200 ppmNunavutOEL STEL (mg/m³)1228 mg/m³NunavutOEL STEL (ppm)500 ppmNunavutOEL TWA (mg/m³)983 mg/m³NunavutOEL TWA (ppm)400 ppmNorthwest TerritoriesOEL STEL (mg/m³)1228 mg/m³Northwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL STEL (ppm)500 ppm			
New BrunswickOEL TWA (ppm)400 ppmNewfoundland & LabradorOEL STEL (ppm)400 ppmNewfoundland & LabradorOEL TWA (ppm)200 ppmNova ScotiaOEL STEL (ppm)400 ppmNova ScotiaOEL TWA (ppm)200 ppmNunavutOEL STEL (mg/m³)1228 mg/m³NunavutOEL STEL (ppm)500 ppmNunavutOEL TWA (mg/m³)983 mg/m³NunavutOEL TWA (ppm)400 ppmNorthwest TerritoriesOEL STEL (mg/m³)1228 mg/m³Northwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL STEL (ppm)500 ppm			
Newfoundland & LabradorOEL STEL (ppm)400 ppmNewfoundland & LabradorOEL TWA (ppm)200 ppmNova ScotiaOEL STEL (ppm)400 ppmNova ScotiaOEL TWA (ppm)200 ppmNunavutOEL STEL (mg/m³)1228 mg/m³NunavutOEL STEL (ppm)500 ppmNunavutOEL TWA (mg/m³)983 mg/m³NunavutOEL TWA (ppm)400 ppmNorthwest TerritoriesOEL STEL (mg/m³)1228 mg/m³Northwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL STEL (ppm)500 ppm	New Brunswick		
Newfoundland & LabradorOEL TWA (ppm)200 ppmNova ScotiaOEL STEL (ppm)400 ppmNova ScotiaOEL TWA (ppm)200 ppmNunavutOEL STEL (mg/m³)1228 mg/m³NunavutOEL STEL (ppm)500 ppmNunavutOEL TWA (mg/m³)983 mg/m³NunavutOEL TWA (ppm)400 ppmNorthwest TerritoriesOEL STEL (mg/m³)1228 mg/m³Northwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL TWA (mg/m³)983 mg/m³	Newfoundland & Labrador		• •
Nova ScotiaOEL STEL (ppm)400 ppmNova ScotiaOEL TWA (ppm)200 ppmNunavutOEL STEL (mg/m³)1228 mg/m³NunavutOEL STEL (ppm)500 ppmNunavutOEL TWA (mg/m³)983 mg/m³NunavutOEL TWA (ppm)400 ppmNorthwest TerritoriesOEL STEL (mg/m³)1228 mg/m³Northwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL STEL (ppm)983 mg/m³		· · · · ·	
Nova ScotiaOEL TWA (ppm)200 ppmNunavutOEL STEL (mg/m³)1228 mg/m³NunavutOEL STEL (ppm)500 ppmNunavutOEL TWA (mg/m³)983 mg/m³NunavutOEL TWA (ppm)400 ppmNorthwest TerritoriesOEL STEL (mg/m³)1228 mg/m³Northwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL STEL (ppm)983 mg/m³			
Nunavut OEL STEL (mg/m³) 1228 mg/m³ Nunavut OEL STEL (ppm) 500 ppm Nunavut OEL TWA (mg/m³) 983 mg/m³ Nunavut OEL TWA (ppm) 400 ppm Northwest Territories OEL STEL (mg/m³) 1228 mg/m³ Northwest Territories OEL STEL (ppm) 500 ppm Northwest Territories OEL TWA (mg/m³) 983 mg/m³		\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	
NunavutOEL STEL (ppm)500 ppmNunavutOEL TWA (mg/m³)983 mg/m³NunavutOEL TWA (ppm)400 ppmNorthwest TerritoriesOEL STEL (mg/m³)1228 mg/m³Northwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL TWA (mg/m³)983 mg/m³		*** *	
NunavutOEL TWA (mg/m³)983 mg/m³NunavutOEL TWA (ppm)400 ppmNorthwest TerritoriesOEL STEL (mg/m³)1228 mg/m³Northwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL TWA (mg/m³)983 mg/m³		, ,	<u> </u>
NunavutOEL TWA (ppm)400 ppmNorthwest TerritoriesOEL STEL (mg/m³)1228 mg/m³Northwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL TWA (mg/m³)983 mg/m³		,	
Northwest TerritoriesOEL STEL (mg/m³)1228 mg/m³Northwest TerritoriesOEL STEL (ppm)500 ppmNorthwest TerritoriesOEL TWA (mg/m³)983 mg/m³			
Northwest Territories OEL STEL (ppm) 500 ppm Northwest Territories OEL TWA (mg/m³) 983 mg/m³			
		, ,	
	Northwest Territories	OEL TWA (mg/m³)	983 mg/m³
MIL 7	Northwest Territories	OEL TWA (ppm)	400 ppm
Ontario OEL STEL (ppm) 400 ppm	Ontario	OEL STEL (ppm)	400 ppm

12/30/2013 EN (English US) 5/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ontario	OEL TWA (ppm)	200 ppm	
Prince Edward Island	OEL STEL (ppm)	400 ppm	
Prince Edward Island	OEL TWA (ppm)	200 ppm	
Québec	VECD (mg/m³)	1230 mg/m³	
Québec	VECD (ppm)	500 ppm	
Québec	VEMP (mg/m³)	985 mg/m³	
Québec	VEMP (ppm)	400 ppm	
Saskatchewan	OEL STEL (ppm)	400 ppm	
Saskatchewan	OEL TWA (ppm)	200 ppm	
Yukon	OEL STEL (mg/m³)	1225 mg/m³	
Yukon	OEL STEL (ppm)	500 ppm	
Yukon	OEL TWA (mg/m³)	980 mg/m³	
Yukon	OEL TWA (ppm)	400 ppm	

Exposure Controls

Appropriate Engineering Controls: Ensure all national/local regulations are observed. Use explosion-proof equipment. Take precautionary measures against static discharges. Gas detectors should be used when flammable gases/vapours may be released. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal Protective Equipment: Protective clothing. Safety glasses. Face shield. Gloves. Insufficient ventilation: wear respiratory protection.



pН









13.5

Materials for Protective Clothing: Wear fire/flame resistant/retardant clothing.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or face shield.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed

established Occupational Exposure Limits.

Relative Vapor Density at 20 °C

Relative Density

Consumer Exposure Controls: Do not eat, drink or smoke during use

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical PropertiesPhysical State:LiquidAppearance:ColorlessOdor:CharacteristicOdor Threshold:Not available

Relative Evaporation Rate (butylacetate=1) Not available **Melting Point** Not available **Freezing Point** Not available **Boiling Point** Not available Flash Point 69 °C (156.2 °F) **Auto-ignition Temperature** Not available **Decomposition Temperature** Not available Flammability (solid, gas) Not available **Lower Flammable Limit** Not available **Upper Flammable Limit** Not available **Vapor Pressure** Not available

12/30/2013 EN (English US) 6/14

Not available

1.08 (water = 1)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific Gravity : 1.08

Solubility:Not availableLog Pow:Not availableLog Kow:Not availableViscosity, Kinematic:Not availableViscosity, Dynamic:Not availableExplosion Data – Sensitivity to Mechanical Impact:Not availableExplosion Data – Sensitivity to Static Discharge:Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Corrosive to metals. Reacts with (strong) oxidizers: (increased) risk of fire. Adding water to solution may generate large

amounts of heat.

Chemical Stability: Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Open flame. Heat. Sparks.

Incompatible Materials: Strong acids. Strong oxidizers.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Potassium oxides. Sodium oxides. Phosphorus oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Harmful if swallowed.

LD50 and LC50 Data

BBQ Cleaner	
ATE (oral)	500.000 mg/kg body weight

Skin Corrosion/Irritation: Causes severe skin burns and eye damage. (pH: 13.5)

Serious Eye Damage/Irritation: Causes serious eye damage. (pH: 13.5)

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available **Carcinogenicity:** Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May be harmful if inhaled. Symptoms/Injuries After Skin Contact: Corrosive. Causes burns. Symptoms/Injuries After Eye Contact: Causes serious eye damage.

Symptoms/Injuries After Ingestion: Harmful if swallowed. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data

Potassium hydroxide (1310-58-3)	
LD50 Oral Rat	214 mg/kg
ATE (oral)	214.000 mg/kg body weight
2-Butoxyethanol (111-76-2)	
LD50 Oral Rat	470 mg/kg
LD50 Dermal Rabbit	220 mg/kg
LC50 Inhalation Rat (ppm)	450 ppm/4h
ATE (oral)	470.000 mg/kg body weight
ATE (dermal)	220.000 mg/kg body weight
ATE (gases)	450.000 ppmV/4h
ATE (vapors)	11.000 mg/l/4h

12/30/2013 EN (English US) 7/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Isopropyl alcohol (67-63-0)		
LD50 Oral Rat	4396 mg/kg	
LD50 Dermal Rabbit	12800 mg/kg	
LC50 Inhalation Rat (ppm)	16000 ppm (Exposure time: 8 h)	
ATE (oral)	4396.000 mg/kg body weight	
ATE (dermal)	12800.000 mg/kg body weight	
Tetrasodium EDTA (64-02-8)		
LD50 Oral Rat	1780 mg/kg	
ATE (oral)	1780.000 mg/kg body weight	
2-Butoxyethanol (111-76-2)		
IARC Group	3	
National Toxicity Program (NTP) Status	Evidence of Carcinogenicity.	
Isopropyl alcohol (67-63-0)		
IARC Group	3	
SECTION 12: ECOLOGICAL INFORMATION		

Toxicity

Ecology - General: Harmful to aquatic life.

1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
34-5)
> 100 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
> 100 mg/l (Exposure time: 48 h - Species: water flea)
9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
1000 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)
11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
1000 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)
41 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
1.01 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)
59.8 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

Persistence and Degradability

BBQ Cleaner			
Persistence and Degradability	Not established.		
Bioaccumulative Potential			
BBQ Cleaner			
Bioaccumulative Potential Not established.			
Potassium hydroxide (1310-58-3)			
Log Pow	0.65		
2-Butoxyethanol (111-76-2)			
Log Pow 0.81 (at 25 °C)			
Isopropyl alcohol (67-63-0)			
Log Pow	0.05 (at 25 °C)		

Mobility in Soil Not available

12/30/2013 EN (English US) 8/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable.

Ecology - Waste Materials: Hazardous waste due to toxicity.

SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG

UN Number UN-No.: 1814

DOT NA no.: UN1814

UN Proper Shipping Name

DOT Proper Shipping Name : Potassium hydroxide, solution

Hazard Classes : 8 - Class 8 - Corrosive material 49 CFR 173.136

Hazard Labels : 8 - Corrosive substances



Packing Group : II - Medium Danger

DOT Special Provisions (49 CFR 172.102) : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 95 / (1 + a (tr - tf)) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: a = (d15 - d50) / 35d50 Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154 DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 242

Additional Information

Emergency Response Guide (ERG) Number : 154

Other Information : This product meets the limited quantities exception as follows: DOT: Not

regulated as dangerous goods except when shipped in bulk (LQ of up to

1L). Otherwise, the above descriptions apply.

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 52 - Stow "separated from" acids

MFAG-No (IMDG) : 154

12/30/2013 EN (English US) 9/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Packaging Instructions (IMDG): P001IBC Instructions (IMDG): IBC02Limited Quantities (IMDG): 1 LExcepted Quantities (IMDG): E2Marine Pollutant (IMDG): No

Air transport

DOT Quantity Limitations Passenger Aircraft/Rail (49 CFR 173.27) : 1 L

DOT Quantity Limitations Cargo Aircraft Only (49 CFR 175.75) : 30 L

Special Provisions (IATA) : A3

Packaging Instruction (IATA) : 851, Y840

Max Net Quantity Per Package (IATA) : 1 L, 0.5 L

Excepted Quantity (IATA) : E2

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

BBQ Cleaner	
SARA Section 311/312 Hazard Classes	Fire hazard
	Immediate (acute) health hazard
	Reactive hazard

Potassium hydroxide (1310-58-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

2-Butoxyethanol (111-76-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Tetrapotassium pyrophosphate (7320-34-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Isopropyl alcohol (67-63-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on SARA Section 313 (Specific toxic chemical listings)

EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSC		
SARA Section 313 - Emission Reporting	1.0 % (only if manufactured by the strong acid process, no supplier notification)		

Tetrasodium EDTA (64-02-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

D-Glucopyranose, oligomeric, decyl octyl glycosides (68515-73-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

US State Regulations

Potassium hydroxide (1310-58-3)

- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)
- U.S. Delaware Pollutant Discharge Requirements Reportable Quantities
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Louisiana Reportable Quantity List for Pollutants
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 2
- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 2
- U.S. Massachusetts Right To Know List
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. Michigan Occupational Exposure Limits Ceilings
- U.S. Michigan Polluting Materials List

12/30/2013 EN (English US) 10/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits Ceilings
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances
- U.S. North Dakota Air Pollutants Guideline Concentrations 1-Hour
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Tennessee Occupational Exposure Limits Ceilings
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Vermont Permissible Exposure Limits Ceilings
- U.S. Washington Permissible Exposure Limits Ceilings
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 25 Feet to Less Than 40 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 40 Feet to Less Than 75 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 75 Feet or Greater
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights Less Than 25 Feet

2-Butoxyethanol (111-76-2)

- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Acute
- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. Colorado Groundwater Quality Standards
- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Idaho Occupational Exposure Limits TWAs
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 2
- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 2
- U.S. Massachusetts Right To Know List
- U.S. Michigan Occupational Exposure Limits Skin Designations
- U.S. Michigan Occupational Exposure Limits TWAs
- U.S. Minnesota Chemicals of High Concern
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits Skin Designations
- U.S. Minnesota Permissible Exposure Limits TWAs
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Occupational Exposure Limits Skin Designations
- U.S. New York Occupational Exposure Limits TWAs
- U.S. North Dakota Air Pollutants Guideline Concentrations 8-Hour
- U.S. Oregon Permissible Exposure Limits Skin Designations
- U.S. Oregon Permissible Exposure Limits TWAs
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Rhode Island Air Toxics Acceptable Ambient Levels 1-Hour

12/30/2013 EN (English US) 11/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- U.S. Rhode Island Air Toxics Acceptable Ambient Levels Annual
- U.S. Tennessee Occupational Exposure Limits Skin Designations
- U.S. Tennessee Occupational Exposure Limits TWAs
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Vermont Permissible Exposure Limits Skin Designations
- U.S. Vermont Permissible Exposure Limits TWAs
- U.S. Washington Permissible Exposure Limits Skin Designations
- U.S. Washington Permissible Exposure Limits STELs
- U.S. Washington Permissible Exposure Limits TWAs
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 25 Feet to Less Than 40 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 40 Feet to Less Than 75 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 75 Feet or Greater
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights Less Than 25 Feet

Tetrapotassium pyrophosphate (7320-34-5)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Isopropyl alcohol (67-63-0)

- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Acute
- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Chronic
- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)
- U.S. Connecticut Volatile Substances
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Idaho Occupational Exposure Limits TWAs
- U.S. Massachusetts Right To Know List
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. Michigan Occupational Exposure Limits STELs
- U.S. Michigan Occupational Exposure Limits TWAs
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits STELs
- U.S. Minnesota Permissible Exposure Limits TWAs
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Environmental Hazardous Substances List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Occupational Exposure Limits TWAs
- U.S. North Dakota Air Pollutants Guideline Concentrations 1-Hour
- U.S. North Dakota Air Pollutants Guideline Concentrations 8-Hour
- U.S. Oregon Permissible Exposure Limits TWAs
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Rhode Island Air Toxics Acceptable Ambient Levels 1-Hour
- U.S. Tennessee Occupational Exposure Limits STELs
- U.S. Tennessee Occupational Exposure Limits TWAs
- U.S. Texas City of Austin Aerosol Paint and Glue Restrictions
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

12/30/2013 EN (English US) 12/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- U.S. Vermont Permissible Exposure Limits STELs
- U.S. Vermont Permissible Exposure Limits TWAs
- U.S. Washington Permissible Exposure Limits STELs
- U.S. Washington Permissible Exposure Limits TWAs

Tetrasodium EDTA (64-02-8)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

D-Glucopyranose, oligomeric, decyl octyl glycosides (68515-73-1)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Canadian Regulations

BO		

WHMIS Classification

Class B Division 3 - Combustible Liquid

Class E - Corrosive Material

Class D Division 2 Subdivision A - Very toxic material causing other toxic effects







Potassium hydroxide (1310-58-3)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Listed on the Canadian Ingredient Disclosure List

WHMIS Classification Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects

Class E - Corrosive Material

2-Butoxyethanol (111-76-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Listed on the Canadian Ingredient Disclosure List

WHMIS Classification Class B Division 3 - Combustible Liquid

Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects

Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Tetrapotassium pyrophosphate (7320-34-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Isopropyl alcohol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Listed on the Canadian Ingredient Disclosure List

WHMIS Classification Class B Division 2 - Flammable Liquid

Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Tetrasodium EDTA (64-02-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification Class D Division 2 Subdivision B - Toxic material causing other toxic effects

D-Glucopyranose, oligomeric, decyl octyl glycosides (68515-73-1)

Listed on the Canadian DSL (Domestic Substances List) inventory.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION

Revision date : 12/30/2013

12/30/2013 EN (English US) 13/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other Information

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acuto Toy 2 (Oral)	Aguta tayisity (aval) Catagory 2
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 4	Flammable liquids Category 4
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H227	Combustible liquid
H290	May be corrosive to metals
H301	Toxic if swallowed
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H401	Toxic to aquatic life
H402	Harmful to aquatic life

NFPA Health Hazard : 2 - Intense or continued exposure could cause temporary incapacitation or


possible residual injury unless prompt medical attention is given.

NFPA Fire Hazard : 2 - Must be moderately heated or exposed to relatively high temperature before

ignition can occur.

NFPA Reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive

with water.



Party Responsible for the Preparation of This Document

Starbrite®

Phone Number: (954)587-6280

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS

12/30/2013 EN (English US) 14/14