

394 GENERAL PURPOSE

DUCT TAPE



Backing:	Polyethylene Coated Cloth
Adhesive:	Natural Rubber
Liner:	N/A
Specifications:	N/A
Colors:	Silver
Available Size:	1.89 in x 54.7 yd x 9 mil (48 mm x 50 m x 228 μm)

Applications

- Bundling, patching, and bonding
- Household patch and repair
- Seaming tarp and sheeting materials
- General purpose abatement and contractor uses

Features

Benefits

Natural Rubber Adhesive	<ul style="list-style-type: none"> • Good all-climate performance up to 200 °F • Bonds well to a variety of surfaces
Polyethylene Coated Cloth Backing	<ul style="list-style-type: none"> • High thread count for easy tearing • Conformable • Resists twisting and curling
Low VOC Content	<ul style="list-style-type: none"> • Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	9.0 mils	228 μm	ASTM D-1000
Adhesion to Steel	40 oz/in	4.38 N/cm	PSTC-101
Tensile Strength	19 lb/in	33.27 N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
VOC Content	< 1 g/L		
Recommended Storage Conditions: 32 - 90 °F at 50% RH ± 2%			
Standard Shelf Life (at 25 °C): 36 months from date of manufacture			

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.