



Brita® Whole House Drop-in Filtration System WHS-101

Usage and quality of water in your incoming water line affect the life of filter cartridges. Cartridges should be replaced sooner if water pressure at the faucet begins to drop noticeably or if the filter fails to perform satisfactorily.

After prolonged periods of non-use, it is recommended that the filter system be flushed thoroughly. Let water run for 10 minutes before using.

The filter used with this filter system has a limited service life. Changes in taste, odor, and/or flow of the water being filtered indicate that the filter should be replaced.

Please see the Performance Data Sheet for the certified performance of specific systems with stated cartridges.

System	Filter Model Numbers
WHS-101 Heavy Duty Drop-in Filtration System	WHF-204 -Sediment Carbon Wrap Flow Rate: 5 gpm (18.9 lpm) Operating Pressure 30-100 psi (207-690 kPa)
Replace filters every six months or when flow rate decreases significantly.	WHF-205 -GAC Heavy Duty Drop-In Filter Flow Rate: 10 gpm (37.85 lpm) Operating pressure 30-100 psi (207-690kPa)
	WHF-201 - Poly Pleat Flow Rate: 10 gpm (37.85 lpm) Operating Pressure 30-100 psi (207-690 kPa)

Replacement Parts Part Number	Description
WFBAB-100	Mounting Bracket
WFB AO-100	System O-Ring
WFB AW-100	System Housing Wrench

