

## GLIDDEN COLOR SAMPLE

### AT GLIDDEN®, WE WANT YOU TO LOVE YOUR COLOR AND RESULTS.

That's why we encourage you to try a couple options and find that perfect choice for your project. With the *Glidden* Universal Color Sample, you can test any color and be sure it's the right one. Once you are happy with your selection, simply choose any tintable product from the *Glidden* line and we'll be happy to mix it up for you.

**DIRECTIONS:** 1. Stir sample completely to ensure a uniform color. 2. With a small brush or roller, apply your *Glidden* Universal Color Sample to the surface of your project.

Tip: This sample will cover approximately 4x4 ft. so don't be shy with your test spot. You want to make sure you get a good feel for how it will look. 3. Wait 60 minutes for your sample to dry. 4. If you are sampling a darker color or making a dramatic shift in color, you may need a second coat to ensure the best representation of the new color. 5. Do you love it? Go get it! Tip: Take this *Glidden* Universal Color Sample back to the store with you to be sure you get the same color and sheen you tested and loved. **Cleanup:** Clean hands and tools with warm, soapy water. Clean spills right away with a damp cloth.

**Note:** Color may vary slightly between sheens. *Glidden* Universal Color Samples are intended for testing color, they are not recommended for touch-up or painting small projects.

Calc. VOC < 50 g/L (0.4 lbs/gal)

Sanding /grinding dusts may be harmful if inhaled. Provide fresh air ventilation during and after use. Avoid the inhalation of dust, particulates, spray or mist arising from product application. Use personal protective equipment. FIRST AID: If swallowed, do not induce vomiting. Call physician immediately. If in eyes/on skin, rinse with water for 15 minutes. Get medical attention immediately. If inhaled, move to fresh air. Call a physician if respiratory symptoms occur. Contains: water; titanium dioxide; proprietary vinyl acetate acrylic copolymer; nepheline syenite; acrylic resin. Keep out of the reach of children. For workplace use, an SDS is available from your retailer or by calling : (412) 492-5555.

EMERGENCY SPILL INFORMATION: (412) 434-4515.