



TECHNICAL DATA SHEET

11/2/2017

Platinum Patch™

Advanced Exterior Filler



Product Description: DAP® PLATINUM PATCH™ Advanced Exterior Filler is formulated for the most demanding exterior home repairs with superior multi-material adhesion to the most common building materials including fiber cement & vinyl siding, PVC trim, composite decking, metal, mortar, wood, brick and more. It's formulated with advanced Weathermax Technology, providing exceptional weatherproof capabilities and UV protection to prevent color fading, discoloration, cracking, crumbling or other damage that could be caused from harsh weather. It's easy to apply, sandable and paintable and low in odor.

MADE FOR THE ELEMENTS



Multi-Material Adhesion



Sandable & Paintable



24 Hour Rain Ready

Featured & Benefits:

- WeatherMAX Technology
 - Weatherproof, Waterproof, Mold & Mildew Resistant
- For the most demanding repairs
- Ideal for exterior applications
- Multi-Material Adhesion
 - Metal, Composite, PVC, Wood Vinyl & More
- Sandable & Paintable

Suggested Uses:

Ideal for filling holes, cracks, crevices, dents or defects on:

- Aluminum/Steel
- Composite
- PVC
- Fiber Cement
- Wood
- Mortar
- Concrete
- Vinyl
- Brick
- Stucco
- Plaster
- Drywall

Available In:

| SKU # | Description | Size | Package Type | Case Pack | Color |
|------------|---|---------------------|--------------|-----------|-------|
| 7079818786 | Platinum Patch Advanced Exterior Filler | 7 Fl. Oz. (236 mL) | Tube | 6 PK | White |
| 7079818740 | Platinum Patch Advanced Exterior Filler | 16 Fl. Oz (473 mL) | Tub | 4 PK | White |
| 7079818740 | Platinum Patch Advanced Exterior Filler | 16 Fl. Oz (473 mL) | Tub | 12 PK | White |
| 7079818787 | Platinum Patch Advanced Exterior Filler | 32 Fl. Oz. (946 mL) | Tub | 8 PK | White |



TECHNICAL DATA SHEET

Surface Preparation & Application Instructions:

- Surface must be clean, dry and free of foreign material.
- If using squeeze tube, knead tube before use and cut nozzle to desired opening size.
- Apply with a clean putty knife.
- For a smoother finish, dip putty knife in water and lightly smooth.
- One application is usually sufficient for small repairs. For repairs deeper than 1/8", apply two or more layers allowing to dry between applications.
- May be sanded and/or painted in 2 to 4 hours depending on temperature, humidity and depth of fill. Wet sanding is recommended to avoid generation of dust.
- Clean tools immediately with water.

For Best Results:

- Do not apply when temperatures are below 40°F.
- Allow product to fully cure before exposing to water, approximately 24 hours.
- Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- **DO NOT USE AS A SKIM COAT.**
- A topcoat is not required, however, if desired, product can be painted with a high-quality latex-based paint.
- Staining is not recommended.
- Not for continuous underwater use.

Typical Physical & Chemical Characteristics:

| | |
|-------------------------|---|
| Consistency | Paste |
| Vehicle | Acrylic Latex |
| Volatile | Water |
| Odor | Slight |
| Weight/Gallon | 13 lbs./gallon |
| Solids | 79% |
| Application Temperature | 40°F - 150°F |
| Service Temperature | 0°F to 120°F |
| Shelf Life | 12 months |
| Freezing | Passes 5 cycles of 16 hours at 0°F / 8 hours at 73°F |
| Dry Time | 2 to 4 hours depending on temperature, humidity and depth of fill |
| SDS Number | 00010501001 |



TECHNICAL DATA SHEET

Cleanup & Storage Recommendations:

- Wash tools immediately after use with water.
- Dried material must be removed by scraping or sanding.
- Be sure container lid/cap is closed and tightly sealed.
- Store in a cool, dry place.

Safety Information:

Contains: Crystalline silica. Sanding of this product may generate dust. Inhalation of dust may cause adverse respiratory effects. May cause eye and skin irritation. Do not breathe dust. Use only with adequate ventilation. Ensure fresh air entry. When sanding, wear a NIOSH-approved dust mask. Harmful if swallowed. Do not ingest. Avoid contact with eyes, skin and clothing. Wear gloves and safety glasses. Close container after use. Wash thoroughly after handling.

FIRST AID: SKIN: Wash thoroughly. EYE: immediately flood with large quantities of water. INHALATION: Remove to fresh air. INGESTION: DO NOT INDUCE VOMITING. Get medical attention if complications arise from any exposure. **For emergencies,** call your poison control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your **supplier or visit dap.com.**

KEEP OUT OF REACH OF CHILDREN.

Warranty Information:

- If product fails to perform as directed, within one year from the date of purchase, call 1-888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund.
- DAP will not be responsible for incidental or consequential damages.

Disclaimer:

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use.

Company Information:

Manufacturer: DAP Products Inc., Baltimore, MD 21224.

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339

Fax Number: 410-558-1068

Also visit the DAP website at dap.com.