# SAFETY DATA SHEET

Issuing Date 29-Nov-2018 Revision Date 28-Nov-2018 Revision Number 4



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Product identifier** 

Product Name Li-Mn Button Cell CR1220

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Lithium Primary/Metal Batteries

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name GUANGZHOU TIANQIU ENTERPRISE CO., LTD.

**Supplier Address** 9/F TianQiu Building No.16-30, He Yi Rd., San Yuan Li Ave., GuangZhou China

GUANGZHOU GUANDONG 510410 CN

Supplier Phone Number Phone:8620-36322277

Fax:8620-36322277

**Supplier Email** idsale6@gztianqiu.com

Emergency telephone number

**Company Emergency Phone** 

Number

8620-13825131170

# 2. HAZARDS IDENTIFICATION

#### Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Gases)	Category 4



Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Reproductive Toxicity	Category 1B

#### GHS Label elements, including precautionary statements

#### **Emergency Overview**

#### Signal word **Danger**

#### **Hazard Statements**

Harmful if swallowed Harmful if inhaled Causes skin irritation Causes serious eve irritation May damage fertility or the unborn child





This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance. This is a battery. In case of rupture: the above hazards exist. .

Appearance Silver Physical state Solid **Odor** Odorless

# **Precautionary Statements - Prevention**

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Wear eye/face protection

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

#### Ingestion



IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

## **Precautionary Statements - Storage**

Store locked up

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

#### **Unknown Toxicity**

3.92 % of the mixture consists of ingredient(s) of unknown toxicity

#### Other information

Harmful to aquatic life with long lasting effects

#### **Interactions with Other Chemicals**

Use of alcoholic beverages may enhance toxic effects.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

.

Chemical name	CAS No.	Weight-%	Trade Secret
Iron	7439-89-6	30 - 60	*
Manganese dioxide	1313-13-9	10 - 30	*
Perchloric acid, lithium salt	7791-03-9	1 - 5	*
Propylene carbonate	108-32-7	1 - 5	*
Lithium	7439-93-2	1 - 5	*
Ethylene glycol dimethyl ether	110-71-4	1 - 5	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret

# 4. FIRST AID MEASURES

#### First aid measures

<u>General Advice</u> First aid is upon rupture of sealed battery. Show this safety data sheet to the doctor in

attendance.

**Eye contact**Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Do not rub affected area.

**Skin contact** Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical

attention if irritation develops and persists.

**Inhalation** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult,

(trained personnel should) give oxygen.

**Ingestion** Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an

unconscious person. Do NOT induce vomiting. Call a physician.

**(III)** 

Page 3/12

Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

**Most Important Symptoms and** 

Burning sensation. Coughing and/ or wheezing. Difficulty in breathing.

**Effects** 

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

# Suitable Extinguishing Media

Dry chemical, soda ash, lime or sand. DRY sand, dry chemical, soda ash or lime or withdraw from area and let fire burn. Move containers from fire area if you can do it without risk.

#### Unsuitable extinguishing media

DO NOT USE WATER OR FOAM.

#### Specific hazards arising from the chemical

Produce flammable gases on contact with water. May ignite on contact with water or moist air. Some react vigorously or explosively on contact with water. May be ignited by heat, sparks or flames. Some are transported in highly flammable liquid. Runoff may create fire or explosion hazard.

#### **Hazardous Combustion Products**

Carbon oxides.

**Physical/Chemical Reaction** 

No data available.

Properties

Explosion Data
Sensitivity to Mechanical Impact

No.

Sensitivity to Static Discharge

No.

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

(UL)

Page 4/12

1288509 - Li-Mn Button Cell CR1220 Revision Date 28-Nov-2018

# 6. ACCIDENTAL RELEASE MEASURES

# Personal precautions, protective equipment and emergency procedures

Personal precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Do not touch or walk through spilled material. Stop leak if you can do it without risk. DO NOT CLEAN-UP OR DISPOSE OF, EXCEPT UNDER SUPERVISION OF A SPECIALIST.

Other Information DO NOT GET WATER on spilled substance or inside containers.

**Environmental precautions** 

**Environmental precautions**Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to

contact spilled material.

Methods and material for containment and cleaning up

Methods for containment Cover with DRY earth, DRY sand or other non-combustible material followed with plastic

sheet to minimize spreading or contact with rain. Dike for later disposal; do not apply water unless directed to do so. Cover powder spill with plastic sheet or tarp to minimize spreading

and keep powder dry.

**Methods for cleaning up** Pick up and transfer to properly labeled containers.

# 7. HANDLING AND STORAGE

# Precautions for safe handling

**Handling** In case of rupture: Handle in accordance with good industrial hygiene and safety practice.

Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Do not breathe dust. Avoid generation of dust. Ensure adequate ventilation. In case of insufficient ventilation, wear

suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities

**Storage** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach

of children. Store locked up.

**Incompatible Products** Strong acids. Strong oxidizing agents. Strong bases.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### **Control parameters**

**Exposure Guidelines** The following ingredients are the only ingredients of the product above the cut-off level (or

level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure

limits from the sources listed here

Chemical name ACGIH TLV OSHA PEL NIOSH IDLH



Manganese dioxide 1313-13-9 TWA: 0.02 mg/m³ particulate TWA: 0.1 mg/m³ particulate	matter Ceiling: 5 mg/m³ Mn Mn inhalable	IDLH: 500 mg/m³ Mn TWA: 1 mg/m³ Mn STEL: 3 mg/m³ Mn
--	--	---

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992) See section 15 for national exposure control parameters

**Appropriate engineering controls** 

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

**Eye/face protection** If splashes are likely to occur:. Wear safety glasses with side shields (or goggles). None

required for consumer use.

**Skin and body protection** Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves.

exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Do not breathe dust. Wash hands before breaks and

immediately after handling the product.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

# **Physical and Chemical Properties**

Physical state

AppearanceSilverOdorOdorlessColorNo information availableOdor ThresholdNo information available

Remarks Method **Property** Values No data available None known pН Melting / freezing point No data available None known Boiling point / boiling range No data available None known **Flash Point** No data available None known No data available None known **Evaporation Rate** No data available Flammability (solid, gas) None known

Solid

Flammability Limit in Air
Upper flammability limit
Lower flammability limit
No data available
No data available

Vapor pressureNo data availableNone knownVapor densityNo data availableNone knownSpecific GravityNo data availableNone known

Water Solubility Negligible

Solubility in other solvents

No data available

Partition coefficient: n-octanol/waterNo data available

Autoignition temperature

No data available

None known

No data available

None known

No data available

None known



Kinematic viscosityNo data availableNone knownDynamic viscosityNo data availableNone knownExplosive propertiesNo data availableOxidizing propertiesNo data available

**Other Information** 

Softening Point
VOC Content (%)
Particle Size
No data available
No data available
No data available

**Particle Size Distribution** 

# 10. STABILITY AND REACTIVITY

#### Reactivity

No data available.

#### **Chemical stability**

Stable under recommended storage conditions.

#### **Possibility of Hazardous Reactions**

None under normal processing.

#### **Hazardous Polymerization**

Hazardous polymerization does not occur.

#### Conditions to avoid

Excessive heat.

#### **Incompatible materials**

Strong acids. Strong oxidizing agents. Strong bases.

#### **Hazardous Decomposition Products**

Carbon oxides.

# 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

**Product Information** Product does not present an acute toxicity hazard based on known or supplied information.

In case of rupture:.

**Inhalation** Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract. Harmful by inhalation. (based on components).

**Eye contact** Specific test data for the substance or mixture is not available. Causes serious eye irritation.

(based on components). May cause redness, itching, and pain.

**Skin contact** Specific test data for the substance or mixture is not available. Causes skin irritation. (based

on components). Prolonged contact may cause redness and irritation.

**Ingestion** Specific test data for the substance or mixture is not available. Ingestion may cause

irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea,

(U)

**1288509 - Li-Mn Button Cell CR1220** Revision Date 28-Nov-2018

vomiting and diarrhea. Harmful if swallowed. (based on components).

#### **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Iron 7439-89-6	= 30 g/kg (Rat)	-	-
Manganese dioxide 1313-13-9	= 9000 mg/kg (Rat)	-	-
Propylene carbonate 108-32-7	= 29000 mg/kg (Rat)	> 3000 mg/kg (Rabbit)	-
Ethylene glycol dimethyl ether 110-71-4	> 4000 mg/kg (Rat) = 775 mg/kg ( Rat)	1000 - 2000 mg/kg (Rabbit)	20 - 63 mg/L (Rat) 6 h

#### Information on toxicological effects

Symptoms Erythema (skin redness). May cause redness and tearing of the eyes. Coughing and/ or

wheezing.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

**Carcinogenicity** Contains no ingredient listed as a carcinogen.

**Reproductive toxicity**Contains a known or suspected reproductive toxin.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Chronic Toxicity**Contains a known or suspected reproductive toxin. Possible risk of irreversible effects. May

cause adverse effects on the bone marrow and blood-forming system.

Target Organ Effects Respiratory system. Eyes. Skin. Reproductive System. Blood. Central Nervous System

(CNS). Kidney. Cardiovascular system.

**Aspiration Hazard** No information available.

#### Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)
567.00 mg/kg
ATEmix (dermal)
68,493.20 mg/kg (ATE)
ATEmix (inhalation-gas)
14,400.00 ppm (4 hr)
ATEmix (inhalation-dust/mist)
4.80 mg/l
ATEmix (inhalation-vapor)
35.20 ATEmix



\_\_\_\_\_

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

Harmful to aquatic life with long lasting effects.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Iron		96h LC50: = 13.6 mg/L		
7439-89-6		(Morone saxatilis)		
Propylene carbonate	72h EC50: > 500 mg/L	96h LC50: = 5300 mg/L	EC50 > 10000 mg/L 17 h	48h EC50: > 500 mg/L
108-32-7	(Desmodesmus	(Leuciscus idus) 96h LC50:		
	subspicatus)	> 1000 mg/L (Cyprinus		
		carpio)		

#### Persistence and Degradability

No information available.

#### **Bioaccumulation**

Chemical name	Log Pow
Manganese dioxide 1313-13-9	<0
Propylene carbonate 108-32-7	0.48

#### Other adverse effects

No information available.

# 13. DISPOSAL CONSIDERATIONS

# Waste treatment methods

Disposal methods This material, as supplied, is not a hazardous waste according to Federal regulations (40

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

regulations for additional requirements.

**Contaminated Packaging** Dispose of contents/containers in accordance with local regulations.

California Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Lithium	Corrosive
7439-93-2	Ignitable
	Reactive

# **14. TRANSPORT INFORMATION**

**Note:**The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime

Dangerous Goods Code and the US Department of Transportation. The batteries must



meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule)

Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

188 OF IMO-IMDG Cod

DOTNOT REGULATEDProper Shipping NameNON-REGULATED

Emergency Response Guide 138

Number

TDG Not regulated

MEX Not regulated

ICAO Not regulated

<u>IATA</u> Not regulated

Proper Shipping Name NON REGULATED

Hazard Class N/A

IMDG/IMO Not regulated

Proper Shipping Name NON-REGULATED PER SP 188

Hazard Class N/A EmS-No. F-A, S-I

Marine Pollutant Product is a marine pollutant according to the criteria set by IMDG/IMO

RID Not regulated

ADR Not regulated

Tunnel restriction code (E)

ADN Not regulated

# 15. REGULATORY INFORMATION

#### **International Inventories**

TSCA Not determined DSL Not determined

IECSC -

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory **DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

#### **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Manganese dioxide - 1313-13-9	1313-13-9	10 - 30	1.0



Ethylene glycol dimethyl ether - 110-71-4	110-71-4	1 - 5	1.0

# SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

#### **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

#### **US State Regulations**

#### **California Proposition 65**

This product does not contain any Proposition 65 chemicals.

#### **U.S. State Right-to-Know Regulations**

.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Manganese dioxide	X		X	Х	X
1313-13-9					
Lithium	Χ	X	X		
7439-93-2					
Ethylene glycol dimethyl ether	Х	X	X	Х	X
110-71-4					

### International Regulations

#### Mexico

National occupational exposure limits

Chemical name	Carcinogen Status	Exposure Limits
Manganese dioxide		Mexico: TWA= 0.2 mg/m <sup>3</sup>

Mexico - Occupational Exposure Limits - Carcinogens

#### Canada

#### **WHMIS Hazard Class**

Non-controlled

16. OTHER INFORMATION

NFPA Health Hazards 1 Flammability 0 Instability 0 Physical and Chemical Hazards W
HMIS Health Hazards 0 Flammability 0 Physical Hazard 0 Personal Protection

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Issuing Date29-Nov-2018Revision Date28-Nov-2018



**1288509 - Li-Mn Button Cell CR1220** Revision Date 28-Nov-2018

\_\_\_\_\_

#### **Revision Note**

No information available

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet** 





Page 12/12