



Technical Bulletin

PHENOMENAL BRANDS, Phenopatch Products
a division of DAP Products Inc.
2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100

Revised: 10/20/13

DAP[®] PHENOPATCH[®] All-Purpose Spackling Paste

- Repairs cracks and holes in walls and ceilings
- Resists cracking
- Easy to sand
- Ready-to-use
- Interior/exterior use

Packaging: 8 fl. oz., 32 fl. oz., 1 Gallon
Color: White
UPC Numbers: 70798 76858, 76857, 76859

Company Identification:

Manufacturer: PHENOMENAL BRANDS, Phenopatch Products, a division of DAP Products Inc., 2400 Boston St., Baltimore, Maryland 21224

Usage Information: 1-888-327-8477 or visit dap.com and click on "Ask the Expert"

Order Information: 1-800-327-3339

Fax Number: 410-558-1068

Also, visit the Phenopatch website at www.phenopatch.com.

Product Description:

DAP[®] PHENOPATCH[®] All-Purpose Spackling Paste is a ready-to-use, heavyweight patching compound for repairing and filling cracks and holes in wallboard, drywall, plaster, wood, brick and stone. It spreads smoothly, sands easily and resists cracking for fast, professional repairs. Interior/exterior use.

Suggested Uses:

For filling and repairing:

- Primed wood
- Wallboard/drywall
- Plaster
- Brick
- Stone
- Nail pops

Surface Preparation & Application:

1. Surface must be clean, dry and structurally sound. Lightly sand to ensure adhesion. Bare wood should be primed prior to application with latex primer.
2. Stir thoroughly before use.
3. Apply with a clean putty knife to thoroughly fill all cracks.
4. Finish flush with surface.
5. One application is usually sufficient for small repairs. For repairs deeper than 1/4", apply two or more layers allowing to it dry between applications.
6. May be sanded or painted in 1-5 hours depending on temperature, humidity and depth of fill.
7. Paintable with latex or oil-based paints. Priming is recommended prior to painting with high gloss paint. Follow paint manufacturer's recommendations regarding priming and application.
8. Wash tools immediately after use with water. Be sure container is closed and tightly sealed. Store in a cool, dry place away from extreme heat or cold.

For Best Results:

- Apply in temperatures 40°F and above.
- Do not use outside if rain or freezing temperatures are expected within 24 hours.
- Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- **DO NOT USE AS A SKIM COAT.**
- For exterior applications, always topcoat with a high quality exterior-grade paint when fully cured and prior to water exposure.

Typical Physical & Chemical Characteristics:

Consistency:	Heavy Paste
Vehicle:	Vinyl-Acrylic Polymer
Volatile:	Water
Filler:	Inert Filler
Odor:	Mild
Weight per gallon:	15.0-16.0 lbs
Solids:	72-77 wt%
Application Temperature Range:	40°F and above
Service Temperature Range:	-20°F to 150°F
Shelf Life:	12 Months
Freeze/Thaw Stability:	Yes
Dry Time:	1 to 5 hours depending on temperature, humidity and depth of fill
Paintability:	Paintable with latex and oil-based paints
MSDS No:	00079925005

Clean Up & Storage:

Wash tools immediately after use with water. Dried compound must be cut or scraped away. Be sure container is closed and tightly sealed. Store in a cool, dry place away from extreme heat or cold.

Safety:

See product label and Safety Data Sheet (SDS) for safety information. You can request an SDS by visiting www.phenopatch.com or by calling 1-888-327-8847.

Contains: Calcium carbonate and crystalline silica. May be harmful if inhaled. May cause eye, skin and respiratory irritation. Harmful if swallowed or absorbed through the skin. Do not breathe vapors or dust. Use only with adequate ventilation. Prevent build-up of dust and vapor by opening windows and doors or use other means to ensure fresh air entry during application, drying and sanding. Wet sanding is recommended to reduce dust exposure. Dry sanding of this product may generate dust. Inhalation of dust may cause lung damage or other adverse pulmonary and respiratory effects. When sanding, wear a NIOSH-approved dust mask. Follow dust mask manufacturer's directions for use. Keep exposure below OSHA permissible exposure limits. Avoid contact with eyes, skin and clothing. Wear gloves and safety glasses. Close container after use. Wash thoroughly after handling. **WARNING:** This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. **FIRST AID: SKIN:** Wash thoroughly. **EYE:** Immediately flood with large quantities of water. **INHALATION:** Remove to fresh air. **INGESTION: DO NOT INDUCE VOMITING.** Get medical attention if complications arise from any exposure. For emergencies, call your poison control center at 1-800-222-1222. See product label and Safety Data Sheet (SDS) for additional information. For an SDS, contact PHENOMENAL BRANDS at 410-779-3265 or visit www.phenopatch.com. **KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY**

SATISFACTION GUARANTEED:

If product fails to perform when used as directed, return used container and sales receipt to PHENOMENAL BRANDS, Technical Customer Service, 2400 Boston St., Ste. 200, Baltimore, MD 21224 for replacement product or sales price refund. PHENOMENAL BRANDS will not be liable for incidental or consequential damages.