

# DRYLOK® Extreme Masonry Waterproofer

## MANUFACTURER

### UNITED GILSONITE LABORATORIES

**MAILING:** P.O. Box 70, Scranton, Pennsylvania, 18501

**SHIPPING:** 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509

**TOLL FREE:** 1-800-UGL-LABS (845-5227)

**PHONE:** 1-570-344-1202 • **FAX:** 1-570-969-7634

[www.ugl.com](http://www.ugl.com)



## PRODUCT DESCRIPTION

Latex Base DRYLOK EXTREME Masonry Waterproofer is the Next Generation in waterproof coatings. Features Flexible Encapsulated Polymers which squeeze into the masonry for the ultimate in waterproof protection.

Specially formulated to resist mildew growth on the dry paint film with the incorporation of an environmentally friendly green biocide. Fully transferable 15 year warranty. Tested to ASTM D-7088 Resistance to Hydrostatic Pressure at 15 psi and ASTM D-6904 Resistance to Wind Driven Rain. Reduces radon gas penetration.

- Bright white, smooth finish
- Resists mildew growth on the dry paint film
- Resists 15 psi, equivalent to a wall of water 33 ft. high
- Fully transferable 15 year warranty
- Guaranteed to stop water, even under pressure
- Features flexible encapsulated polymers
- Reduces radon gas penetration
- White is tintable

## BASIC USES

Ideal for interior, exterior, above or below grade masonry walls, basement walls, retaining walls, foundations, landscape walls, cinder blocks, concrete blocks, bare concrete swimming pools, stucco and brick.

## LIMITATIONS

DRYLOK Extreme may be applied over previous coatings in sound condition, but the warranty is void. **Not formulated for horizontal surfaces subject to foot traffic.**

## TECHNICAL DATA

### COMPOSITION:

Latex base

### SHEEN:

N/A

### % WEIGHT SOLIDS:

64-66%

### % VOLUME SOLIDS:

55-57%

### DENSITY (LBS./US GAL.):

9.8-10.0

### VISCOSITY:

110-120 Ku@77°F

### pH:

9.0-9.9

### COLOR:

- White – ready mixed formula

### DRY TIME:

- 2 hours
- To recoat: 3 hours

**Note:** Maximum cure and dry time will be prolonged when slightly humid and damp, cool conditions prevail.

**Note:** When painting the inside of concrete non-potable watertanks, allow to dry at least 1 week before putting into service.

### CLEAN UP:

Warm soapy water  
Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

### COVERAGE (SQ. FT./US GAL.):

- 75-100 sq. ft./gallon

**Note:** Actual coverage will vary depending upon application method, surface texture and porosity.

### RECOMMENDED FILM THICKNESS/COAT:

- 13-21 wet mils/coat

### FLASH POINT:

N/A

### SHELF LIFE:

5 Years

### FREEZE/THAW:

Three cycles

### CONTAINER SIZES:

One quart (US), One gallon (US), and five gallon (US) containers

### VOC

Does not exceed 100 g/L

### TINTING

Use alkali-proof universal tinting colorants. Use only 50% of color normally recommended. Do not use more than 2 fl. oz. of colorant per gallon.

### SURFACE PREPARATION

Masonry surfaces must be clean and free from dirt, dust, grease, oil, form release compound, frost or paint. Patch all holes or cracks with DRYLOK FAST PLUG®, a fast setting hydraulic cement, and smooth the patch evenly with the surface around it. Check the joint where the floor and wall meet and fill any breaks with DRYLOK FAST PLUG®.

**EFFLORESCENCE**, a white, powdery, crystal-like deposit visible on the masonry surface must be removed.

DRYLOK ETCH or muriatic acid, used according to manufacturer's directions, are effective efflorescence removal agents. All masonry surfaces are subject to occurrences of efflorescence.

May be applied on slightly damp surfaces, but best results are obtained when applied over dry surfaces. For best waterproofing results, wait for a dry (rain-free) period.



### DRY TIME:

2 Hours  
Recoat 3 Hours



### CLEAN-UP:

Soap and Water



### COVERAGE:

2 Coats Minimum



### SPREAD RATE:

100 Sq. Ft./Gallon

## WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## APPLICATION

STIR THOROUGHLY BEFORE AND DURING APPLICATION. DO NOT THIN. Air and surface temperatures must be 50°F, or higher. Apply directly on bare masonry. Apply first coat with a roller (3/4" nap), DRYLOK Brush or a good quality nylon bristle brush or sprayer. If rolled, back brush the first coat to fill any pinholes in the masonry. If brushed, work the DRYLOK into the pores of the masonry, making sure to fill all pores and pinholes (see COVERAGE). If sprayed, refer to spray specification sheet D98 at [www.ugl.com](http://www.ugl.com). Apply two coats. Allow to dry 3 hours between coats. The second and subsequent coats may be applied by roller, brush or spray. When painting the inside of concrete swimming pools allow DRYLOK Extreme Waterproofer to dry at least one week before putting into service.

## IMPORTANT

If leaking is still present after two coats, it indicates that pores or pin holes are still open. After applying the second coat of DRYLOK Extreme, carefully inspect the entire wall surface for any pinholes in the waterproof coating. Any affected area should be painted with an additional coat to ensure satisfactory waterproofing results. Paint these areas again.

When painting the inside of concrete non-potable watertanks, allow to dry at least 1 week before putting into service.

## CAUTION

Use only with adequate ventilation.

Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, nose and throat irritation. May be harmful if absorbed through skin. Harmful if swallowed.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use. Do not get in eyes, on skin or clothing. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN.  
DO NOT TAKE INTERNALLY.  
KEEP FROM FREEZING.

## FIRST AID

**EYES:** Flush immediately with large amounts of water for at least 15 minutes. Consult a physician if irritation persists.

**SKIN:** Wash affected areas with soap and water. Consult a physician if irritation persists.

**INGESTION:** Give 1 or 2 glasses of water. If individual is drowsy or unconscious do not give anything by mouth. Consult a physician, medical facility or poison control center for advise about whether to induce vomiting.

**INHALATION:** Remove to fresh air.

For additional health and safety information please refer to the "Safety Data Sheet".

## LIMITED WARRANTY

**United Gilsonite Laboratories (UGL®) warrants DRYLOK® EXTREME Masonry Waterproofer**, when applied according to directions on a properly prepared bare masonry surface, will provide a waterproof coating for fifteen (15) years from the date of application, warranty includes subsequent owners. There are no other

warranties that extend beyond this warranty. This warranty shall not apply when the waterproofer fails due to improper product application, failure to follow label directions, inadequate surface preparation, cracked structural surfaces, reoccurring efflorescence or any conditions not foreseen by UGL. Two coats of DRYLOK EXTREME Waterproofer are required to assure warranted waterproofing. Label directions are as complete as possible, but cannot encompass all conditions, applications and/or surfaces. In the event that the coating fails, your remedy is limited to either replacement of the product purchased or refund of the purchase price. This is the exclusive remedy. For warranty fulfillment, return used product container and sales receipt to UGL, Technical Customer Service, 1396 Jefferson Ave., Dunmore, PA, 18509. **THIS LIMITED WARRANTY EXCLUDES ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE.** UGL will in no event be liable for any incidental or consequential damages. Some States do not allow limitations on how long an implied warranty lasts or the exclusion or limitations of incident or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from State to State.



Extreme Waterproofer		White
1 QT.	4/Case	.....28612
1 GAL.	2/Case	.....28613
5 GAL.	1/Case	.....28615

**DISCLAIMER:** This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.