



FILL and SEAL™ Expanding Foam Sealant

Ready-to-use expanding polyurethane foam sealant

FILL and SEAL™ is a ready-to-use expanding polyurethane foam sealant that fills, seals and insulates gaps greater than 1 inch. It can be used to fill gaps around the home on the interior or exterior. FILL and SEAL™ Expanding Foam Sealant expands to take the shape of gaps, creating a long-lasting, airtight and water-resistant seal to minimize drafts.

Features:

- Fills, seals and insulates gaps greater than 1 inch
- Ready-to-use (straw applicator)
- Forms a long-lasting weathertight and water-resistant seal to minimize drafts
- Interior/exterior use¹
- Adheres to wood, metal, masonry, glass and most plastics²
- Tack free in 15 minutes³; Trims in one hour
- Cures rigid
- Paintable, stainable and sandable
- Cream colored foam
- UL Classified



¹Skin of cured foam can discolor if exposed to natural light. Paint or coat foam for best results.

²The product adheres best when the surfaces are clean and free of oil or chemicals.

³70 ± 5°F and 50 ± 5%RH, 1 inch bead diameter, 6 inch length. Cure rate is dependent on temperature, humidity, and size of foam bead.

In the U.S.

The Dow Chemical Company

Dow Building Solutions
200 Larkin Center, 1605 Joseph Drive
Midland, MI 48674

For Technical Information

1-866-583-BLUE (2583)

For Sales Information

1-800-232-2436

dowbuildingsolutions.com

sprayfoamatdow.com

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

Dow Polyurethane Foam Insulation and Sealants

CAUTION: When cured, these products are combustible and will burn if exposed to open flame or sparks from high-energy sources. Do not expose to temperatures above 240°F (116°C). For more information, consult (Material) Safety Data Sheets ((M)SDS) call Dow at 1-866-583-2583 or contact your local building inspector. In an emergency, call 1-989-636-4400 in the U.S. or 1-519-339-3711 in Canada. When air sealing buildings, ensure that combustion appliances, such as furnaces, water heaters, wood-burning stoves, gas stoves and gas dryers, are properly vented to the outside. See: <http://www.epa.gov/iaq/homes/hip-ventilation.html>.

FILL and SEAL™ Expanding Foam Sealants contain isocyanate and a flammable blowing agent. Read all instructions and (M)SDS carefully before use. Eliminate all sources of ignition before use. Cover all skin. Wear long sleeves, gloves, and goggles or safety glasses. Provide adequate ventilation or wear proper respiratory protection. Contents under pressure. Not to be used for filling closed cavities or voids such as between walls and under tub surrounds.

Building and/or construction practices unrelated to building materials could greatly affect moisture and the potential for mold formation. No material supplier including Dow can give assurance that mold will not develop in any specific system.

®/™* Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow.

Printed in the U.S.A.
Form No. 179 15207-0415 CDP