Safety Data Sheet According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/EN Product name: Battery **Revision date:** 28/08/2013 **Printing date:** 28/08/2013

(a) Product identifier	
Product name:	Battery
(b) Other means of identif	fication
Product description:	Model: SZNS18650-2600mAh
	Product Code: 406978
	Nominal Voltage: 3.7V
	Ampere-hour: 2.6Ah
	Typical Capacity: 2600mAh
	Lithium content: 0.54g
	Weight: 45.83g
	Dimension: 66.3mm×18.3mm (L×D)
(c) Recommended use of t	he chemical and restrictions on use
Recommended use:	Battery.
Restriction on use:	No information available.
(d) Details of the supplier	of the product
Company name(China)	Shenzhen Good&Easy Technology Co., Ltd.
Address:	2/F, Building C6, Hengfeng Industrial Park, Xixiang Town, Bao'an District, Shenzhen, Chin
E-mail:	coco@wangrise.com
Telephone:	+86-755-29990740
(e) Emergency phone num	iber

2. Hazard(s) identification

(a) Classification of the chemical

The batteries are defined as "articles", they are exempted from the requirements of the Hazard Communication Standard. A sealed Li-ion Battery is not hazardous in normal use.

(b) Label elements

Pictogram(s):	No pictogram.
Signal word:	No signal word.
Hazard statements:	No hazard statement.
Precautionary statements:	No precautionary statement.

(c) Description of any hazards not otherwise classified

In case of mistreatment (abusive over charge, reverse charge, external short circuit...) and in case of fault some electrolyte can leak from the cell through the safety device. In these cases refer to the risk of the electrolyte. Contact with internal components may cause irritation or severe burns. Irritating to eyes, respiratory system, and skin. The electrode materials are only hazardous, if the materials are released by mechanical damaging of the cell or if exposed to fire.

Skin touch: Contact with battery electrolyte may cause burns and skin irritation.

Eyes touch: Contact with battery electrolyte may cause burns. Eye damage is possible.

Inhalation: Inhalation of a large number of vapors or fumes released due to heat may cause respiratory.

Ingestion: Ingestion of battery contents may cause mouth, throat and intestinal burns and damage.

(d) Ingredient with unknown acute toxicity

No information available.

3. Composition/information on ingredients

(a) Mixtures information

Chemical name	CAS No.	Concentration%
Lithium cobalt oxide(LiCoO2)	12190-79-3	23
Lithium manganese oxide	12057-17-9	23
Graphite	7782-42-5	18
Copper	7440-50-8	11
Steel Shell	12597-69-2	7.3
Aluminum Foils	7429-90-5	5
lectrolyte	1073-05-8	5
Butadiene-styrene copolymer	9003-55-8	2.2
Polyvinylidene Fluoride	24937-79-9	2
PE Separator	90989-93-8	2
Naphthenic acids, nickel salts	61788-71-4	1.5

4. First-aid measures

(a) Description of first aid measures

Inhalation:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical
	advice / attention if you feel unwell.
Skin contact:	Remove contaminated clothes and rinse the skin with plenty of water. Get medical advice /
	attention if you feel unwell.
Eye contact:	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
	Continue rinsing. Get medical advice / attention if you feel unwell.
Ingestion:	Have victim drink 60 to 240 mL (2-8 oz.) of water. and DO NOT induce vomiting. Get medical aid.

(b) Most important symptoms/effects, acute and delayed

Contact with internal components may cause allergic skin sensitization (rash) and irritate eyes, skin, nose, throat, respiratory system. Cobalt and Cobalt compounds are considered to be possible human carcinogen(s).

(c) Immediate medical attention and special treatment

No information available.

5. Fire-fighting measures

(a) Extinguishing media

Suitable extinguishing media: Use foam, dry powder or dry sand, CO₂ as appropriate.

Unsuitable extinguishing media: No information available.

(b) Special hazards arising from the chemical

Under fire conditions, batteries may burst and release hazardous decomposition products when exposed to a fire situation. This could result in the release of flammable or corrosive materials. Hazardous combustion products: CO, CO₂, Metal oxides, Irritating fumes

(c) Special protective equipment and precautions for fire-fighters

Firefighters must wear fire resistant protective equipment and appropriate breathing apparatus. The staff must equip with filtermask (full mask) or isolated breathing apparatus. The staff must wear the clothes which can defense the fire and the toxic gas. Put out the fire in the upwind direction. Remove the container to the open space as soon as possible. Spray water on the containers in the fireplace to keep them cool until finish extinguishment.

6. Accidental release measures

(a) Personal precautions, protective equipment and emergency procedures

If the battery material is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. The preferred response is to leave the area, dispose the case after the batteries cool and vapors dissipate. Provide maximum ventilation. Avoid skin and eye contact or inhalation of vapors.

(b) Methods and materials for containment and cleaning up

If battery casing is dismantled, small amounts of electrolyte may leak. Collect all released material in a plastic lined container. Dispose off according to the local law and rules. Avoid leached substances to get into the earth, canalization or waters.

7. Handling and storage

(a) Precautions for safe handling

Always follow the warning information on the batteries and in the manuals of devices. Only use the recommended battery types. Keep batteries away from children. For devices to be used by children, the battery casing should be protected against unauthorized access. Unpacked batteries shall not lie about in bulk. In case of battery change always replace all batteries by new ones of identical type and brand. Do not swallow batteries. Do not throw batteries into fire. Avoid deep discharge. Do not short-circuit batteries Use recommended charging time and current.

(b) Conditions for safe storage, including any incompatibilities

If the Lithium Battery is subject to storage for such a long term as more than 3 months, it is recommended to recharge the Lithium Battery periodically. Operating temperature: Charge: $0^{\circ}C^{45}^{\circ}C$. Discharge: $-20^{\circ}C^{60}^{\circ}C$ And recommended at $-20^{\circ}C^{45}^{\circ}C$ for 1 month storage, at $-20^{\circ}C^{35}^{\circ}C$ for 3 months storage. The capacity recovery rate in the delivery state (50% capacity of fully charged) after storage is assumed to be 80% or more. The voltage for a long time storage shall be $3.7V^{4.2V}$ range. Do not storage Lithium Battery haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects. Keep out of reach of children.

Safety Data Sheet According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/EN Product name: Battery

(a) Control parameters

Not established.

(b) Appropriate engineering controls

Under normal conditions (during charge and discharge) release of ingredients does not occur.

(c) Personal protective equipment

Respiratory protection:	No personal respiratory protective equipment normally required. In case of
	inadequate ventilation wear respiratory protection.
Hand protection:	Wear protective gloves.
Eye/face protection:	No personal protective equipment normally required.
Skin/body protection:	Wear protective clothing to prevent contact.

9. Physical and chemical properties

(a) Appearance	Green translucent solid
(b) Odor	Monotony
(c) Odor threshold	Not available.
(d) pH	Not available.
(e) Melting point/freezing point	Not available.
(f) Initial boiling point and boiling range	Not available.
(g) Flash point	Not applicable.
(h) Evaporation rate	Not applicable.
(i) Flammability	Non flammable.
(j) Upper/lower flammability or explosive limits	Not available.
(k) Vapor pressure	Not applicable.
(I) Vapor density	Not available.
(m) Relative density	Not available.
(n) Solubility(ies)	Insoluble in water.
(o) Partition coefficient: n-octanol/water	Not available.
(p) Auto-ignition temperature	130 °C
(q) Decomposition temperature	Not available.
(r) Viscosity	Not available.

10. Stability and reactivity

(a) Reactivity

Stable under recommended storage and handling conditions.

(b) Chemical stability

Stable under normal conditions.

(c) Possibility of hazardous reactions

When heated above 150°C the risk of rupture occurs. Due to special safety construction, rupture implies controlled release of pressure without ignition.

Safety Data Sheet According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/EN Product name: Battery

(d) Conditions to avoid

Do not subject Lithium Battery to mechanical shock. Keep away from open flames, high temperature.

(e) Incompatible materials

Strong oxidizer, strong acid.

(f) Hazardous decomposition products

Under fire conditions, the electrode materials can form carcinogenic nickel and cobalt oxides.

11. Toxicological information

(a) Information on the likely routes of exposure

Inhalation:	Inhalation of a large number of vapors or fumes released due to heat may cause respiratory.
Ingestion:	Ingestion of battery contents may cause mouth, throat and intestinal burns and damage.
Skin contact:	Contact with battery electrolyte may cause burns and skin irritation.
Eye contact:	Contact with battery electrolyte may cause burns. Eye damage is possible.

Under normal conditions (during charge and discharge) release of ingredients does not occur. If accidental release occurs see information in section 2, 3, and 4. Swallowing of a battery can be harmful. Call the local Poison Control Centre for advice and follow-up.

(b) Information on toxicological characteristics

Acute toxicity:	No data available.			
Skin corrosion/irritation:	The liquid in the battery irritates.			
Serious eye damage/irritation:	The liquid in the battery irritates.			
Respiratory sensitization:	The liquid in the battery may cause sensitization to some person.			
skin sensitization:	The liquid in the battery may cause sensitization to some person.			
Carcinogenicity:	Cobalt and Cobalt compounds are considered to be possible human			
	carcinogen(s).			
Germ Cell Mutagenicity:	No data available.			
Reproductive Toxicity:	No data available.			
STOT-Single Exposure:	No data available.			
STOT-Repeated Exposure:	No data available.			
Aspiration Hazard:	No data available.			

12. Ecological information

(a) Ecotoxicity

Water hazard class 1(Self-assessment): slightly hazardous for water.

(b) Persistence and Degradability

No information available.

(c) Bioaccumulative potential

No information available.

(d) Mobility in soil

No information available.

(e) Other adverse effects

No information available.

13. Disposal considerations

(a) Safe handling and methods of disposal

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

14. Transport information

According to PACKING INSTRUCTION 965 ~ 970 of IATA DGR 56rd Edition for transportation, the special provision 188 of IMDG (inc Amdt 35-10). The batteries should be securely packed and protected against short-circuits. Examine whether the package of the containers are integrate and tighten closed before transport. Take in a cargo of them without falling, dropping, and breakage. Prevent collapse of cargo piles. Don't put the goods together with oxidizer and chief food chemicals. The transport vehicle and ship must be cleaned and sterilized otherwise it is not allowed to assemble articles. During transport, the vehicle should prevent exposure, rain and high temperature. For stopovers, the vehicle should be away from fire and heat sources. When transported by sea, the assemble place should keep away from bedroom and kitchen, and isolated from the engine room, power and fire source. Under the condition of Road Transportation, the driver should drive in accordance with regulated route, don't stop over in the residential area and congested area. Forbid to use wooden, cement for bulk transport.

(a) UN number	3480&3481
(b) UN Proper shipping name	LITHIUM ION BATTERIES (including lithium ion polymer batteries) or;
	LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT or LITHIUM
	ION BATTERIES PACKED WITH EQUIPMENT (including lithium ion
	polymer batteries)
(c) Transport hazard class(es)	9
(d) Packing group (if applicable)	II
(e) Marine pollutant (Yes/No)	No
(f) Transport in bulk (according to Annex II of	No information available.
MARPOL 73/78 and the IBC Code)	
(g) Special precautions	No information available.

15. Regulatory information

(a) Safety, health and environmental regulations specific for the product in question

	USA	EU	Japan	Korea	China	Canada
CAS No.	TSCA	EINECS	ENCS	ECL	IECSC	DSL

Version: 1.0/EN Product name: Battery

Revision date: 28/08/2013 Printing date: 28/08/2013

12190-79-3	Listed	Listed	Listed	Listed	Listed	Listed
12057-17-9	Listed	Not listed	Not listed	Listed	Not listed	Not listed
7782-42-5	Listed	Listed	Not listed	Listed	Listed	Listed
7440-50-8	Not listed					
12597-69-2	Not listed					
7429-90-5	Listed	Listed	Not listed	Listed	Listed	Listed
1073-05-8	Listed	Listed	Listed	Listed	Listed	Listed
9003-55-8	Listed	Not listed	Listed	Listed	Listed	Listed
24937-79-9	Listed	Not listed	Listed	Listed	Listed	Listed
90989-93-8	Not listed	Listed	Not listed	Not listed	Not listed	Not listed
61788-71-4	Listed	Listed	Listed	Listed	Listed	Listed

16. Other information, including date of preparation or last revision

(a) Preparation and revision information

Date of previous revision: Not applicable.Date of this revision: 28/08/2013Revision summary: The first New SDS

(b) Abbreviations and acronyms

TSCA:	Toxic Substances Control Act, The American chemical inventory.
DSL	Domestic Substances List
EINECS:	European Inventory of Existing Commercial chemical Substances
ENCS	Japanese Existing and New Chemical Substances
ECL:	Existing Chemicals List, the Korean chemical inventory.
IECSC:	Inventory of existing chemical substances in China.

(c) Disclaimer

Because all of our batteries are defined as "articles", they are exempted from the requirements of the Hazard Communication Standard. The information in this SDS is provided all the relevant data fully and truly. However, the information is provided without any warranty on their absolute extensiveness and accuracy. This SDS was prepared to provide safety preventive measures for the users who have got professional training. The personal user who obtained this SDS should make independent judgment for the applicability of this SDS under special conditions. In these special cases, we do not assume responsibility for the damage.

----- End of the SDS ------