



**CHALKED  
ULTRA MATTE SPRAYS**

**DESCRIPTION AND USES**

Rust-Oleum® Chalked Ultra Matte Sprays create an ultra matte finish with excellent coverage and adhesion on furniture and home décor. Chalked Ultra Matte Sprays provide one coat coverage on most surfaces without special surface preparation or priming. It can be painted or distressed, giving the project a one of a kind look. It is suitable for use on wood, metal, ceramic, glass, canvas and more.

Chalked Ultra Matte Sprays feature an advanced spray system that allows you to spray at any angle, even upside down for those hard to reach areas. A comfort spray tip with a wider finger pad to reduce fatigue caused by continuous spraying.

Some plastics made of polyethylene such as Little Tikes® children's products are manufactured in a way that may hinder maximum paint adhesion. Test this product in an inconspicuous area to test for compatibility on the surface. Not for use on galvanized metal.

**PRODUCTS**

SKU (12 ounces)	Description
302590	Charcoal
302591	Linen White
302592	Aged Gray
302593	Country Gray
302594	Blush Pink
302595	Serenity Blue
302596	Chiffon Cream
302597	Tidal Pond
302598	Coastal Blue
302599	Matte Clear

**PAINTING CONDITIONS**

Use outdoors or in a well ventilated area such as an open garage. Apply when the temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 85% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Cover the surrounding area to protect from spray mist.

**PRODUCT APPLICATION**

**SURFACE PREPARATION**

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with soap and water and let dry. Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy or porous surfaces. Remove any wax by lightly wiping the surface with mineral spirits.

**WARNING:** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**PRODUCT APPLICATION (cont.)**

**PRIMING**

Priming is not required for most surfaces. For excellent coverage, use of a Rust-Oleum primer can be used on surfaces such as bare wood and treated wood. Recommended primers include:

- Painter's Touch 1908502 Flat Gray
- Painter's Touch 224430T Flat White

**APPLICATION**

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can upright 10-12" from the surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply 2 or more light coats a few minutes apart. Do not use near open flame.

**DRY & RECOAT**

Dry and recoat times are based on 70°F (21°C) and 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 20 minutes and is dry to handle in 1 hour. May be recoated in 1 hour or after 48 hours. The finish coat is fully dry in 24 hours. NOTE: On plastic, maximum paint adhesion and durability is achieved in 5-7 days. Chalked Clear Protective Topcoat can be applied for added protection. Apply according to the label instructions.

**CLEAN UP**

Wipe off tip before storing. Clean-up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

**CLOGGING**

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

**DISTRESSING**

This paint can be distressed if desired. To distress the surface, lightly sand the surface with fine to medium grit sandpaper or a sanding sponge. Wait 2 hours before sanding or distressing.

**TECHNICAL DATA****CHALKED ULTRA MATTE SPRAYS****PHYSICAL PROPERTIES**

		CHALKED ULTRA MATTE PAINT
<b>Resin Type</b>		Acrylic Modified Alkyd
<b>Pigment Type</b>		Varies with color
<b>Solvents</b>		Acetone, Mineral Spirits, Naphtha
<b>MIR</b>		0.80 Max
<b>Fill Weight</b>		12 ounces
<b>Recommended Dry Film Thickness (DFT) Per Coat</b>		1.0-2.0 mils (25-50 $\mu$ )
<b>Practical Coverage at Recommended DFT</b>		12 sq.ft./can (1.11 m <sup>2</sup> /can)
<b>Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity</b>	<b>Touch</b>	20 minutes
	<b>Handle</b>	1 hour
	<b>Recoat</b>	Within 1 hour or after 48 hours
<b>Shelf Life</b>		5 years
<b>Flash Point</b>		-156°F (-104°C)
<b>Safety Information</b>		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.