

P2574 60" Ceiling Fan

 Ceiling mounted • Damp location listed 

Description:

Refresh your indoor or covered outdoor living spaces with the crisp, clean style of the 60" Whirl fan. The stylish design comes in Antique Nickel, Antique Bronze and Forged Black finish options. The five-blade fan features an all weather damp location rating (ABS) to accommodate a variety of settings throughout the home. White opal glass shade with a 17W LED light source offers a warm 3000K-color temperature, energy savings and maintenance benefits for the home. Whirl features a dual mount system and a three-speed pull chain fan switch, as well as an on/off pull chain switch to operate the light.

Specifications:

- Antique Nickel (-81) (Plated)
- Steel construction Diffuser Refresh your indoor or covered outdoor living spaces with the crisp, clean style of the 60" Whirl fan.
- The five-blade fan features an all-weather damp location rating to accommodate a variety of settings throughout the home.
- Includes Progress Lightings dependable AirPro motor for a smooth, quiet performance
- Features a 17W dimmable, 1400 Lumen, 3000K, 90CRI LED replaceable light module, offering energy- and cost-savings benefits with a white opal shade
- Whirl features a dual mount system to offer greater flexibility when installing. The fan can be installed on a flat or sloped ceiling.
- Includes a three-speed pull chain fan switch, as well as an on/off pull chain switch to operate the light.
- Reversible motor for year round comfort allows you to choose either a down draft (summer) or an up draft (winter)
- Add a P2630-30 wall control or P2614-30 remote control for added convenience.
- Rated for damp locations
- ABS blades are included for maintenance free operation inside or out
- Limited Lifetime Warranty on the motor for peace of mind
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 80' of wire supplied
-

Performance:

Number of Modules	1
Input Power	18w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1386/77 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	46,000 (L70/TM-21)
EMI/RFI	Title 20
Min. Start Temp	-10 °C
Max. Operating Temp	40 °C
Warranty	Limited Lifetime warranty
Labels	UL Damp location listed

P2574-8130K

Images:



Dimensions:

Diameter: 60"
Height: 15-7/8"