

# Safety Data Sheet

24 Hour Emergency Phone Numbers:

Medical/Poison Control:

In U.S.: Call 1-800-222-1222

Outside U.S.: Call your local poison

control center

Transportation/National Response

Center:

1-800-535-5053 1-352-323-3500

NOTE: The National ResponseCenter emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this MSDS are further described in Section 16.

# 1. Identification

This Material Safety Data Sheet is available in American Spanish upon request. Los Datos de Serguridad del Producto pueden obtenerse en Espanol si lo riquiere.

Product Name: Alex Painters Acrylic Latex Caulk Revision Date: 5/14/2015

Product UPC Number: 18065 Supercedes Date: 4/20/2014

Product Use/Class: Caulking Compound SDS No: 00010011001

Manufacturer: DAP Products Inc.

2400 Boston Street Suite 200 Baltimore, MD 21224-4723

888-327-8477 (non-emergency matters)

Preparer: Regulatory Department

# 2. Hazards Identification

**EMERGENCY OVERVIEW:** Under normal use conditions, this product is not expected to cause adverse health effects.

### **GHS Classification**

Not a hazardous substance or mixture.

### Symbol(s) of Product

Not a hazardous substance or mixture.

### Signal Word

Not a hazardous substance or mixture.

# 3. Composition/Information on Ingredients

 Chemical Name
 CAS-No.
 Wt. %
 GHS Symbols
 GHS Statements

 Limestone
 1317-65-3
 50-75
 GHS07
 H332

Petroleum distillates 64741-88-4 2.5-10 GHS06 H331

| Diethylene glycol dibenzoate  | 120-55-8   | 1.0-2.5 GHS07          | H312           |
|-------------------------------|------------|------------------------|----------------|
| Solvent ref. light paraffinic | 64741-89-5 | 1.0-2.5 GHS06          | H331           |
| Quartz                        | 14808-60-7 | 0.1-1.0 GHS07          | H302           |
| Titanium dioxide              | 13463-67-7 | 0.1-1.0 No Information | No Information |

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

# 4. First-aid Measures

**FIRST AID - INHALATION:** Material is not likely to present an inhalation hazard at ambient conditions. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

FIRST AID - SKIN CONTACT: No health hazards are known to exist. In case of contact, wash skin immediately with soap and water.

**FIRST AID - EYE CONTACT:** In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

FIRST AID - INGESTION: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

# 5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: None known.

**SPECIAL FIREFIGHTING PROCEDURES:** Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

## 6. Accidental Release Measures

**ENVIRONMENTAL MEASURES:** No Information

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Scrape up dried material and place into containers. Use personal protective equipment as necessary. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

# 7. Handling and Storage

**HANDLING:** KEEP OUT OF REACH OF CHILDREN!DO NOT TAKE INTERNALLY. Use only with adequate ventilation. Ensure fresh air entry during application and drying. Wash thoroughly after handling.

**STORAGE:** Avoid excessive heat and freezing. Do not store at temperatures above 120 degrees F. Store away from caustics and oxidizers.

# 8. Exposure Controls/Personal Protection

### Ingredients with Occupational Exposure Limits **Chemical Name ACGIH TLV-TWA ACGIH-TLV STEL OSHA PEL-TWA OSHA PEL-CEILING** Limestone N.E. N.E. 15 mg/m3 TWA N.E. total dust, 5 mg/m3 TWA respirable fraction Petroleum distillates N.F. N.F. N.E. N.E. Diethylene glycol dibenzoate N.E. N.E. N.E. N.E. Solvent ref. light paraffinic N.E. N.E. N.E. N.E. Quartz 0.025 mg/m3 TWA N.E. N.E. N.E. respirable fraction Titanium dioxide N.E. 15 mg/m3 TWA N.E. 10 mg/m3 TWA total dust

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

### **Personal Protection**



**RESPIRATORY PROTECTION:** No personal respiratory protective equipment normally required. National Institute for Occupational Safety and Health (NIOSH) has recommended that the permissible exposure limit be changed to 50 micrograms respirable free silica per cubic meter of air (0.05 mg/m3) as determined by a full shift sample up to 10-hour work shift.



SKIN PROTECTION: Rubber gloves.



EYE PROTECTION: Goggles or safety glasses with side shields.



OTHER PROTECTIVE EQUIPMENT: Not required under normal use.



**HYGIENIC PRACTICES:** Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

# 9. Physical and Chemical Properties

Appearance: White to Off-White Physical State: Paste

Odor:Very Slight AmmoniaOdor Threshold:Not EstablishedDensity, g/cm3:1.51 - 1.61pH:Between 7.0 and 12.0

Freeze Point, °C:

Not Established

Viscosity (mPa.s):

Not Established

Solubility in Water:

Not Established

Partition Coeff., n-octanol/water:

Not Established

**Decomposition Temperature, °C:** Not Established **Explosive Limits, %:** N.I. - N.I.

Boiling Range, °C: N.I. - N.I. Auto-Ignition Temperature, °C Not Established

Minimum Flash Point, °C: 93.3 Vapor Pressure, mmHg: No Information

Evaporation Rate: Slower Than n-Butyl Acetate Flash Method: Seta Closed Cup

Vapor Density: Heavier Than Air

Combustibility: Does not Support Combustion

(See "Other information" Section for abbreviation legend)

(If product is an aerosol, the flash point stated above is that of the propellant.)

# 10. Stability and Reactivity

**STABILITY:** Stable under recommended storage conditions.

CONDITIONS TO AVOID: Excessive heat and freezing.

**INCOMPATIBILITY:** Incompatible with strong bases and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e., COx, NOx.

# 11. Toxicological Information

EFFECT OF OVEREXPOSURE - INHALATION: Under normal use conditions, this product is not expected to cause adverse health

effects. Inhalation of vapors in high concentration may cause mild irritation of respiratory system (nose, mouth, mucous membranes).

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Under normal use conditions, this product is not expected to cause adverse health effects. Prolonged or repeated contact with skin may cause mild irritation.

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** Under normal use conditions, this product is not expected to cause adverse health effects. Direct eye contact may cause irritation.

**EFFECT OF OVEREXPOSURE - INGESTION:** Under normal use conditions, this product is not expected to cause adverse health effects. Single dose oral toxicity is very low. Amounts ingested incidental to industrial handling are not likely to cause injury; however, ingestion of large amounts may cause injury.

**CARCINOGENICITY:** No Information

PRIMARY ROUTE(S) OF ENTRY: Inhalation, Skin Contact

### **Acute Toxicity Values**

The acute effects of this product have not been tested. Data on individual components are tabulated below

| <u>CAS-No.</u><br>1317-65-3 | <u>Chemical Name</u><br>Limestone | Oral LD50<br>6450 mg/kg Rat | Dermal LD50<br>>2000 mg/kg | Vapor LC50<br>>20 mg/L |
|-----------------------------|-----------------------------------|-----------------------------|----------------------------|------------------------|
| 64741-88-4                  | Petroleum distillates             | >5000 mg/kg Rat             | >2000 mg/kg Rabbit         | 2.18 mg/L Rat          |
| 120-55-8                    | Diethylene glycol dibenzoate      | 2830 mg/kg Rat              | 2000 mg/kg Rabbit          | > 200 mg/L Rat         |
| 64741-89-5                  | Solvent ref. light paraffinic     | >5000 mg/kg Rat             | >5000 mg/kg Rabbit         | 2.18 mg/L Rat          |
| 14808-60-7                  | Quartz                            | 500 mg/kg Rat               | >2000 mg/kg                | >20 mg/L               |
| 13463-67-7                  | Titanium dioxide                  | >10000 mg/kg Rat            | >5000 mg/kg Rabbit         | >20 mg/L               |

N.I. = No Information

# 12. Ecological Information

ECOLOGICAL INFORMATION: Ecological injuries are not known or expected under normal use.

## 13. Disposal Information

**DISPOSAL METHOD:** This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulation, 40 CFR Section 261. Dispose as hazardous waste according to all local, state, federal and provincial regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Scrape up dried material and place into containers. Use personal protective equipment as necessary. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

## 14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

**DOT Proper Shipping Name:** Not Regulated.

DOT Technical Name:N.A.Hazard SubClass:N.A.DOT Hazard Class:N.A.DOT UN/NA Number:N.A.

Packing Group: N.A.

# 15. Regulatory Information

# U.S. Federal Regulations:

# **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Health Hazard, Chronic Health Hazard

### **SARA SECTION 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

### TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA12(b) components exist in this product in concentrations at or above their thresholds.

### **CALIFORNIA PROPOSITION 65 CARCINOGENS**

WARNING: This product contains chemicals known to the State of California to cause cancer.

### **CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**

This product does not contain any chemicals known to the State of California to cause birth defects or other reproductive harm.

# International Regulations: As follows -

## **CANADIAN WHMIS:**

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class Consumer Commodity

# 16. Other Information

Revision Date: 5/14/2015 Supersedes Date: 4/20/2014

Reason for revision: HazCom2012/GHS Conversion

Datasheet produced by: Regulatory Department

**HMIS Ratings:** 

| 1.1 141   | 4   | F1 1, 200     | • | D             | _   | Description of Description |   |
|-----------|-----|---------------|---|---------------|-----|----------------------------|---|
| ∣ Health: | 1 1 | Flammability: | 0 | ∣ Reactivity: | 1 0 | Personal Protection:       | X |

VOC Less Water Less Exempt, g/L:58.4

VOC, Material, g/L:37

VOC as Defined by California Consumer Product Regulation, Wt/Wt%:1.0

### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

| H302 | Harmful if swallowed.         |
|------|-------------------------------|
| H312 | Harmful in contact with skin. |

H331 Toxic if inhaled.
H332 Harmful if inhaled.

### Icons for GHS Pictograms shown in Section 3 describing each ingredient:



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.