Dalton Enterprises, Inc.

Product: Gray Crack-Stix & Pli-Stix
Phone: (203) 272-3221

SDS Date: 05/22/2018



SAFETY DATA SHEET



Section I - PRODUCT AND COMPANY IDENTIFICATION

Product Name: Latexite® Gray Crack-Stix/Pli-Stix Crack & Joint Filler

Manufacturer Name: Dalton Enterprises, Inc.

Product	Package Size	Item #	UPC
Medium (1/2" Diameter)	Pli-Stix Clamshell (30 ft.)	35100	0 90932 35100 4
Medium (1/2" Diameter)	2 Gallon Pail (125 ft.)	2051	0 90932 02051 1
Small (1/4" Diameter)	2 Gallon Pail (225 ft.)	2061	0 90932 02061 0
Medium (1/2" Diameter)	Full Spool (500 ft.)	2052	0 90932 02052 8
Small (1/4" Diameter)	Full Spool (1000 ft.)	2062	0 90932 02062 7

Address: 131 Willow Street Cheshire, CT 06410

Telephone Number: (203) 272-3221

24 Hour Emergency Number: (203) 272-3221

U.S. And Canada: (203) 272-3221

Trade Names and Synonyms: Crack Filler

Recommended Use and Restrictions: Joint sealer / Crack filler

Section II - HAZARDS IDENTIFICATION

Classification

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Irritation	Category 2B

Label Elements

GHS Pictogram:

Signal Word: Warning

Hazard Statements:

Causes skin irritation Causes eye irritation

Precautionary Statements – Prevention

Obtain special instructions before use

Dalton Enterprises, Inc.

Product: Gray Crack-Stix & Pli-Stix

Phone: (203) 272-3221 SDS Date: 05/22/2018

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Precautionary Statements – Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs, Get medical advice/attention.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms, Call a POISON CENTER or doctor/physician.

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container in accordance with local regulations.

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Contact with heated material will cause burns

Interactions with Other Chemicals

No information available.

Section III - COMPOSITION

CAS#	Component	% Composition	
64742-52	Distillates (petroleum), hydrotreated heavy naphthenic*	1 - 2.5%	

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

Section IV - FIRST-AID MEASURES

Emergency and First Aid Procedures

General Advice: Present this safety data sheet to the physician in attendance.

Eye Contact: If hot material is splashed in eye immediately flush eyes with clean water for an extended

Dalton Enterprises, Inc. Product: Gray Crack-Stix & Pli-Stix

Phone: (203) 272-3221 SDS Date: 05/22/2018

time of not less than 5 minutes. Seek medical attention.

Skin Contact: If hot material is spilled on skin cool in cold water immediately. DO NOT try to peel solidified product from skin. Vegetable Oil or Baby Oil is recommended for removal from skin.

Ingestion: If swallowed do NOT induce vomiting. Seek medical attention if symptoms develop.

Inhalation: Move to fresh air if symptoms develop. If irritation persists, see a physician. If not breathing give artificial respiration.

Most Important Symptoms: Possibility of minor eye and skin irritation.

Indication of Immediate Medical Attention and Special Treatment Needed: Treat Symptomatically

Section V - FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Water Spray, CO2, dry chemical, foam, sand

Unsuitable Extinguishing Media: Do not use heavy water stream

Specific Hazards arising From the Chemical: Combustion may yield fumes, smoke, carbon monoxide and carbon dioxide.

Special Protective Equipment and Precautions for Firefighters: Wear self contained breathing apparatus equipped with a full face piece and operated in a pressure demand mode. Wear approved protective clothing. Personnel without suitable respiratory protection must leave the area to avoid significant exposure to hazardous gases from combustion, burning or decomposition.

Section VI - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures: Avoid skin and eye contact, use proper protective equipment recommended in section 8.

Methods and Materials for Containment and Cleanup: Contain spill. If spilled in an enclosed area. Ventilate. Cool material to solidify. Wear proper personal protective clothing and equipment. Do not flush liquid in public sewer, water systems or surface waters. Recover as much as possible and absorb remainder with an inert material. Place into labeled closed containers and store in safe locations for proper disposal. Wash spilled areas with soap and water.

Section VII - HANDLING AND STORAGE

Precautions for Safe Handling: For Hot Material avoid eye contact, repeated or prolonged skin contact or inhalation of vapors. Wash thoroughly after handling. Use in well ventilated areas.

Conditions for Safe Storage, Including Incompatibilities: Keep container closed when not in use. Do not store in open, unlabeled or mislabeled containers. Unheated material presents no known hazards. Store in areas where sources of ignition have been eliminated from vicinity of stored products.

Section VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component ACGIH TWA		OSHA PEL (TWA)	NIOSH IDLH	
	(mg/m^3)	(mg/m3)		
Distillates (petroleum),	5 mg/m ³ 8 hours.	5 mg/m ³ 8 hours	TWA: 5 mg/m ³ 10 hours. Mist	

Dalton Enterprises, Inc. Product: Gray Crack-Stix & Pli-Stix

Phone: (203) 272-3221 SDS Date: 05/22/2018

hydrotreated heavy naphthenic	Form: Inhalable	STEL: 10 mg/m ³ 15 minutes.
		Mist

Engineering Controls: Provide effective general, and when necessary, local exhaust ventilation to draw vapors and fumes of molten material away from workers to prevent routine inhalation.

Individual Protection Measures

Eyes/Face: Safety goggles

Skin: Wear protective heat resistant gloves, aprons, long sleeve shirts and hard sole shoes when heating

and/or applying hot material.

Respiratory: Melting of material should be limited to outside, open areas to ensure exposure limits are not exceeded. Use NOISH/MSHS approved respirator whenever exposure to fumes or vapors

exceed exposure limits.

Hygienic controls: Wash thoroughly with soap and water before eating or drinking. Wash

contaminated clothing.

Section IX - PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Gray SolidUpper Explosive Limit: N/APhysical State: Solid @ Room TempLower Explosive Limit: N/A

Odor: Asphaltic odor when heated Vapor Pressure: N/A

Odor Threshold: N/A Vapor Density: Heavier than air

pH: N/A Specific Gravity: 2.5

Melting Point: N/A Solubility In Water: Insoluble

Flash Point: N/A

Evaporation Rate: Slower then N-Butyl Acetate

Auto Ignition Temperature: N/A

Decomposition Temperature: N/A

Flammability: N/A Max Voc: 0 g/L

Section X - STABILITY AND REACTIVITY

Reactivity: None known under normal conditions **Stability:** Stable under normal conditions and usage

Hazardous Reactions: None known under normal conditions **Conditions to avoid:** Strong Oxidizing Agents, Excessive Heat

Incompatibility: Strong oxidizers

Hazardous Decomposition Products: Combustion may yield fumes, smoke, carbon monoxide and carbon

dioxide.

Section XI - TOXICOLOGICAL INFORMATION

Health Effects

Eye Contact: Irritation may result from hot material Skin Contact: Irritation may result from hot material Ingestion: Irritation may result from hot material Inhalation: Irritation may result from hot material

Dalton Enterprises, Inc. Product: Gray Crack-Stix & Pli-Stix

Phone: (203) 272-3221 SDS Date: 05/22/2018

Numerical Measures of Toxicity

	Component	CAS#	Acute oral toxicity LD50	Acute dermal toxicity LD50
1	Distillates (petroleum), nydrotreated heavy naphthenic	64742-52-5	>5000 mg/kg (rat)	>2000 mg/kg (rabbit)

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization: Product not known to cause sensitization

Mutagenic Effects: None known

Carcinogenicity: Based on available data, classification criteria not met

Reproductive Toxicity: No toxicity known STOT – Single Exposure: None Known STOT – Repeated Exposure: None Known Chronic Toxicity: No Known Effect

Target Organ Effects: Eyes, Skin, and respiratory system.

Aspiration Hazard: Based on available data, the classification criteria are not met.

Section XII - ECOLOGICAL INFORMATION

Ecological Fate:No data availablePersistence/DegradabilityNo data availableBioaccumulation Potential:No data availableMobility in Soil:No data availableOther Adverse Effects:No data available

Analysis for ecological effects has not been conducted.

Section XIII - DISPOSAL CONSIDERATIONS

Waste Disposal Information: Dispose of waste & contaminated packaging in accordance with federal, state, and local regulations.

Section XIV - TRANSPORT INFORMATION

DOT – U.S. Department of Transportation **Proper Shipping Name:** Not regulated

IATA – International Air Transport Association Proper Shipping Name: Not regulated

IMDG – International Maritime Dangerous Goods

Proper Shipping Name: Not regulated

Dalton Enterprises, Inc.

Product: Gray Crack-Stix & Pli-Stix Phone: (203) 272-3221 SDS Date: 05/22/2018

Section XV - REGULATORY INFORMATION

International Inventories

TSCA: Complies

DSL/NDSL: Complies **US Federal Regulations**

SARA 313: This product contains no chemicals subject to Annual Release Reporting Requirements

under SARA Title III, Section 313 (40 CFR 372)

SARA Hazard Category (311/312): Non Hazardous

CWA (Clean Water Act): This product contains no chemicals regulated by the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA: This product contains no substances regulated by the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

US State Regulations

Component Name	CAS	State Right to Know		
Component Name	CAS	MA	NJ	PA
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	No	Yes	No

International Regulations

WHMIS: Non Hazardous

Section XVI - OTHER INFORMATION

Other precautions:

Keep out of reach of children.

Always read label plus precautions and follow directions carefully.

Use only with adequate ventilation.

Do not take internally.

Avoid contact with eyes and skin.

Wash thoroughly after using.

NFPA Rating: Health 1; Fire 1: Reactivity 0

Revision Date: 05/22/18 **Supersedes**: 05/02/18

Disclaimer/Statement of Liability:

THE INFORMATION AND RECOMMENDATIONS PROVIDED HEREIN ARE BELIEVED TO BE ACCURATE AS OF THE DATE HEREOF. HOWEVER, SUCH INFORMATION AND RECOMMEN- Dalton Enterprises, Inc.

Product: Gray Crack-Stix & Pli-Stix
Phone: (203) 272-3221

SDS Date: 05/22/2018

DATIONS ARE PROVIDED WITHOUT WARRANTY OF ANY KIND AND THIS CORPORATION DISCLAIMS ANY AND ALL LIABILITY OR LEGAL RESPONSIBILITY FOR USE OR RELIANCE UPON SAME.