



# GRANITE GRIP™ CONCRETE COATING

## NO. 650 & NO. 655



### PRODUCT INFORMATION

This interior/exterior decorative floor coating revives concrete surfaces by providing a durable protective finish that fills hairline cracks up to 1/8" and resists dirt and grease. Its slip-resistant coating is ideal for horizontal surfaces such as walkways, patios, porches, and pool decks.

### RECOMMENDED USES:

Use on properly prepared interior and exterior horizontal surfaces such as:

- Porous Concrete
- Masonry
- Brick

### PRODUCT SPECIFICATIONS:

#### Tint Bases/Max Tint Load:

No. 650 128 oz. / 1/16 oz. max  
 No. 655 128 oz. / 1/16 oz. max

**Gloss:** < 10 @ 60°

**Sheen:** < 10 @ 85°

**Resin Type:** Acrylic

**Weight per Gallon:** 10.92 lbs

**% Solids by Volume:** 39.1%

**% Solids by Weight:** 54.0%

**VOC:** < 50 g/L

**Flash Point:** N/A

**Viscosity:** 118 to 128 KU's

#### Recommended Film Thickness (approximate):

Wet: 40 mils, Dry: 16 mils @ 40 Sq. Ft./Gal. (2 Coats)

Wet: 27 mils, Dry: 11 mils @ 60 Sq. Ft./Gal. (2 Coats)

**Coverage:** 40 to 60 Sq. Ft./Gal. (2 Coats required)

### APPLICATION:

**Brush:** Synthetic

**Roller:** 1/4" Adhesive Roller

**Airless Spray:** N/A

**Texture Sprayer:** Capable of 40 psi

**Tip:** 4 mm

**Filter:** N/A

**Thinning:** DO NOT THIN. Product is formulated for use at package consistency.

**Dry Time:** @ 77°F (25°C), 50% RH

Longer dry time required in cooler temperatures and in higher humidity.

**To Touch:** 1 hour

**To Recoat:** 3-4 hours

Apply a first coat using a 1/4" adhesive roller cover, nylon/polyester brush or synthetic stain pad.  
 NOTE: The first coat will act as the base coat and it will not completely cover the surface by design. Avoid over application on the first coat. Apply in 4' x 4' sections. Begin with the roller in the center of the section and roll outwards in random directions. Avoid regular patterns and knock down hard edges using the roller. Allow first coat to dry then apply second coat in the same method as the first coat. While two coats are necessary, additional coats may help hide previous surface imperfections or cover over dark colors. For large projects, consider using a texture sprayer with a 4mm tip. Spray in 4' x 4' sections and back roll with an adhesive roller cover.

### SURFACE PREPARATION:

(Proper surface preparation is required.) All surfaces must be clean, sound, dry and free of any dirt, oil, and grease. For hairline cracks up to 1/8", completely fill in with coating using a nylon/polyester brush and allow to dry completely prior to roller application. **Uncoated Concrete or Masonry Surfaces:** Allow new surfaces to cure 30 days. Clean and etch surface using a product such as a muriatic acid etcher (read and follow all manufacturer's label and safety directions) to achieve a textured profile similar to 150 grit sandpaper. **Previously Coated Surfaces:** For a painted surface in sound condition, use a product to clean and prepare the surface. If the coating is failing or peeling, use a paint stripper to remove old coating or scrape/sand down to a sound concrete surface. Scuff sand glossy surfaces. Clean and spot etch any exposed concrete. Remove all dust with a damp cloth, allow to dry.

### CLEAN UP:

Clean all tools and equipment with clean water. For disposal of empty containers and unused product, contact your household refuse collection service.

COMPLIES WITH THE BELOW AS OF 12/1/15			
SCAQMD	YES	OTC	YES
CARB	YES	LADCO	YES

### CAUTIONS/LIMITATIONS:

- DO NOT THIN.
- Intermix all cans of same product to ensure color uniformity. Stir before applying.
- Use product when air and surface temperatures are between 50-90° F.
- Do not apply in direct sunlight.
- Not for surfaces subject to vehicle traffic or parking.

### GENERAL INFORMATION:



**Warning!** Causes eye and skin irritation. Wear protective clothing, gloves, eye, and face protection. Do not eat, drink, or smoke when using this product. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

**First aid: If in eyes:** Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists. **If on skin:** Wash with plenty of soap and water. **If swallowed:** Rinse mouth and get medical attention if you feel unwell.