



USE & CARE MANUAL



KILZ® PVA Drywall Primer Water Base Sealer

- Formulated to effectively seal new drywall
- Helps to reduce the number of topcoats required to achieve a uniform, professional finish
- Interior use latex primer
- Promotes topcoat adhesion
- Ready to brush, roll or spray
- Fast drying
- Easy soap and water cleanup

WHERE TO USE:

KILZ® PVA Interior Primer is designed for use on new drywall. It is a fast-drying, interior latex primer formulated to prime and seal new, uncoated drywall and reduce the number of topcoats required to achieve a uniform, professional quality finish.

PREPARATION:

Cover all nail and screw heads with joint compound according to directions and sand to smooth surface. Tape drywall and apply joint compound and allow to fully cure according to directions prior to priming. Sand to smooth surface before priming. Wipe off dust with a damp cloth, allow to dry thoroughly.

APPLICATION:

Eye protection is recommended. Only apply if surface, air and product temperatures are between 50°-90°F (10°-32°C). Stir thoroughly before and occasionally during use. Brush – High quality Nylon/Polyester. Roller – High quality 3/8-1/2" nap on smooth surfaces or 1/2-3/4" nap on semi-rough or porous surfaces. Airless spray – .017" - .021" tip / 60 mesh filter. Prime the entire surface to ensure a uniform appearance of the topcoat. Stainblocking: Not formulated to block stains. For stainblocking, use KILZ MAX®, KILZ® PREMIUM, KILZ® ORIGINAL, KILZ COMPLETE®, KILZ ODORLESS® or KILZ 2® Primers. Tinting: KILZ® PVA Drywall Primer may be tinted with up to 2 ounces of universal colorant per gallon. Tinting to a lighter shade than the topcoat is recommended. Coverage: 300 - 400 sq. ft. (27.87 - 37 m²) per gallon depending on application method and surface porosity. Dry Time @ 77°F (25°C) / 50% RH: Touch 30 minutes, Recoat 2 hours. Cooler temperatures and higher humidity may prolong dry time.

CLEAN-UP & DISPOSAL:

Clean equipment and paint spatters with warm, soapy water. Do not dispose of this product down a drain. Please consider donating any unused product. For recycling or disposal information contact your local household refuse collection service. If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and product in accordance with all current federal, state and local regulations. For recycling or disposal information contact your local household refuse collection service.

CAUTIONS / LIMITATIONS:

IMPORTANT! Do not open can without reading instructions. Interior use only. For use on uncoated drywall only. Do not use on floors. Do not use when air and surface temperatures are below 50°F or above 90°F. Allow 2 weeks for full cure before washing or cleaning. Do not use over glossy surfaces. Shelf life under normal conditions is two years unopened.

WARNING:

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

USE ONLY WITH ADEQUATE VENTILATION

ATTENTION! IRRITANT! HARMFUL OR FATAL IF SWALLOWED. Avoid contact with eyes. May cause eye, nose and throat irritation. Avoid breathing of dust, vapors or spray mist. Open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache, or dizziness, or if air monitoring demonstrates vapor / mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH / MSHA TC 23C or equivalent) during and after application. Follow respirator manufacturer's direction for respirator use. Close container after each use. Wash thoroughly after handling and before smoking and eating. FIRST AID: If swallowed, do not induce vomiting. Get medical attention immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush eyes immediately with plenty of water for at least 15 minutes and get medical attention.

KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY



LIMITED WARRANTY:

For one year from the date of purchase, Masterchem Industries LLC warrants to the original residential consumer purchaser (1) that the product meets Masterchem Industries LLC's manufacturing specifications, and (2) the performance of this product when applied according to the label instructions and specifications. In the event that this product proves to be defective within one year from the date of purchase, Masterchem Industries LLC will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. This warranty is not transferable. This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. To the extent permitted by applicable law, any implied warranties including the implied warranties of merchantability and of fitness for a particular purpose, are limited to the duration of this express warranty. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. Note to residents of the State of New Jersey: The provisions of this warranty, including its limitations, are intended to apply to the fullest extent permitted by the laws of the State of New Jersey. For warranty service, call: 1-866-774-6371, or email: techservice@masterchem.com. Masterchem Industries LLC reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.



©2017 Masterchem Industries LLC 1-866-774-6371 • www.kilz.com • MAX VOC 100 g/L