## **Battic Door Energy Conservation Products**

Visit us online at www.batticdoor.com

P.O. Box 15 Mansfield, MA 02048-0015 508.320.9082 voice orders@batticdoor.com www.batticdoor.com

## FIREPLACE PLUG INSTALLATION TIPS

Thank you for your purchase! We are proud that the Fireplace Plug is made in USA!

The Fireplace Plug is designed to seal your fireplace between uses, reducing energy loss and improving the comfort of your home by preventing heating and cooling from flowing up and out of your chimney. Additional benefits include the reduction of noise, odors, and pollutants from entering your home through the chimney and fireplace.

The Large Fireplace Plug will seal most any masonry fireplace. The edges curl down the sides for smaller fireplaces. Our Round Plug will fit most metal fireplaces with round dampers.

Please note that the plug is installed below the damper. It can be easily removed to use the fireplace.

Here are some tips to assist you with the installation:

- 1. Install the plug under the damper, not up inside the chimney.
- 2. Inflate the plug so it is full of air but very soft. Insert the plug and adjust the pole height so the plug is 2-3" below contact with the damper. Then tuck the front and back up and add a little more air so it seals.

Troubleshooting: If unable to achieve a good seal, try these tips:

- 1. Lower the pole to install the plug in a "V" shape not a "^" shape.
- 2. Reduce the air pressure. If you put in too much air, the plug can become stiff and create creases and gaps. The plug should seal all gaps and conform to the shape of the fireplace. A soft plug can seal around the damper well.
- 3. If damper handle is in the way, please note that it is not always necessary to make a slit to accommodate the damper handle. BEFORE MAKING A SLIT FOR THE DAMPER HANDLE, trial fit the plug. If the damper handle is in the way, open the damper to move the handle; or remove the handle temporarily. If you decide to slit the plug, use extreme caution or you will puncture the plug.

Please note that we are not able to accept a return if the plug has been cut, damaged or is dirty.

If you have any questions or require further assistance, please call or email our office.

Thank you and Regards,

Mark Tyrol, President - Battic Door Energy Conservation Products

tel. 508.320.9082 email: mark@batticdoor.com

web: www.batticdoor.com