

SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Polymer Li-ion Battery PL683086P

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use LITHIUM ION BATTERIES

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Shenzhen Power Tech international Co.,Ltd

Supplier Address No.5 Industrial Area, Shiyan Town, Shenzhen,518108
China

Supplier Phone Number Phone:+860755-27627380
Fax: +860755-27627380
Contact Phone+860755-27627380

Supplier Email zhangfan@ptiking.com

Emergency telephone number


2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Specific target organ toxicity (repeated exposure)	Category 1

GHS Label elements, including precautionary statements**Emergency Overview**

Signal word	Danger		
Hazard Statements			
Cause skin irritation			
Causes serious eye irritation			
May cause an allergic skin reaction			
			
<p>This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance. This is a battery. In case of rupture: the above hazards exist.</p>			
Appearance	Silver	Physical State	Solid
			Odor Odorless

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Contaminated work clothing should not be allowed out of the workplace
 Wear protective gloves
 Do not breathe dust/fume/gas/mist/vapors/spray
 Wear eye/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of soap and water
 Take off contaminated clothing and wash before reuse
 If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity**Other information**

Very toxic to aquatic life with long lasting effects
 Repeated or prolonged skin contact may cause allergic reactions with susceptible persons

Interactions with Other Chemicals

No information available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight %
Iron	7439-89-6	10
Aluminum	7429-90-5	10
Phosphate(1-), hexafluoro-, lithium	21324-40-3	24
Polyethylene	9002-88-4	0.8
Polypropylene	9003-07-0	0.8
Copper	7440-50-8	7.2
Styrene-Butadiene polymer	9003-55-8	4.8
Cellulose, carboxymethyl ether	9000-11-7	2.4
Aluminum foil	7429-90-5	3.2
1,1-Difluoroethylene polymer	24937-79-9	0.8
Carbon	7440-44-0	0.4
Graphite	7782-42-5	11.6
Lithium Cobalt Oxide (CoLiO ₂)	12190-79-3	24

4. FIRST AID MEASURES

First aid measures

General Advice

First aid is upon rupture of sealed battery. Show this safety data sheet to the doctor in attendance

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Do not rub affected area

Skin Contact

Wash off immediately with soap and plenty of water for at least 15 minutes. In the case of skin irritation or allergic reactions see a physician. May cause an allergic skin reaction.

Inhalation

Remove to fresh air. If symptoms persist, call a physician. Get medical attention immediately if symptoms occur.

Ingestion

Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician.

Self-protection of the first aider

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8)

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects

Burning sensation. Coughing and/ or wheezing. Difficulty in breathing. Itching. Rashes. Hives.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

May cause sensitization of susceptible persons. Treat symptomatically

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

CAUTION: Use of water spray when fighting fire may be inefficient

Specific Hazards Arising from the Chemical

Product is or contains a sensitizer. May cause sensitization by skin contact.

Hazardous Combustion Products

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand,MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal. protective equipment as required. Evacuate personnel to safe areas.

Other Information Refer to protective measures listed in Sections 7 and 8

Environmental Precautions

Environmental Precautions Refer to protective measures listed in Sections 7 and 8.

Methods for cleaning up Pick up and transfer to properly labeled containers

Methods for Containment Prevent further leakage or spillage if safe to do so.
Methods for cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling In case of rupture. Use personal protection equipment. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible Products Strong acids. Strong oxidizing agents. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lithium Cobalt Oxide	TWA: 0.02 mg/m ³		

12190-79-3			
Graphite 7782-42-5	TWA: 2 mg/m ³ respirable fraction all forms except graphite fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ respirable dust
Copper 7440-50-8	TWA: 0.2 mg/m ³ fume TWA: 1 mg/ mg/m ³ Cu dust and mist	TWA: 0.1 mg/m ³ fume TWA: 1 mg/m ³ dust and mist (vacated) TWA: 0.1 mg/m ³ Cu dust, fume, mist	IDLH: 100 mg/m ³ dust, fume and mist TWA: 1 mg/m ³ dust and mist TWA: 0.1 mg/m ³ fume
Aluminum foil 7429-90-5	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ Al Aluminum	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Aluminum 7429-90-5	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ Al Aluminum	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³ F TWA: 2.5 mg/m ³ dust (vacated) TWA: 2.5 mg/m ³	

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection If splashes are likely to occur: Wear safety glasses with side shields (or goggles). None required for consumer use.

Skin and Body Protection Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State	Solid	Odor	Odorless
Appearance	Silver	Odor Threshold	No information available
Color	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks/ Method</u>
pH	No data available	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	No data available	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	0.00001	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	0.00001	None known
Explosive properties	No data available	
Oxidizing Properties	No data available	

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

None known based on information supplied.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	Product does not present an acute toxicity hazard based on known or supplied information In case of rupture
Inhalation	Specific test data for the substance or mixture is not available. Corrosive by inhalation.(based on components).
Eye Contact	Specific test data for the substance or mixture is not available. Expected to be and irritant based on components. Irritating to eyes. May cause redness, itching, and pain. May cause temporary eye irritation.
Skin Contact	Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to skin. Prolonged contact may cause redness and irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be harmful if swallowed. (based on components).

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Graphite 7782-42-5	> 10000 mg/kg (Rat)	-	-
Iron 7439-89-6	= 984 mg/kg (Rat)		

Information on toxicological effects

Symptoms Erythema (skin redness). May cause redness and tearing of the eyes. Coughing and/ or wheezing.Itching. Rashes Hives.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause sensitization of susceptible persons. May cause sensitization by skin contact. May cause sensitization by inhalation.

Mutagenic Effects No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen

Chemical Name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	A3	Group 2B		X

ACGIH (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen

A3 - Animal Carcinogen
IARC (International Agency for Research on Cancer)
 Group 1 - Carcinogenic to Humans
 Group 2B - Possibly Carcinogenic to Humans
NTP (National Toxicology Program)
 Known - Known Carcinogen
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
 X- Present

Reproductive Toxicity	Contains a known or suspected reproductive toxin
STOT - single exposure	No information available.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).
Chronic Toxicity	No known effect based on information supplied. Contains a known or suspected carcinogen. Contains a known or suspected reproductive toxin. Possible risk of irreversible effects. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse effects on the bone marrow and blood-forming system. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. May cause adverse liver effects.
Target Organ Effects	Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Reproductive System. Blood. Central Nervous System (CNS). Central Vascular System (CVS). Kidney. Lungs. Nasal cavities. Cardiovascular system. Systemic Toxicity. Liver.
Aspiration Hazard	No information available.

Numerical measures of toxicity Product Information
 The following values are calculated based on chapter 3.1 of the GHS document
 ATEmix (oral)
 ATEmix (dermal)
 ATEmix (inhalation-dust/mist)

12. ECOLOGICAL INFORMATION

Ecotoxicity
 Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Copper 7440-50-8	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas)		48h EC50: = 0.03 mg/L
Iron 7439-89-6		96h LC50: = 13.6 mg/L (Morone saxatilis)		

Persistence and Degradability
 No information available.

Bioaccumulation

No information available

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods

Should not be released into the environment.

Contaminated Packaging

Dispose of in accordance with federal, state and local regulations.

California Hazardous Waste Codes 141

Chemical Name	California Hazardous Waste
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	Toxic
Aluminum foil 7429-90-5	Ignitable powder
Aluminum 7429-90-5	Ignitable powder
Copper 7440-50-8	Toxic

14. TRANSPORT INFORMATION

Note:

The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule) Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

DOT	NOT REGULATED
Proper Shipping Name	NON REGULATED
Hazard Class	N/A
TDG	Not regulated
MEX	Not regulated
ICAO	Not regulated
IATA	Not regulated
Proper Shipping Name	Not regulated
Hazard Class	N/A
IMDG/IMO	Not regulated
Proper Shipping Name	NON-REGULATED PER SP 188
Hazard Class	N/A
EmS No.	F-A, S-I
RID	Not regulated
ADR	Not regulated
AND	Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL All components are listed either on the DSL or NDSL.
 TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Lithium Cobalt Oxide (CoLiO ₂)	12190-79-3	24	0.1
Aluminum foil	7429-90-5	3.2	1.0
Aluminum	7429-90-5	10	1.0
Copper	7440-50-8	7.2	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard No
 Chronic Health Hazard No
 Fire Hazard No
 Sudden release of pressure hazard No
 Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper 7440-50-8		X	X	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Aluminum foil 7429-90-5			

US State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Lithium Cobalt Oxide (CoLiO ₂) 12190-79-3	X		X	X	X
Graphite 7782-42-5	X	X	X		
Carbon 7440-44-0			X		
Copper 7440-50-8	X	X	X	X	X
Aluminum foil 7429-90-5		X		X	
Aluminum 7429-90-5	X	X	X	X	

International Regulations**Mexico****National occupational exposure limits**

Component	Carcinogen Status	Exposure Limits
Graphite 7782-42-5 (11.6%)		Mexico: TWA= 2 mg/m ³
Copper 7440-50-8 (7.2%)		Mexico: TWA= 1 mg/m ³ Mexico: TWA= 0.2 mg/m ³ Mexico: STEL= 2 mg/m ³
Aluminum foil 7429-90-5 (3.2%)		Mexico: TWA= 10 mg/m ³
Aluminum 7429-90-5 (10%)		Mexico: TWA= 10 mg/m ³

*Mexico - Occupational Exposure Limits - Carcinogens***Canada****WHMIS Hazard Class**

Non-controlled

16. OTHER INFORMATION

NFPA	Health Hazards 1	Flammability 0	Instability 0	Physical and Chemical Hazards - Personal Protection X
HMIS	Health Hazards 0	Flammability 0	Physical Hazard 0	

Prepared By Shenzhen Power Tech international Co.,Ltd**Issuing Date****Revision Date**

06-Mar-2015

Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet