



WATCO® SATIN WAX

DESCRIPTION AND USES

WATCO® Satin Wax is a liquid solvent-based wax that leaves a rich, soft satin luster while providing an additional level of protection and water resistance to oil-finished or bare woods. Use WATCO Natural Satin Wax for light-colored woods and the Dark Stain Wax for dark-colored woods, or mix them for a medium toned wax. Satin Wax is recommended is suitable for use on furniture, trim, paneling, or any interior bare or oil-finished wood surface. It is NOT recommended for floors or exterior surfaces.

PRODUCTS

1-Quart	1-Pint	Description
66941	66951	Dark Stain Wax
67041	67051	Natural Stain Wax

PRODUCT APPLICATION

SURFACE PREPARATION

Allow any previously applied oil or stain on wood surface to dry 72 hours before applying WATCO Satin Wax for Finishing.

For unfinished bare wood surfaces, sand using 150-220 grit sandpaper and remove all sanding dust with a vacuum or a rag dampened with mineral spirits. If a filler or putty is used, make sure it does not contain wax and allow for enough time to dry thoroughly.

WARNING! If you scrape, sand or remove old paint, you may Release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

Use only when air (ambient) temperature is between 60-90°F (16-32°C) and relative humidity is below 85%. Allow for longer dry times during damp and humid conditions. Mix material thoroughly before application. Stir occasionally during use. Spread a thin, even coat of WATCO Satin Wax with a clean cloth. Wait 10 minutes, wipe clean and dry. Polish with a soft cloth.

MAINTENANCE

Periodically apply additional coats of WATCO Satin Wax as needed, buffing with a soft cloth. For additional luster, reapply WATCO Satin Wax and wet sand surface lightly with 600-grit wet/dry sandpaper. Sand in the direction of the wood grain. After 10 minutes wipe clean and dry, then polish with a soft cloth.

NOTE: Do not apply surface finishes such as polyurethane over wax. If a clear wood finish such as polyurethane is desired, completely remove wax with a wax stripper, following product directions, and allow wood surface to dry for 72 hours before applying Varathane® Interior Premium Polyurethane.

CLEAN UP

Application tools or brushes should be cleaned with mineral spirits or paint thinner.

**TECHNICAL DATA****WAT-03****WATCO® SATIN WAX****PHYSICAL PROPERTIES**

		WATCO SATIN WAX
Resin Type		Hydrocarbon Wax
Pigment Type		None
Solvents		Light petroleum distillate
Weight	Per Gallon	6.7 lbs.
	Per Liter	0.8 kg.
Solids%	By Weight	7.5-10.9%
	By Volume	6.6-9.3%
Volatile Organic Compounds		722-744g/l
Recommended Dry Film Thickness (DFT) Per Coat		NA
Wet Film to Achieve DFT (unthinned material)		NA
Theoretical Coverage at 1 mil DFT (25µ)		150 sq.ft./gal.
Practical Coverage at Recommended DFT (assumes 15% material loss)		Varies with type and porosity of wood.
Dry Times at 77°F (25°C) and 50% Relative Humidity	Touch	30 minutes
	Handle	30 minutes
	Recoat	72 hours
Shelf Life		3 years
Flash Point		>93°F (34°C)
Safety Information		see MSDS for information

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.