

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®
SPECIALTY

GLITTER SPRAYS

DESCRIPTION AND USES

Glitter Sprays are designed to provide a sparkle finish on many surfaces including wood, metal, wicker, ceramic, pottery, Styrofoam® paper, plastic, and more. For added protection, top coat with Rust-Oleum® Glitter Sealer. The clear topcoat helps prevent Glitter from flaking and fading while maintaining the sparkle finish. For use on interior items only.

PRODUCTS

267689	Glitter Gold
267734	Glitter Silver
268045	Glitter Red
267736	Glitter Clear Sealer
276287	Glitter Bright Pink
277781	Glitter Kelly Green
278073	Multicolor Glitter Purple

PAINTING CONDITIONS

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Do not apply to surfaces that, when heated, exceed 200°F (93°C). Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

PRIMING

Use of a Painter's Touch® primer provides excellent adhesion and hiding and is especially recommended for bare wood and metal. A primer, however, is not recommended for Styrofoam® and paper. The following primers are recommended.

249086	Red Primer
249088	Gray Primer
249058	White Primer

PRODUCT APPLICATION

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces to create a surface profile. **WARNING!** If you scrape, sand or remove old paint from any surface, you may release lead paint dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle **DO NOT STRIKE CAN**. Contact Rust-Oleum. Shake often during use. Hold can upright 12-14" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply two or more light coats a few minutes apart. **Do not use near open flame.**

DRY & RECOAT

Dry and recoat times are based on 70°F and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 20 minutes, to handle in 1 hour, and fully dry in 24 hours. Recoat at anytime.

CLEAN-UP

When finished spraying, clear valve by turning can upside down and pushing spray button for 5 seconds. Clean-up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

* Styrofoam® is a trademark of the Dow Chemical Company.

TECHNICAL DATA

GLITTER SPRAYS

PHYSICAL PROPERTIES

Physical Properties	Finishes
Resin Type	Acrylic
Pigment Type	Glitter Flake
MIR	1.20 Max
Fill Weight	10.25 ounces
Solvents	Naphtha, Hexane
Practical Coverage at Recommended DFT (assumes 15% material loss)	3-5 sq.ft./can (Colors) 6-10 sq.ft./can (Clear)
Dry Times at 77°F (25°C) and 50% Relative Humidity	
Touch	20 minutes
Handle	1 hour
Recoat	Anytime
Shelf Life	5 years
Flash Point	NA
Safety Information	For additional information, see MSDS.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.