

Version number 5 Reviewed on 05/18/2015

1 Identification

· Product identifier

• Trade name: B 18 / 5.2 Li-Ion B 22 / 5.2 Li-Ion B 36 / 3.0 Li-Ion B 36 / 3.3 Li-Ion

B 36 / 3.9 Li-Ion **B** 36 / 6.0 Li-Ion

B 7 / 1.5 Li-Ion B 12 / 2.6 Li-Ion B 14 / 1.6 Li-Ion B 14 / 3.3 Li-Ion B 18 / 2.6 Li-Ion B 18 / 1.6 Li-Ion B 18 / 3.3 Li-Ion B 22 / 1.6 Li-Ion B 22 / 2.6 Li-Ion B 22 / 3.3 Li-Ion B 36 / 2.4 Li-Ion B 36 / 2.6 Li-Ion B 144 / 2.6 Li-Ion POA 80 **POA 84** POA90 **PRA 84** PRA 84 02

PRA 84 G PSA 81 PSA 82 AI E20 AI E21

· Relevant identified uses of the substance or mixture and uses advised against

· Article category AC3 Electrical batteries and accumulators

 $\cdot \ \textbf{Application of the substance / the mixture} \ \text{Rechargeable Lithium Ion battery for power tools}$

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Hilti, Inc.

5400 South 122nd East Ave.

US-Tulsa, OK 74146 Phone: (800) 879-8000 Fax: (800) 879-7000

Español: (800) 879-5000

· Information department: see section 16

· Emergency telephone number:

Chem-Trec

Tel.: 1 800 424 9300 (USA, PR, Virgin Islands, Canada)

Tel.: 703 527 3887 (Other countries)

2 Hazard(s) identification

· Classification of the substance or mixture

The product is not classified according to the Globally Harmonized System (GHS).

· Additional information:

For the battery chemical materials are stored in a hermetically sealed metal case, designed to withstand temperatures and pressures encountered during normal use. As a result, during normal use there is no physical danger of ignition or explosion and chemical danger of hazardous materials leakage.

It may cause heat generation or electrolite leakage if battery terminals contact with other metals. Elektrolyte is flammable. In case of electrolyte leakage move the battery from fire immediately.

However if exposed to a fire, added mechanical shocks, decomposed, added electric stress by miss-use, the gas release vent will be operated. The battery case will be breaked at the extreme, hazardous materials may be released.

Moreover, if heated strongly by a surrounding fire, acrid gas may be emitted.

- · Label elements
- · GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Classification system
- · NFPA ratings (scale 0-4)



 $\begin{aligned} & \text{Health} = 2 \\ & \text{Fire} = 0 \\ & \text{Reactivity} = 0 \end{aligned}$

- · Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

US EN



Printing date 05/18/2015 Version number 5 Reviewed on 05/18/2015

Trade name: B 18 / 5.2 Li-Ion B 22 / 5.2 Li-Ion B 36 / 3.0 Li-Ion B 36 / 3.3 Li-Ion B 36 / 3.9 Li-Ion B 36 / 6.0 Li-Ion B 7 / 1.5 Li-Ion B 12 / 2.6 Li-Ion B 14 / 1.6 Li-Ion B 14 / 3.3 Li-Ion B 18 / 1.6 Li-Ion B 18 / 2.6 Li-Ion B 18 / 3.3 Li-Ion B 22 / 1.6 Li-Ion B 22 / 2.6 Li-Ion B 22 / 3.3 Li-Ion B 36 / 2.4 Li-Ion B 36 / 2.6 Li-Ion B 144 / 2.6 Li-Ion POA 80 POA 84 POA 90 **PRA 84** PRA 84 02 **PRA 84 G PSA 81 PSA 82 AI E20 AI E21**

(Contd. of page 1)

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description:

Lithium Ion rechercheable battery pack:

Name/Type	Lithiumequivalent (g)	Energy content (Wh)
Hilti B 18 / 5.2 Li-Ion		112,4
Hilti B 22 / 5.2 Li-Ion	9,4	112,4
Hilti B 36 / 3.0 Li-Ion	9,0	108
Hilti B 36 / 3.3 Li-Ion	9,9	118,8
Hilti B 36 / 3.9 Li-Ion	11,7	140
Hilti B 36 / 6.0 Li-Ion	18,0	216
B 7 / 1.5 Li-Ion	0,9	10,8
B 12 / 2.6 Li-Ion	2,34	28,1
B 14 / 1.6 Li-Ion	1,92	23
B 14 / 3.3 Li-Ion	3,84	46
B 18 / 1.6 Li-Ion	2,88	35
B 18 / 2.6 Li-Ion	4,68	56,16
B 18 / 3.3 Li-Ion	5,94	71,3
B 22 / 1.6 Li-Ion	2,88	35
B 22 / 2.6 Li-Ion	4,68	56,16
B 22 / 3.3 Li-Ion	5,94	71,3
B 36 / 2.6 Li-Ion	7,8	94
B 36 / 2.4 Li-Ion	7,2	86,4
B 144 / 2.6 Li-Ion	3,12	37,44
POA 80	2	19,8
POA 84	4	55
POA 90		45
PRA 84	4	33,0
PRA 84 02	4	37,0
PRA 84 G	4	44,0
PSA 81	4	37
PSA 82	4	36
AI E20	2	8
AI E21	2	16

\cdot Dangerous components:

This product contains a positive electrode (Lithium cobalt oxide), a negative electrode (graphite) and electrolyte (ethylene carbonate, diethyl carbonate and lithium hexafluorophosphate). The physical form of the product, however, precludes exposure to workers under normal conditions of use.

1307-96-6	cobalt oxide	<30%
1313-13-9	manganese dioxide	<30%
1313-99-1	nickel monoxide	<30%
7440-44-0	carbon	<30%
	Electrolyte; main ingredients: Lithium hexaflourophospate, organic carbonates	<20%
24937-79-9	Polyvinylidene fluoride (PVdF)	<10%
7429-90-5	Aluminium foil	2-10%
7440-50-8	Copper foil	2-10%

• Additional information For the wording of the listed risk phrases refer to section 16.

- US EN



Printing date 05/18/2015 Version number 5 Reviewed on 05/18/2015

B 22 / 5.2 Li-Ion B 36 / 3.0 Li-Ion B 36 / 3.3 Li-Ion Trade name: B 18 / 5.2 Li-Ion B 36 / 3.9 Li-Ion B 36 / 6.0 Li-Ion B 7 / 1.5 Li-Ion B 12 / 2.6 Li-Ion B 14 / 3.3 Li-Ion B 14 / 1.6 Li-Ion B 18 / 1.6 Li-Ion B 18 / 2.6 Li-Ion B 18 / 3.3 Li-Ion B 22 / 1.6 Li-Ion B 22 / 3.3 Li-Ion B 36 / 2.4 Li-Ion B 36 / 2.6 Li-Ion B 22 / 2.6 Li-Ion B 144 / 2.6 Li-Ion POA 80 POA 84 POA 90 PRA 84 PRA 84 02 PRA 84 G PSA 81 PSA 82 AI E20 **AI E21**

(Contd. of page 2)

4 First-aid measures

- · Description of first aid measures
- · General information

This product contains an organic electrolyte. If the electrolyte is leaking out of the battery pack, the following measures have to be taken.

· After inhalation

Take affected persons into fresh air and keep quiet.

Supply fresh air or oxygen; call for doctor.

- · After skin contact Immediately wash with water and soap and rinse thoroughly.
- · After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing Seek immediate medical advice.
- · Information for doctor
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents

CO2, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam.

Foam

· Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Ensure adequate ventilation

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources

Keep people at a distance and stay upwind.

- Environmental precautions: Do not allow to penetrate the ground/soil.
- \cdot Methods and material for containment and cleaning up:

Pick up mechanically.

Absorb liquid components with liquid-binding material.

· Reference to other sections See Section 7 for information on safe handling

7 Handling and storage

- $\cdot \ Handling$
- $\cdot \ Precautions \ for \ safe \ handling$

Do not soak in water or seawater.

Do not expose to strong oxidizers.

Do not give a strong mechanical shock or fling.

Never disassemble, modify or deform.

Do not connect the positive terminal to the negative terminal with electrically conductive material.

Use only the chargers / electric tools specified by Hilti to charge or discharge the battery.

No special measures required.

(Contd. on page 4)



Printing date 05/18/2015 Version number 5 Reviewed on 05/18/2015

B 22 / 5.2 Li-Ion B 36 / 3.0 Li-Ion B 36 / 3.3 Li-Ion Trade name: B 18 / 5.2 Li-Ion B 36 / 3.9 Li-Ion B 36 / 6.0 Li-Ion B 7 / 1.5 Li-Ion B 12 / 2.6 Li-Ion B 14 / 3.3 Li-Ion B 14 / 1.6 Li-Ion B 18 / 3.3 Li-Ion B 22 / 1.6 Li-Ion B 18 / 1.6 Li-Ion B 18 / 2.6 Li-Ion B 36 / 2.6 Li-Ion B 22 / 2.6 Li-Ion B 22 / 3.3 Li-Ion B 36 / 2.4 Li-Ion B 144 / 2.6 Li-Ion POA 80 POA 84 POA 90 PRA 84 PRA 84 02 **PRA 84 G PSA 81 PSA 82** AI E20 **AI E21**

(Contd. of page 3)

· Information about protection against explosions and fires:

Do not throw into fire or expose to high temperatures (>85 °C).

Do not connect the positive terminal to the negative terminal with electrically conductive material.

- · Conditions for safe storage, including any incompatibilities
- ·Storage
- · Requirements to be met by storerooms and receptacles:

Avoid direct sunlight, high temperature, high humidity.

Store in a cool place (temperature: -20 °C ~ 35 °C, humidity: 45 - 85%)

· Information about storage in one common storage facility:

Store away from water.

Do not store together with electrically conductive materials.

· Further information about storage conditions:

The accu-pack should be stored at 30 to 50% of the charging capacity.

Avoid storing in places where it is exposed to static electricity.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

No technical measures are necessary during normal use. In case of leakage of substances contained within the cell, the information below may be useful.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment
- · General protective and hygienic measures The usual precautionary measures for handling chemicals should be followed.
- · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves.

EN 374

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.12 mm

- Penetration time of glove material Value for the permeation: Level 6 (> 480 min)
- · Eye protection:



Tightly sealed goggles.

(Contd. on page 5)



Printing date 05/18/2015 Version number 5 Reviewed on 05/18/2015

B 36 / 3.0 Li-Ion B 22 / 5.2 Li-Ion B 36 / 3.3 Li-Ion Trade name: B 18 / 5.2 Li-Ion B 36 / 3.9 Li-Ion B 36 / 6.0 Li-Ion B 7 / 1.5 Li-Ion B 12 / 2.6 Li-Ion B 14 / 1.6 Li-Ion B 14 / 3.3 Li-Ion B 22 / 1.6 Li-Ion B 18 / 1.6 Li-Ion B 18 / 2.6 Li-Ion B 18 / 3.3 Li-Ion B 36 / 2.4 Li-Ion B 36 / 2.6 Li-Ion B 22 / 2.6 Li-Ion B 22 / 3.3 Li-Ion B 144 / 2.6 Li-Ion POA 80 POA 84 POA 90 PRA 84 PRA 84 02 **PSA 81 AI E20 AI E21 PRA 84 G PSA 82**

(Contd. of page 4)

· Body protection:



Protective work clothing.

9 Physical and chemical properties

 \cdot Information on basic physical and chemical properties

· General Information

· Appearance:

Form: plastic case
Color: Black / Red
Odor: Odorless
Odour threshold: Not determined

• pH-value: Not applicable

· Change in condition

Melting point/Melting range: Not applicable Boiling point/Boiling range: Not applicable

Flash point: Not applicable

· Flammability (solid, gaseous) Not applicable

• Ignition temperature: Not applicable

· **Decomposition temperature:** Not applicable

· **Auto igniting:** Product is not selfigniting.

• **Danger of explosion:** Risk of explosion by shock, friction, fire or other sources of ignition.

· Explosion limits:

Lower: Not applicable
Upper: Not applicable
Oxidizing properties Not applicable

· Vapor pressure: Not applicable

Density: Not applicable
Relative density Not applicable
Vapour density Not applicable
Evaporation rate Not applicable

· Solubility in / Miscibility with

Water: Not applicable

 $\cdot \ Viscosity:$

kinematic:

dynamic: Not applicable. Not applicable

Not applicable. Not applicable

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 6)



Printing date 05/18/2015 Version number 5 Reviewed on 05/18/2015

B 22 / 5.2 Li-Ion B 36 / 3.0 Li-Ion B 36 / 3.3 Li-Ion Trade name: B 18 / 5.2 Li-Ion B 36 / 3.9 Li-Ion B 36 / 6.0 Li-Ion B 7 / 1.5 Li-Ion B 12 / 2.6 Li-Ion B 14 / 3.3 Li-Ion B 14 / 1.6 Li-Ion B 18 / 3.3 Li-Ion B 22 / 1.6 Li-Ion B 18 / 1.6 Li-Ion B 18 / 2.6 Li-Ion B 36 / 2.6 Li-Ion B 22 / 2.6 Li-Ion B 22 / 3.3 Li-Ion B 36 / 2.4 Li-Ion B 144 / 2.6 Li-Ion POA 80 POA 84 POA 90 PRA 84 PRA 84 02 **PRA 84 G PSA 81 PSA 82 AI E20 AI E21**

(Contd. of page 5)

- · Possibility of hazardous reactions No dangerous reactions known
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Conductive materials, water, seawater, strong oxidizers and strong acids.
- · Hazardous decomposition products: Acrid or harmful gas is emitted during fire

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin:

This product contains an organic electrolyte. <u>If the electrolyte is leaking out of the battery pack, the following effects are known when getting into contact:</u>

Irritant to skin and mucous membranes.

- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

- · Carcinogenic categories
- · NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow battery packs to penetrate the soil.

The battery cell may corrode and electrolyte may leak.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Dispose of this battery pack according to national regulations or return the used battery pack to Hilti. Smaller quantities can be disposed of with household waste.

· Europea	n waste catalogue:
16 06 05	other batteries and accumulators
20 01 34	batteries and accumulators other than those mentioned in 20 01 33

(Contd. on page 7)



Printing date 05/18/2015 Version number 5 Reviewed on 05/18/2015

B 22 / 5.2 Li-Ion B 36 / 3.0 Li-Ion B 36 / 3.3 Li-Ion Trade name: B 18 / 5.2 Li-Ion B 36 / 3.9 Li-Ion B 36 / 6.0 Li-Ion B 7 / 1.5 Li-Ion B 12 / 2.6 Li-Ion B 14 / 1.6 Li-Ion B 14 / 3.3 Li-Ion B 18 / 3.3 Li-Ion B 22 / 1.6 Li-Ion B 18 / 1.6 Li-Ion B 18 / 2.6 Li-Ion B 36 / 2.6 Li-Ion B 22 / 2.6 Li-Ion B 22 / 3.3 Li-Ion B 36 / 2.4 Li-Ion B 144 / 2.6 Li-Ion POA 80 POA 84 POA 90 PRA 84 PRA 84 02 PRA 84 G PSA 81 **AI E20 AI E21 PSA 82**

(Contd. of page 6)

- · Uncleaned packagings:
- · **Recommendation:** Dispose of packaging according to regulations on the disposal of packagings.

4 Transport information	
· UN-Number · DOT, ADR, IMDG, IATA	UN3480
· UN proper shipping name · DOT, IMDG, IATA · ADR	LITHIUM ION BATTERIES UN3480 LITHIUM ION BATTERIES
· Transport hazard class(es)	
· DOT, ADR, IMDG, IATA · Class	9 Miscellaneous dangerous substances and articles
· Packing group · DOT, ADR, IMDG, IATA	Void
· Environmental hazards:	Not applicable.
· Special precautions for user · EMS Number:	Warning: Miscellaneous dangerous substances and articles F-A,S-I
· Transport in bulk according to Annex I MARPOL73/78 and the IBC Code	II of Not applicable.
· Transport/Additional information:	Lithium-ion batteries are tested in accordance with: UN manual of Tests and Criteria, Part III, subsection 38.3
· UN "Model Regulation":	UN3480, LITHIUM ION BATTERIES, 9

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

٠	Section	355	(Extreme	ly	hazaro	lous	subs	tances)):
---	---------	-----	----------	----	--------	------	------	---------	----

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65:

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

(Contd. on page 8)



Printing date 05/18/2015 Version number 5 Reviewed on 05/18/2015

B 22 / 5.2 Li-Ion B 36 / 3.0 Li-Ion B 36 / 3.3 Li-Ion Trade name: B 18 / 5.2 Li-Ion B 36 / 3.9 Li-Ion B 36 / 6.0 Li-Ion B 7 / 1.5 Li-Ion B 12 / 2.6 Li-Ion B 14 / 1.6 Li-Ion B 14 / 3.3 Li-Ion B 18 / 1.6 Li-Ion B 18 / 2.6 Li-Ion B 18 / 3.3 Li-Ion B 22 / 1.6 Li-Ion B 36 / 2.4 Li-Ion B 36 / 2.6 Li-Ion B 22 / 2.6 Li-Ion B 22 / 3.3 Li-Ion B 144 / 2.6 Li-Ion POA 80 POA 84 POA 90 PRA 84 PRA 84 02 **PRA 84 G PSA 81 PSA 82 AI E20 AI E21**

(Contd. of page 7)

· Chemical safety assessment: not required.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS:

Hilti Entwicklungsgesellschaft mbH

Hiltistrasse 6

D-86916 Kaufering Tel.: +49 8191 906310 Fax: +49 8191 90176310 e-mail: anchor.hse@hilti.com · Contact: Mechthild Krauter

· Date of preparation / last revision 05/18/2015 / 4

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

· * Data compared to the previous version altered.