

FOILMASTIC® SEALANT TAPE

UL LISTED TAPE



Backing: Printed Aluminum Foil
Adhesive: Butyl Rubber
Liner: PE Film
Specifications: UL 181B-FX Listed
Colors: Aluminum
Available Size: 1.89 in x 33.9 yd
 (48 mm x 31 m)

Applications

- Verified by SMACNA Testing & Research Institute for sealing rigid sheet metal ducts
- Cleaner alternative to mastic putty process
- Indoor/Outdoor sealing of low, medium, and high pressure HVAC systems including UL Listed non-metallic flexible duct

Features

Benefits

UL 181B-FX Listed

- Meets code requirements for sealing UL-Listed non-metallic flexible duct connections
- Can contribute toward satisfying EA Credit 1 (Optimize Energy Performance) under LEED®

Butyl Rubber Adhesive

- Permanent air and water-tight bond
- Repositionable for several minutes for easy installation
- Resists mold and mildew growth

Aluminum Foil Backing

- Thick and durable
- Conforms securely around duct and corners
- 181B-FX printed for easy inspector identification

Low VOC Content

- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	17 mils	432 µm	ASTM D-1000
Adhesion to Steel	90 oz/in	9.85 N/cm	PSTC-101
Tensile Strength	23 lb/in	40.28 N/cm	ASTM D-1000
Operating Temperature	-20 to 200 °F	-29 to 93 °C	
VOC Content	< 1 g/L		
Recommended Storage Conditions: 60 - 80 °F at 40-60% RH			
Standard Shelf Life (at 25 °C): 36 months from date of manufacture			

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.