

# 80™ / 180™ Series Regular-Duty Standard and Bracket System

## 79 Series Easy Installation Hang Rail

**Dimensions:** 2" tall x 1/2" deep  
**Material:** Hardened steel  
**Finish:** Titanium (TI), White (WH)  
**Features:** Holds up to 2,700 lbs. per 80" hang rail, and up to 1,700 lbs. per 48" hang rail; rail has screw holes every 8" for mounting to 16" and 24" stud centers; rigid profile design prevents twisting and bowing; mounts to most wall types and bare studs; anti-dislodge safety features

## 7980 Standard Links

**Dimensions:** 6-5/8" tall x 3/4" wide x 4/5" deep  
**Material:** Cast aluminum  
**Finish:** Titanium (TI), White (WH)  
**Features:** Holds up to 200 lbs. per standard link; sleek design for a clean look; mounting screws included


### Pack Configurations

Standard	10 per carton	
<b>79 Series Easy Installation Hang Rail</b>		
<b>Size</b>	<b>Titanium (TI)</b>	<b>White (WH)</b>
48"	79 TI 48	79 WH 48
80"	79 TI 80	79 WH 80

### Pack Configurations

Standard	12 pairs per carton, with screws	
<b>7980 Series Standard Links</b>		
<b>Titanium (TI)</b>	<b>White (WH)</b>	
7980 TI	7980 WH	

WH



TI



TI



WH



## Accessories

**Packed:** 100 per carton

- 101 PLAS: Clear plastic back rest with divider
- 102 PLAS: Clear plastic front rest with divider
- 103 PLAS: Clear plastic front rest
- 103-1/2L PLAS: Clear plastic front rest left
- 103-1/2R PLAS: Clear plastic front rest right
- 104 ANO: Anochrome (ANO) steel back rest
- 104 PLAS: Clear plastic back rest
- 104-1/2 ANO: Anochrome (ANO) steel back rest
- 104-1/2 PLAS: Clear plastic back rest
- 119 RUB: Gray rubber cushion use with metal rests
- 129 RUB: Gray rubber cushion use with plastic rests
- 136 ANO: Socket-#80 standard bottom socket
- 137 ANO: Socket-#80 standard top socket
- 153 ANO: Standard fastener floor mount (bolt and nut not included)
- 154 ANO: Shelf-fastener (fastens shelf to bracket)

