


# MATERIAL SAFETY DATA SHEET

## Klean-Strip Acetone

Page: 1



HEALTH		1
FLAMMABILITY		3
PHYSICAL		0
PPE		



Printed: 09/22/2011  
Revision: 04/14/2009  
Supersedes Revision: 11/13/2008

### 1. Product and Company Identification

**Product Code:** 1640.1  
**Product Name:** Klean-Strip Acetone  
**Reference #:** 1640.1

**Manufacturer Information**

**Company Name:** W. M. Barr  
2105 Channel Avenue  
Memphis, TN 38113

**Phone Number:** (901)775-0100

**Emergency Contact:** 3E 24 Hour Emergency Contact (800)451-8346

**Information:** W.M. Barr Customer Service (800)398-3892

**Web site address:** www.wmbarr.com

**Preparer Name:** W.M. Barr EHS Department (901)775-0100

#### Synonyms

CAC18, DAC18, GAC18, GAC718, QAC18, QAC18L, QAC718, QAC18L

### 2. Composition/Information on Ingredients

Hazardous Components (Chemical Name)	CAS #	Concentration	OSHA PEL	ACGIH TWA	Other Limits
1. Acetone {2-Propanone}	67-64-1	100.0 %	1000 ppm	500 ppm	No data.

Hazardous Components (Chemical Name)	CAS #	OSHA STEL	OSHA CEIL	ACGIH STEL	ACGIH CEIL
1. Acetone {2-Propanone}	67-64-1	No data.	No data.	750 ppm	No data.

### 3. Hazards Identification

#### Emergency Overview

Danger! Extremely Flammable. Keep away from heat, sparks, flame and all other sources of ignition. Vapors may cause flash fire or ignite explosively. Vapors may travel long distances to other areas and rooms away from the work site. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and all other sources of ignition anywhere in the structure, dwelling, or building during use and until all vapors are gone from the work site. Keep away from electrical outlets and switches. Beware of static electricity that may be generated by synthetic clothing and other sources.

#### Potential Health Effects (Acute and Chronic)

Inhalation Acute Exposure Effects:

Vapor harmful. May cause dizziness, headache, watering of eyes, irritation of respiratory tract, drowsiness, nausea, and numbness in fingers, arms and legs.

Skin Contact Acute Exposure Effects:

May cause drying of skin, and numbness in fingers and arms. Liquid is absorbed readily.

Eye Contact Acute Exposure Effects:

This material is an eye irritant.

Ingestion Acute Exposure Effects:

Harmful if swallowed. May cause dizziness, headache, nausea, and irritation of the mouth, throat, and stomach.

# MATERIAL SAFETY DATA SHEET

## Klean-Strip Acetone

Page: 2

Printed: 09/22/2011

Revision: 04/14/2009

Supersedes Revision: 11/13/2008

### Chronic Exposure Effects:

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. May cause weakness, fatigue, skin irritation, and numbness in hands and feet.

### Signs and Symptoms Of Exposure

#### Primary Routes of Exposure:

Inhalation, ingestion, and dermal.

### Medical Conditions Generally Aggravated By Exposure

Skin, eye, lung (asthma-like conditions)

### OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

## 4. First Aid Measures

### Emergency and First Aid Procedures

#### Inhalation:

If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be reached.

#### Skin Contact:

Wash with soap and water.

#### Eye Contact:

Flush with large quantities of water for at least 15 minutes and seek immediate medical attention.

#### Ingestion:

Call your poison control center, hospital emergency room, or physician immediately for instructions.

### Note to Physician

Call your local poison control center for further instructions.

## 5. Fire Fighting Measures

### Flammability Classification:

Class IB

### Flash Pt:

-4.0 F Method Used: TAG Closed Cup

### Explosive Limits:

LEL: 2.5 % at 77 F UEL: 13.0 % at 77 F

### Autoignition Pt:

870 F

### Fire Fighting Instructions

Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

### Flammable Properties and Hazards

Extremely Flammable!

### Hazardous Combustion Products

carbon monoxide, carbon dioxide

### Extinguishing Media

Use carbon dioxide, dry powder, or foam.

### Unsuitable Extinguishing Media

No data available.

## 6. Accidental Release Measures

### Steps To Be Taken In Case Material Is Released Or Spilled

#### Clean Up:

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. For small spills, take up liquid with sand, earth, or other noncombustible absorbent material and place in a container for disposal. For large spills, dike far ahead of spill and use sand, earth, or other noncombustible absorbent material and then place material in a container for disposal.

#### Waste Disposal:

Dispose in accordance with applicable local, state, and federal regulations.

## 7. Handling and Storage

### Precautions To Be Taken in Handling

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse the container.

### Precautions To Be Taken in Storing

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

## 8. Exposure Controls/Personal Protection

### Respiratory Equipment (Specify Type)

For OSHA controlled work place and other regular users. Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.

### Eye Protection

Safety glasses, chemical goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.

### Protective Gloves

Wear chemical resistant gloves suited for use with acetone. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product.

### Other Protective Clothing

Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.

### Engineering Controls (Ventilation etc.)

Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or your experience slight dizziness, headache, nausea, or eye-watering - STOP - ventilation is inadequate. Leave area immediately.

### Work/Hygienic/Maintenance Practices

A source of clean water should be available in the work area for flushing eyes and skin.

Do not eat, drink, or smoke in the work area.

Wash hands thoroughly after use.

Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use.

Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

## 9. Physical and Chemical Properties

<b>Physical States:</b>	[ ] Gas [ X ] Liquid [ ] Solid
<b>Melting Point:</b>	No data.
<b>Boiling Point:</b>	> 130 F
<b>Autoignition Pt:</b>	870 F
<b>Flash Pt:</b>	-4.0 F Method Used: TAG Closed Cup
<b>Explosive Limits:</b>	LEL: 2.5 % at 77 F UEL: 13.0 % at 77 F
<b>Specific Gravity (Water = 1):</b>	0.789
<b>Density:</b>	6.572 LB/GA at 77 F
<b>Vapor Pressure (vs. Air or mm Hg):</b>	213 MM HG at 77 F
<b>Vapor Density (vs. Air = 1):</b>	No data.
<b>Evaporation Rate:</b>	No data.
<b>Solubility in Water:</b>	No data.
<b>Percent Volatile:</b>	100 % by weight.

### Appearance and Odor

Clear colorless liquid with a characteristic ketone odor.

## 10. Stability and Reactivity

**Stability:** Unstable [ ] Stable [ X ]

### Conditions To Avoid - Instability

No data available.

### Incompatibility - Materials To Avoid

May form explosive mixtures with chromic anhydride, chromyl alcohol, hexachloromelamine, hydrogen peroxide, permonosulfuric acid, potassium tertbutoxide, and thioglycol. Strong oxidizers.

### Hazardous Decomposition Or Byproducts

Decomposition may produce carbon monoxide, carbon dioxide, and other asphyxiants.

**Hazardous Polymerization:** Will occur [ ] Will not occur [ X ]

### Conditions To Avoid - Hazardous Polymerization

No data available.

## 11. Toxicological Information

LD50 Rat oral 10.7 mL/kg (=8450 mg/kg bw); acetone given by gastric intubation to groups of five non-fasted Carworth-Wistar female rats

LD50 Rat oral 9800 mg/kg/ bw

LD50 Rat oral 5800 mg/kg bw

LD50 Mouse oral 3000 mg/kg bw

LD50 Rabbit oral 5340 mg/kg bw

LC50 Rat inhalation exposure 76 mg/L/4 hr

LC50 Rat inhalation 50.1 mg/L/8 hr

LD50 Rabbit dermal 20 mg/kg bw

LD50 Rabbit dermal 20,000 mg/kg bw

LD50 Mouse ip 1,297 mg/kg bw

LD50 Rat iv 5500 mg/kg bw

LD50 Mouse oral 5.2 g/kg

### Chronic Toxicological Effects

No data available.

# MATERIAL SAFETY DATA SHEET

## Klean-Strip Acetone

Page: 5

Printed: 09/22/2011

Revision: 04/14/2009

Supersedes Revision: 11/13/2008

**Hazardous Components (Chemical Name)****CAS #****NTP****IARC****ACGIH****OSHA**

1. Acetone {2-Propanone}

67-64-1

n.a.

n.a.

A4

n.a.

### 12. Ecological Information

No data available.

### 13. Disposal Considerations

**Waste Disposal Method**

Dispose in accordance with applicable local, state and federal regulations.

### 14. Transport Information

**LAND TRANSPORT (US DOT)****DOT Proper Shipping Name** Acetone**DOT Hazard Class:** 3**DOT Hazard Label:** FLAMMABLE LIQUID**UN/NA Number:** UN1090**Packing Group:** II**Additional Transport Information**

The transportation information listed above is suitable for all modes of transportation. IMO/IMDG, ICAO/IATA, 49 CFR

For D.O.T. information, contact W.M. Barr Technical Services at 1-800-398-3892.

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

### 15. Regulatory Information

**US EPA SARA Title III****Hazardous Components (Chemical Name)****CAS #****Sec.302 (EHS)****Sec.304 RQ****Sec.313 (TRI)****Sec.110**

1. Acetone {2-Propanone}

67-64-1

No

Yes 5000 LB

No

Yes

**US EPA CAA, CWA, TSCA****Hazardous Components (Chemical Name)****CAS #****EPA CAA****EPA CWA NPDES****EPA TSCA****CA PROP 65**

1. Acetone {2-Propanone}

67-64-1

HAP, ODC ()

No

Inventory

No

**EPA Hazard Categories:**

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

 Yes  No Acute (immediate) Health Hazard Yes  No Chronic (delayed) Health Hazard Yes  No Fire Hazard Yes  No Sudden Release of Pressure Hazard Yes  No Reactive Hazard

### 16. Other Information

**Company Policy or Disclaimer**

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in

**MATERIAL SAFETY DATA SHEET**  
**Klean-Strip Acetone**

Page: 6

Printed: 09/22/2011

Revision: 04/14/2009

Supercedes Revision: 11/13/2008

accordance with applicable federal, state and local laws and regulations.