



Dependable. Reliable. Professional.

STRETCH & SEAL[®] SELF-FUSING SILICONE TAPE

SPECIALTY TAPE



- Backing:** Self-Fusing Silicone
- Adhesive:** N/A
- Liner:** Clear Cellophane
- Specifications:** UL 510 Classified
Meets A-A-59163 Type I and Type II
- Colors:** Black, Clear, White, Red, Blue
- Available Size:** 1 in x 10 ft (25.4 mm x 3.05 m)

Applications

- Sealing leaking pipes and hoses
- Wrap pipes to protect against rust and corrosion
- Bundling, securing, and clamping applications
- Wrapping and splicing electrical wires and cords
- General purpose waterproofing and sealing uses
- Covering sharp edges and wrapping handles on tools and equipment for safer operation

Features

Benefits

Self-Fusing Silicone	<ul style="list-style-type: none"> • Initially repositionable to achieve a proper seal • Extreme temperature resistance (-65 to 500 °F) • Stretches up to 300% • Apply even in wet conditions for water and air-tight seals • Resists UV and chemical exposure
Non-Adhesive	<ul style="list-style-type: none"> • Cut away to remove • Leaves no messy residue behind
Multi-Color Assortment	<ul style="list-style-type: none"> • Excellent for color coding
UL 510 Classified	<ul style="list-style-type: none"> • Insulates up to 8000 volts per wrap • Meets requirements for most electrical uses

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	20 mils	508 µm	ASTM D-1000
Tensile Strength	700 psi		ASTM D-412
Elongation	300%		ASTM D-412
Operating Temperature	-65 to 500 °F	-54 to 260 °C	
Dielectric Strength	8000V per wrap		
Tear Resistance	65 psi		
Recommended Storage Conditions: 32 - 90 °F at 50% RH ± 2%			
Standard Shelf Life (at 25 °C): 12 months from date of manufacture			

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.



25 Forge Parkway Franklin, MA 02038
1-800-343-7875 Fax 1-800-328-4822
www.nashuatape.com