

Chemsico
 Division of United Industries Corp.
 P.O. Box 142642
 St. Louis, MO 63114-0642

Hazardous Material Identification System-(HMIS)

HEALTH - 1

REACTIVITY - 0

FLAMMABILITY - 2

PERSONAL -
 Rubber gloves

Material Safety Data Sheet

Complies with OSHA's Hazard Communication Standard, 29 CFR 1910.1200

I Trade Name: Spectracide Pruning Seal

Product Type: Aerosol Tree Wound Dressing

EPA Registration Number

Manufacturer

Emergency Telephone No.

N/A

Chemsico
 8494 Chapin Industrial Dr.
 St. Louis, MO 63114

For Chemical Emergency: 1-800-633-2873
 For Information: 1-800-332-5553
 Prepared by: H.L. Pauls
 Date Prepared: October 24, 2004

II Hazardous Ingredients/Identity Information

III Physical and Chemical Characteristics

| Chemical | % | OSHA PEL | ACGIH TLV |
|-----------------------------------|------|----------|-----------------------------|
| Asphalt CAS #64742-93-4 | 16.0 | NE | 5 mg/m ³ (fumes) |
| Xylene CAS #1330-20-7 | 3.0 | 100 ppm | 100 ppm |
| Mineral Spirits CAS #8012-95-1 | 11.0 | 500 ppm | 100 ppm |
| Isobutane CAS # 75-28-5 | 4.0 | NE | NE |
| Propane CAS # 74-98-6 | 6.0 | 1000 ppm | NE |

Appearance and Odor: Coarse fan spray. Black wet film. Asphaltic odor.
Boiling Point: NA
Melting Point: NA
Vapor Pressure: 120 psig @ 54°C/130°F
Specific Gravity: 1.03 (H₂O=1)
Vapor Density: greater than 1 (Air=1)
% Volatile (by vol.): 72%
Solubility in Water: 48%
Evaporation Rate: less than 1 (Butyl Acetate=1)

IV Fire and Explosion Hazard Data

V Reactivity Data

Flash Point: 145°F (TCC)
Flame Extension: 8" (Level 1 Aerosol)
Flammable Limits: N/A
Autoignition Temp: N/A
Fire Extinguishing Media: Water Fog, Carbon Dioxide
 DryChemical
Decomposition Temp: N/A
Special Fire-Fighting Procedures: Keep containers cool. Use equipment or shielding required protecting personnel against bursting, rupturing or venting containers.
Unusual Fire and Explosion Hazards: At elevated temperatures (over 54°C/130°F), containers may vent, rupture or burst. Also see Section V.

Stability: Stable
Polymerization: Will not occur
Conditions to Avoid: Temperatures over 130°F
Incompatible Materials: Strong oxidizers.
Hazardous Decomposition or Byproducts: N/A

VI Health Hazard Data

VII Precautions for Safe Handling and Use

Ingestion (Swallowing): Harmful or fatal if swallowed. **First Aid:** Consult a physician.
Skin Contact: May cause skin irritation. **First Aid:** Wash contaminated skin with soap and water.
Eye Contact: May cause eye irritation. **First Aid:** Flush eyes with plenty of water.
Inhalation Toxicity: Avoid breathing vapors. **First Aid:** Remove to fresh air.
Special Notes: None
Health Conditions Aggravated by Exposure: None Known
Ingredients listed by NTP, OSHA or IARC as Carcinogens or potential carcinogens: None

Steps to be Taken in Case Material is Released or Spilled:
 Avoid breathing vapors. Remove ignition sources. Avoid skin contact with liquid.
Waste Disposal:
 Do not puncture or incinerate containers. Give empty, leaking or full containers to a facility qualified to dispose of pressurized containers.
Handling & Storage Precautions:
 Do not store where temperatures can exceed 54°C/130°F.

VIII Control Measures

IX Transportation Data

Read and follow label directions. They are your best guide to using this product effectively, and give necessary safety precautions to protect your health.

DOT: Consumer Commodity, Hazard Class ORM-D (Limited Quantity Exception)
IMDG: Aerosols (Maximum 1 Liter), Hazard Class 2, UN -1950, Packing Group III
IATA: Aerosols, Flammable (Each Not Exceeding 1 Liter Capacity), Hazard Class 2.1. UN-1950, Packing Group III

The information and statements herein are believed to be reliable but are not to be construed as warranty or representation for which we assume legal responsibility. Users should undertake sufficient verification and testing to determine the suitability for their own particular purpose of any information or products referred to herein. NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE.