

# UL3 FINGERPRINT AND TOUCHSCREEN SMARTLOCK

Simplify Your Safety

4

-



ultralôg

www.u-tec.com

## Welcome To A New Generation Of Keyless

Ultraloq UL3 smart lever lock is designed to be "RealKeyless" for maximum flexibility and convenience. You are free to use fingerprint, code or key to unlock. You have full control of all guests' access and you can simply share a code to let visitors in when you are not there.



### How Does Ultralog Work For You?

#### Tired of forgetting or losing your key?

More options. Fewer headaches. With Ultralog, you have the flexibility to use your finger or code to open your door. Now you will never be locked out again!

#### A rent home owner?


You can manage all renters' access and share them code for their temporary stay. No more key losses. Both you and your renters will have peace of mind.

#### Your employees quit without returning their keys?

No more waste of time and money replacing locks or exchanging keys. Just take few seconds to delete their fingerprints or codes.

#### Keep kids away from where gun is stored and protect your valuables

Our advanced fingerprint technology can keep your kids away from guns and protect valuables in your home office, home to garage door, wine cellar or storage room. Your fingerprint is unique and can never be forgotten or stolen.



### **Designed For DIY Installation**

Battery operated. No wiring. In about 10 minutes, you are ready to go.

#### Specification

Model	Ultraloq UL3	
Sensor	Optical fingerprint sensor	
Sensor Wake Up Mode	Touch	
Scan Area	0.9 x 0.7 inch / 22.9 × 17.8 mm	
Resolution	500 DPI	
Fingerprint Capacity	95	
Code Capacity	95	
Identification Mode	Fingerprint, code	
Identification Time	<0.5 Sec	789.
FRR (False Rejection Rate)	0.001%	1 2 3
FAR (False Acceptance Rate)	0.00001%	4 5 6 7 8 9
Finish	Satin Nickel, aged Bronze, bright Brass	
Case Material	Strong Zinc Alloy	7 8 9 - utratão
Working Voltage	4.5V (3 x AA batteries included)	
Working Temperature	Outside lock body: -31°F (-35°C) to 158°F (70°C)	
	Inside lock body: 14°F (-10°C) to 131°F (55°C)	Introl da
Reversible Handle	Yes	
Dimension	3.5 x 6.3 x 7 inch / 89 x 160 x 178 mm (front panel)	
	3.3 x 6.3 x 7 inch / 84 x 160 x 178 mm (back panel)	
Weight	5.5 Pounds / 2.5 Kilograms	
Door Thickness	1 <sup>3</sup> / <sub>8</sub> "~ 1 <sup>3</sup> / <sub>4</sub> " (35 - 44 mm)	



### It's all about you.

U-tec Group Inc. All rights reserved. U-tec and Ultralog brands and products are trademarked and protected under law in the United States. Unauthorized use is prohibited. Ultralog is sub-brand of U-tec Group Inc.

r I I