

Wall Base Adhesive

7200

SUPERIOR

Roberts® 7200 is a superior performing wall base adhesive with quick grab and rapid set-up for the fast installation of wall base.

Features:

- Excellent holding power
- Strong initial grab for holding heavy rubber wall base
- Fast set-up
- Non-staining

Enviro Friendly:

- Solvent Free
- Zero VOCs (calculated)

Roberts 7200 is a VOC Compliant adhesive and meets the strict requirements of the South Coast Air Quality Management District and may contribute one LEED point as a “Low Emitting Adhesive.”

Roberts 7200 is protected by GoldGuard®, an antimicrobial protection system that inhibits the growth of mold, mildew and odor causing bacteria in both wet and dry adhesive.

Uses: For adhering vinyl, rubber and carpet wall base.

Installation Surfaces: Porous wall surfaces such as gypsum drywall, plaster, brick, concrete block and wood. Roberts 7200 is not recommended over non-porous or painted surfaces.

Surface Preparation: Surface must be structurally sound, dry, smooth, flat and free of excess moisture/alkali and all substances (oil, grease, paint, wall paper, sealers, dust, etc.) that might interfere with the performance of the wall base or its installation. Do not install over non-porous surfaces.

All cracks, holes, high spots and irregularities must be adequately repaired to ensure a smooth, finished appearance. Patching compounds must be suitable for the use application, polymer-fortified and applied according to the manufacturer’s instructions.

General: Concrete and plaster must be properly seasoned and dry prior to installation. Ensure wall surface, wall base and adhesive are fully acclimated prior to installation at the same temperature and humidity level expected during normal use (between 65–95°F with a relative humidity (RH) of no greater than 65%). Refer to wall base manufacturer’s specific recommendations and industry standards.

Materials and area temperature must be between 65–95°F with a maximum RH of 65% for 48 hours before and during installation as well as for 72 hours

afterward. Large temperature or humidity increases or decreases can affect the wall base and performance of the installation. Ensure adequate ventilation during wall base installation.

Physical Characteristics (70°F, RH 50%):

Open Time: Up to 10 minutes

Working Time: Up to 30 minutes

Shelf Life: One year in unopened container

Protect from freezing

Application and Installation: Trim any vinyl wall coverings to 1/4 in. below the top of the wall base with Roberts 10-215 or 10-920-6 knife. Spread adhesive uniformly to the wall or to the back of the wall base. Cartridges: *30 oz.* – Unscrew cap, cut top seal, replace cap, load Roberts 10-981-25 Snozzle and place in Roberts 10-980 30 oz. cartridge gun. *11 oz.* – Cut tip, load Roberts Snozzle and place into 11 oz. cartridge gun. Squeeze gun gently, with even pressure, to apply. Press the wall base firmly in place while the adhesive is still wet (typically within 10 minutes). Note: The amount of time in which you have to place the wall base will vary with temperature and humidity.



FLOORING TYPE	TROWEL SIZE	ROBERTS ITEM #	COVERAGE
Wall Base (4 in.)	Snozzle 	10-981-25	13–22 lin. ft./11 ounces 50–60 lin. ft./30 ounces
Wall Base (4 in.)	3/16 in. x 5/32 in. 	10033	20–24 lin. ft./11 ounces 55–65 lin. ft./30 ounces
Wall Base (4 in.)	1/8 in. x 1/8 in. 	n/a	16–20 lin. ft./11 ounces 45–55 lin. ft./30 ounces

The trowel notches referenced are those typically recommended for wall base. They are normally the minimum size recommended. Consult wall base manufacturer for their specific trowel recommendations. Surface conditions (roughness and porosity of wall surface) and type of wall base will ultimately determine the required trowel notch size and coverage. Ensure 100% transfer of adhesive to the wall base and the wall surface.

Application and Installation (continued):

The higher the temperature and the lower the humidity the faster the adhesive will set.

Use Roberts 10-960 Hand Roller to press and smooth wall base into the adhesive. Always roll back to the starting point to prevent stretching the adhesive.



Clean Up: Fresh adhesive – warm soapy water. Dried adhesive – use mineral spirits sparingly with a clean, white cotton cloth. **DO NOT POUR CLEANER DIRECTLY ONTO FLOORING.**

Refer to material safety data sheet, www.robertsconsolidated.com and industry standards prior to installation for additional information. For installation questions that are not covered in this document please contact our Technical Services Department at (706) 277-5294.

Limited Warranty: Buyer assumes all risk of use, handling and storage of product not in strict accordance with the label, printed literature and industry standards. **This limited warranty excludes all other express or implied warranties including the warranties of merchantability or fitness for a particular use or purpose.** Any implied warranties arising by operation of law are limited to one year. Roberts will not be liable for any incidental or consequential damages. Some states do not allow these limitations or exclusions, therefore they may not apply. This warranty gives you specific legal rights and you may also have other rights which vary from state to state.

Available Sizes:

SIZE	PRODUCT #	UPC
30 Ounces (887 mL)	7200-30C	075378720072
11 Ounces (325 mL)	7200-11C	075378720065

WARNING: EXISTING PAINT MAY CONTAIN LEAD. Unless you have confirmation that the existing paint is not lead containing, do not sand, dry sweep, dry scrape, abrade, drill, saw, bead blast, mechanically chip or pulverize existing paint without taking all appropriate precautions. Refer to local, state and federal guidelines for treatment and removal of lead containing paint. You may also refer to www.epa.gov/lead.