Travertine Repair Kit

1 Product Name

Travertine Repair Kit

2 Manufacturer

Custom Building Products
Technical Services

10400 Pioneer Boulevard, Unit 3 Santa Fe Springs, CA 90670 Customer Support: 800-272-8786 Technical Services: 800-282-8786

Fax: 800- 200-7765

Email: contactus@cbpmail.net www.custombuildingproducts.com

3 Product Description

Travertine Repair Kit is used to repair cracks and holes up to 1/4" (6mm) deep and 1" (25mm) wide. It is designed to repair isolated, damaged areas. By mixing the light and dark fillers, a broad range of colors can be blended to match most colors of travertine.

Key Features

- · Matches most colors
- · Takes less than 5 minutes
- · Easy to use
- Durable Fix

Suitable Tile Types

Honed, Tumbled and Polished Travertine.

Limitations to the Product

Filler provides a textured, non-polished finish. Not for repairing hairline cracks. Not for re-bonding a broken tile. Not for filling entire tile surface.

Packaging

Contents Include:

- Net .5 pint of Light Filler
- Net .5 pint of Dark Filler
- Putty Knife
- · Wooden Sticks
- · Plastic Bag

4 Instructions

General Surface Prep

Clean surface of contaminants using water and a microfiber or lint-free towel. Be sure all loose material and dust is removed from the stone.

Application of Product

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.



In the provided plastic bag, mix together the light filler and dark filler until desired color is achieved. If the color desired matches either the light or the dark, there is no need to mix. Apply the product to the surface using a putty knife, ensuring to pack the repair area with filler. Using the putty knife, scrape the excess material around the repair off the surface. With a damp sponge, in a circular motion gently remove the film off the surface. Do not press firmly or filler will be removed from the repair. Allow the product to fully cure for 24 hours before allowing traffic.

Cleaning of equipment

Clean with soap and water before material dries. Cured material is difficult to clean from surfaces.

Storage

Keep from freezing. Make sure lid is secured tightly with no exposure to air.

Health Precautions

Keep out of reach of children. Wear safety glasses and chemical resistant gloves. Use only in a well-ventilated area. Avoid contact with eyes or prolonged contact with skin. Do not take internally. If eye or skin contact, flush thoroughly with water. If irritation persists, seek medical attention. If ingested, do not induce vomiting. Seek medical attention.

5 Availability & Cost

Net .5 pint of Bone Filler Net .5 pint of Linen Filler

Item Code Chart

TRAVRK



Travertine Repair Kit

6 Product Warranty

Custom® Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another. This warranty is not transferrable.

7 Product Maintenance

Clean with a neutral cleaner such as TileLab Grout & Tile Cleaner.

8 Technical Services Information

For technical assistance, contact Custom® Building Products.

9 Filing System

Additional product information is available from the manufacturer upon request.

10 VOC Content

VOC less than 70 g/L

