# SAFETY DATA SHEET



Date of issue/Date of revision 16 December 2015

**Version 1** 

### **Section 1. Identification**

Product name : GLE3012 GLIDDEN ESSENTIALS INTERIOR LATEX SEMI-GLOSS - BASE 2

Product code : 00380325
Other means of : Not available.

identification

Product type : Liquid.

#### Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications, Used by spraying.

Use of the substance/

mixture

: Coating.

Uses advised against : Not applicable.

Manufacturer : PPG Industries, Inc.

One PPG Place

Pittsburgh, PA 15272

**Emergency telephone** : (4

number

: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) 01-800-00-21-400 (Mexico)

**Technical Phone Number** : 1-800-441-9695 (8:00 am to 5:00 pm EST)

### Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the substance or mixture

: CARCINOGENICITY - Category 2

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 3.6%

**GHS label elements** 

Hazard pictograms :



Signal word : Warning

**Hazard statements**: Suspected of causing cancer.

**Precautionary statements** 

United States Page: 1/12

Date of issue 16 December 2015 Version 1

Product name GLE3012 GLIDDEN ESSENTIALS INTERIOR LATEX SEMI-GLOSS - BASE 2

### Section 2. Hazards identification

**Prevention** 

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing.

**Response** 

: IF exposed or concerned: Get medical attention.

**Storage** 

: Store locked up.

**Disposal** 

 Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label

elements

: Emits toxic fumes when heated.

**Hazards not otherwise** 

classified

: None known.

# Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

**Product name** 

: GLE3012 GLIDDEN ESSENTIALS INTERIOR LATEX SEMI-GLOSS - BASE 2

| Ingredient name  | %          | CAS number |
|------------------|------------|------------|
| Kaolin           | ≥0.1 - <25 | 1332-58-7  |
| titanium dioxide | ≥0.1 - <25 | 13463-67-7 |

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

#### **Description of necessary first aid measures**

**Eye contact** 

: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Skin contact

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion

: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

#### Most important symptoms/effects, acute and delayed

Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.

United States Page: 2/12

Product code 00380325 Date of issue 16 December 2015 Version 1

Product name GLE3012 GLIDDEN ESSENTIALS INTERIOR LATEX SEMI-GLOSS - BASE 2

### Section 4. First aid measures

Inhalation : No known significant effects or critical hazards. Skin contact : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

**Eye contact** : No specific data. Inhalation : No specific data. Skin contact : No specific data. : No specific data. Ingestion

#### Indication of immediate medical attention and special treatment needed, if necessary

: Treat symptomatically. Contact poison treatment specialist immediately if large Notes to physician

quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### See toxicological information (Section 11)

### Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

Hazardous thermal decomposition products : In a fire or if heated, a pressure increase will occur and the container may burst.

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective** equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing

apparatus (SCBA) with a full face-piece operated in positive pressure mode.

**United States** Page: 3/12

Date of issue 16 December 2015 Version 1

Product name GLE3012 GLIDDEN ESSENTIALS INTERIOR LATEX SEMI-GLOSS - BASE 2

### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Special precautions** 

If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

> **United States** Page: 4/12

Date of issue 16 December 2015 Version 1

Product name GLE3012 GLIDDEN ESSENTIALS INTERIOR LATEX SEMI-GLOSS - BASE 2

### Section 7. Handling and storage

including any incompatibilities

Conditions for safe storage, : Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### Section 8. Exposure controls/personal protection

### **Control parameters**

### Occupational exposure limits

| Ingredient name  | Exposure limits                         |  |  |
|------------------|---|--|--|
| Kaolin           | ACGIH TLV (United States, 4/2014).      |  |  |
|                  | TWA: 2 mg/m³ 8 hours. Form: Respirable  |  |  |
|                  | fraction                                |  |  |
|                  | OSHA PEL (United States, 2/2013).       |  |  |
|                  | TWA: 5 mg/m³ 8 hours. Form: Respirable  |  |  |
|                  | fraction                                |  |  |
|                  | TWA: 15 mg/m³ 8 hours. Form: Total dust |  |  |
| titanium dioxide | OSHA PEL (United States, 2/2013).       |  |  |
|                  | TWA: 15 mg/m³ 8 hours. Form: Total dust |  |  |
|                  | ACGIH TLV (United States, 4/2014).      |  |  |
|                  | TWA: 10 mg/m³ 8 hours.                  |  |  |

#### Key to abbreviations

| Α     | = Acceptable Maximum Peak  | S    | <ul> <li>Potential skin absorption</li> </ul>        |
|-------|--|------|--|
| ACGIH | = American Conference of Governmental Industrial Hygienists.       | SR   | <ul> <li>Respiratory sensitization</li> </ul>        |
| С     | = Ceiling Limit  | SS   | = Skin sensitization                                 |
| F     | = Fume   | STEL | <ul> <li>Short term Exposure limit values</li> </ul> |
| IPEL  | = Internal Permissible Exposure Limit                              | TD   | = Total dust   |
| OSHA  | <ul> <li>Occupational Safety and Health Administration.</li> </ul> | TLV  | = Threshold Limit Value                              |
| R     | = Respirable   | TWA  | = Time Weighted Average                              |
| Z     | = OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances |      |  |

### Consult local authorities for acceptable exposure limits.

# procedures

**Recommended monitoring**: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### Appropriate engineering controls

controls

**Environmental exposure** 

- : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

**United States** Page: 5/12

Date of issue 16 December 2015 Version 1

Product name GLE3012 GLIDDEN ESSENTIALS INTERIOR LATEX SEMI-GLOSS - BASE 2

### Section 8. Exposure controls/personal protection

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection **Skin protection** 

: Safety glasses with side shields.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be

noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before

handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected

based on the task being performed and the risks involved and should be approved by a

specialist before handling this product.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers

are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying

with an approved standard if a risk assessment indicates this is necessary.

## Section 9. Physical and chemical properties

**Appearance** 

Physical state : Liquid.
Color : Various

Odor threshold : Characteristic.

Odor threshold : Not available.

pH : !

Melting point: Not available.Boiling point: 100°C (212°F)

Flash point : Closed cup: Not applicable. [Product does not sustain combustion.]

Auto-ignition temperature: Not available.Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive: Upper: 0%

(flammable) limits

**Evaporation rate** : 0.05 (butyl acetate = 1)

Vapor pressure : 3.3 kPa (25 mm Hg) [room temperature]

Vapor density : Not available.

Relative density : 1.08

Density ( lbs / gal ) : 9.01

United States Page: 6/12

Date of issue 16 December 2015 Version 1

Product name GLE3012 GLIDDEN ESSENTIALS INTERIOR LATEX SEMI-GLOSS - BASE 2

: Partially soluble in the following materials: cold water.

: Kinematic (40°C (104°F)): >0.21 cm<sup>2</sup>/s (>21 cSt)

### Section 9. Physical and chemical properties

**Solubility** Partition coefficient: n-

: Not available.

octanol/water

**Viscosity** 

Volatility

: 70% (v/v), 65.018% (w/w)

% Solid. (w/w)

: 34.982

### Section 10. Stability and reactivity

Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** 

: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** 

: When exposed to high temperatures may produce hazardous decomposition products.

Refer to protective measures listed in sections 7 and 8.

**Incompatible materials** 

: Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

**Hazardous decomposition** products

Decomposition products may include the following materials: carbon monoxide, carbon

dioxide, smoke, oxides of nitrogen.

### Section 11. Toxicological information

### Information on toxicological effects

### **Acute toxicity**

| Product/ingredient name | Result    | Species | Dose        | Exposure |
|-------------------------|-----------|---------|-------------|----------|
| Kaolin                  | LD50 Oral | Rat     | >5000 mg/kg | -        |
| titanium dioxide        | LD50 Oral | Rat     | >11 g/kg    | -        |

**Conclusion/Summary** 

: There are no data available on the mixture itself.

**Irritation/Corrosion** 

Conclusion/Summary

Skin : There are no data available on the mixture itself. : There are no data available on the mixture itself. **Eyes** : There are no data available on the mixture itself. Respiratory

**Sensitization** 

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself. Respiratory : There are no data available on the mixture itself.

**Mutagenicity** 

Conclusion/Summary : There are no data available on the mixture itself.

> **United States** Page: 7/12

Date of issue 16 December 2015 Version 1

Product name GLE3012 GLIDDEN ESSENTIALS INTERIOR LATEX SEMI-GLOSS - BASE 2

### **Section 11. Toxicological information**

**Carcinogenicity** 

Conclusion/Summary : There are no data available on the mixture itself.

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|-------------------------|------|------|-----|
| titanium dioxide        | -    | 2B   | -   |

#### Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA:

Not listed/not regulated: -

Reproductive toxicity

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

<u>Target organs</u>: Contains material which causes damage to the following organs: eyes.

Contains material which may cause damage to the following organs: lungs, upper

respiratory tract, stomach.

#### **Aspiration hazard**

Not available.

#### Information on the likely routes of exposure

### Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

### Over-exposure signs/symptoms

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary : There are no data available on the mixture itself. If splashed in the eyes, the liquid may

cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inheletion and degree of purposure and our contest.

inhalation and dermal routes of exposure and eye contact.

#### Short term exposure

United States Page: 8/12

Date of issue 16 December 2015 Version 1

Product name GLE3012 GLIDDEN ESSENTIALS INTERIOR LATEX SEMI-GLOSS - BASE 2

### **Section 11. Toxicological information**

Potential immediate

effects

: There are no data available on the mixture itself.

**Potential delayed effects** 

: There are no data available on the mixture itself.

Long term exposure

**Potential immediate** 

: There are no data available on the mixture itself.

effects

Potential delayed effects : There are no data available on the mixture itself.

Potential chronic health effects

General : No known significant effects or critical hazards.

Carcinogenicity Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity : No known significant effects or critical hazards. **Teratogenicity** : No known significant effects or critical hazards. **Developmental effects** : No known significant effects or critical hazards. **Fertility effects** : No known significant effects or critical hazards.

**Numerical measures of toxicity** 

**Acute toxicity estimates** 

| Route | ATE value      |  |
|-------|----------------|--|
| Oral  | 287362.3 mg/kg |  |

# Section 12. Ecological information

#### **Toxicity**

| Product/ingredient name | Result                           | Species                 | Exposure |
|-------------------------|----------------------------------|-------------------------|----------|
| titanium dioxide        | Acute LC50 >100 mg/l Fresh water | Daphnia - Daphnia magna | 48 hours |

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Not available.

**Mobility in soil** 

Soil/water partition coefficient (Koc)

: Not available.

**United States** Page: 9/12

Date of issue 16 December 2015 Version 1

Product name GLE3012 GLIDDEN ESSENTIALS INTERIOR LATEX SEMI-GLOSS - BASE 2

### Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

### 14. Transport information

|                              | DOT             | IMDG            | IATA            |
|------------------------------|-----------------|-----------------|-----------------|
| UN number                    | Not regulated.  | Not regulated.  | Not regulated.  |
| UN proper shipping name      | -               | -               | -               |
| Transport hazard class (es)  | -               | -               | -               |
| Packing group                | -               | -               | -               |
| <b>Environmental hazards</b> | No.             | No.             | No.             |
| Marine pollutant substances  | Not applicable. | Not applicable. | Not applicable. |

#### **Additional information**

DOT : None identified. **IMDG** : None identified. **IATA** : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

> **United States** Page: 10/12

Date of issue 16 December 2015 Version 1

Product name GLE3012 GLIDDEN ESSENTIALS INTERIOR LATEX SEMI-GLOSS - BASE 2

### Section 15. Regulatory information

### **United States**

United States inventory (TSCA 8b): All components are listed or exempted.

**SARA 302/304** 

SARA 304 RQ : 72098.1 lbs / 32732.5 kg [8006.5 gal / 30307.9 L]

Composition/information on ingredients

|                    |      | SARA 302 TPQ |           | SARA 304 RQ |           |
|--------------------|------|--------------|-----------|-------------|-----------|
| Name               | EHS  | (lbs)        | (gallons) | (lbs)       | (gallons) |
| ammonia, anhydrous | Yes. | 500          | -         | 100         | -         |

#### **SARA 311/312**

Classification : Delayed (chronic) health hazard

Composition/information on ingredients

| Name             | hazard | Sudden<br>release of<br>pressure | Reactive |     | Delayed<br>(chronic)<br>health<br>hazard |
|------------------|--------|----------------------------------|----------|-----|--|
| titanium dioxide | No.    | No.                              | No.      | No. | Yes.                                     |

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

### Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health: 1 \* Flammability: 0 Physical hazards: 0

( \* ) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Health: 1 Flammability: 0 Instability: 0

Date of previous issue : No previous validation

Organization that prepared :

the MSDS

: EHS

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

United States Page: 11/12

Date of issue 16 December 2015 Version 1

Product name GLE3012 GLIDDEN ESSENTIALS INTERIOR LATEX SEMI-GLOSS - BASE 2

### **Section 16. Other information**

UN = United Nations

▼ Indicates information that has changed from previously issued version.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

United States Page: 12/12