MATERIAL SAFETY DATA SHEET



Product Name: Caliwel with BNA - Calcium Hydroxide (Hydrated Lime)

Alistagen Corporation Ten Park Avenue New York, NY 10019

Emergency: National Response Center (800) 424-8802

EPA Reg. No: 73696-2

1. PRODUCT IDENTIFICATION

Product Name: Caliwel with BNA - Hydrated Lime (Calcium Hydroxide) UN/MA#.....N/A DOT Hazard Class.....N/A

2. TYPICAL CHEMICAL COMPOSITION

Recommended Exposure Limits Hazardous Components CAS Number OSHA PEL ACGIH TLV-TWA Mg/m³ Mg/m³ Calcium Hydroxide 1305-62-0 5 5 Titanium Dioxide 15 10 13463-67-7 Magnesium Oxide 1309-48-4 10 (fume) 10 (fume) Calcium Carbonate 1317-65-3 15 15 Silica 7831-86-9 80/(%SiO₂) 5

3. PHYSICAL DATA

Boiling Point	<212 F
Melting Point	
Vapor Pressure	N/A
Vapor Density	N/A
pH	12.4
Solubility in Water	Soluble
Evaporation Rate	Of water

4. FIRE AND EXPLOSION HAZARD DATA (ASTM E84)

Flash Point (F): Flame Spread Index (FSI):	
Smoke Developed Index (SDI):	
Ignition Time (Min:Sec):	
Maximum Temp. at Exposed TC (F°):	560
Time to Maximum Temp. (Min:Sec):	9:42
Flaming on Floor:	None
Afterflame Top (Min:Sec):	None
Afterflame Florr (Min:Sec):	None
LEL:	NA
UEL:	NA
Flammability Classification:	Non-Flammable

DOT: No information Special Fire Fighting Procedures: NA Unusual Fire and Explosion Hazards: NA Fire Extinguishing Media.....Considered non-combustible. Use media appropriate for surrounding fire. Special Fire Fighting Procedures.....Fire fighters should wear full protective clothing and self-contained breathing apparatus.

5. REACTIVITY DATA

Stability.....Stable Incompatibility.....Acids, Chlorinated Phenols + Potassium Nitrate, Moleic Anhydride, Nitroparaffins and Phosphorus. Hazardous Decomposition Products.....None expected Hazardous Polymerization......Will not occur Conditions to Avoid.....N/A

6. SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released: In case of release to the environment, report spills to the National Response Center 1 -800-424-8802

Suggested Local Action: Contain spill. Prevent large quantities from contacting vegetation or domestic and natural water sources. If material is not contaminated place in appropriate DOT approved containers for disposal.

Waste Disposal Method: (ERA Waste identification #: N/A) If contaminated with other materials, the nature and extent of contamination may require the use of specialized disposal methods. If disposal is necessary, comply with all local, state, and federal regulations. Contact your local EPA office for help.

For Hazardous Waste Regulation: call 1-800-424-9346 - The RCRA Hotline.

7. HEALTH HAZARD DATA

Inhalation: In a confined area vapors in high concentration may provoke headache or dizziness. Skin Contact: May cause irritation, particular on damp skin. Repeated or prolonged contact could lead to dermatitis. Wash affected area with mild soap and water.

Eye Contact: May cause irritation and conjunctivitis. Flush with large amounts of water for at least 15 minutes, while rolling eyeball and lifting eyelid. Get medical attention.

Ingestion: Give milk, egg whites, or water to

8. EMERGENCY AND FIRST AID PROCEDURE

Inhalation: Remove from exposure. If breathing is difficult or has stopped, administer artificial respiration or oxygen as indicated. Immediately seek medical aid.

Skin Contact: Wash thoroughly with soap and water. Seek medical aid.

Eye Contact: Flush immediately with large amounts of water, lifting the lower and upper lids occasionally. Seek medical help.

Ingestion: Give 1 -2 large glasses of water or milk. Immediately seek medical aid. Never give liquids to an unconscious person.

Carcinogenicity: Not listed as a carcinogen by NTP, (ARC, or OSHA)

Routes of Entry: Inhalation, Skin and Eye Contact if handled in such a manner that dust is generated.

Effects of Overexposure: As sold, this product is not anticipated to pose an acute or significant health hazard. However, if subjected to dust generating processes, adverse health effects may occur.

9. SPECIAL PROTECTION INFORMATION

Respiratory: Respiratory protection approved by NIOSH/MSHA for protection against dust and spray mist. Appropriate respiration selection depends on the type and magnitude of exposure. Skin: Clean, body-covering clothing should be worn to prevent irritation in situation where direct contact with product may occur or dust levels are excessive.

Eyes: Employees should be required to wear chemical safety splash goggles in situations where direct contact with the product may result in eye injury.

Ventilation: Local exhaust ventilation should be used to control worker exposure to below recommended Permissible Exposure Levels (PEL).

Other Protective Equipment: Emergency eye wash stations and deluge safety showers should be available in the work areas.

10. SPECIAL PRECAUTIONS

Precaution to be taken in handling and storage: Store in a cool, dry location. Keep out of reach of children and pets.

THIS INFORMATION IS TAKEN FROM SOURCES OR BASED UPON DATE BELIEVED TO BE RELIABLE; HOWEVER, ALISTAGEN CORPORATION, MAKES NO WARRANTY AS TO THE ABSOLUTE CORRECTNESS OR SUFFICIENCY OF ANY OF THE FOREGOING OR THAT ADDITIONAL OR OTHER MEASURES MAY NOT BE REQUIRED UNDER PARTICULAR CONDITIONS.